

# **NON-Hazardous Chemical, NON-Dangerous Goods**

#### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

# Product name: Casali Reinforced Bitumen Sheets for Roof Waterproofing

Recommended use: Waterproofing membrane.

Supplier: APTC Australia Pty Ltd

**ABN:** 61 058 678 961 **Street Address:** 18 - 22 Pacific Drive Keysborough VIC 3173

**Telephone:** 1300 394 239

Facsimile: 1300 394 239

Emergency Telephone number: 1300 394 239 (6:30 am to 4:30 pm, Mon - Fri, AEST)

#### 2. HAZARDS IDENTIFICATION

Based on available information, this material is not classified as hazardous according to criteria of Safe Work Australia.

Poison Schedule: Not Applicable

#### DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

#### 3. COMPOSITION INFORMATION

CHEMICAL ENTITY

CAS NO
PROPORTION

Ingredients determined to be Non-Hazardous

100 %

100%

## 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Not applicable as supplied.

**Skin Contact:** Not applicable as supplied.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible

precaution to seek medical advice.

**Ingestion:** Not applicable as supplied.

Product Name: Casali Reinforced Bitumen Sheets for Roof Reference No: BL007101

Waterproofing

Issued: 2019-07-26 Version: 1.0 Page 1 of 6



PPE for First Aiders: Wear safety shoes, overalls.

Notes to physician: Treat symptomatically.

### **5. FIRE FIGHTING MEASURES**

Hazchem Code: Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

**Fire fighting further advice:** On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination. For small particles, sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

#### 7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### National occupational exposure limits:

		TWA		STEL	
	ppm	mg/m3	ppm	mg/m3	
Bitumen fumes	_	5	-	-	-

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as

Product Name: Casali Reinforced Bitumen Sheets for Roof Reference No: BL007101

Waterproofing

Issued: 2019-07-26 Version: 1.0 Page 2 of 6



fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Avoid generating and inhaling dusts. Use with local exhaust ventilation or while wearing dust mask.

Personal Protection Equipment: SAFETY SHOES, OVERALLS.

When handling material wear standard safety equipment – including safety shoes.

When cutting or mechanically abrading material wear safety shoes, overalls, safety glasses. Avoid generating and inhaling dust or fumes. If dust or fumes exists, wear a dust mask / respirator conforming to the requirements of AS/NZS 1715 or AS/NZS 1716. Protective gloves should be worn when cutting rolls and as per site regulations, however, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust or fumes.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Membrane rolls
Colour: Coloured
Odour: Slight bitumen

Solubility: Insoluble in water
Density: 1 - 1.5 kg/L
Relative Vapour Density (air=1): N App
Vapour Pressure (20 °C): N App

Flash Point (°C): >230 (Bitumen)

Flammability Limits (%): N Av

Autoignition Temperature (°C): >485 (Bitumen)

Melting Point/Range (°C): >100

Boiling Point/Range (°C): >470 (Bitumen)

pH: N App Viscosity: N App Total VOC (g/Litre): N Av

> (Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

#### 10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

Product Name: Casali Reinforced Bitumen Sheets for Roof Reference No: BL007101

Waterproofing

Issued: 2019-07-26 Version: 1.0 Page 3 of 6



Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

#### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

**Inhalation:** Not applicable as supplied. If material is cut or mechanically abraded may be an irritant to mucous membranes and respiratory tract.

**Skin contact:** Not applicable as supplied. If material is cut or mechanically abraded, contact with skin may result in irritation.

**Ingestion:** Not applicable as supplied. If material is cut or mechanically abraded swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Eye contact:** Not applicable as supplied. If material is cut or mechanically abraded may be an eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

#### **Acute toxicity**

**Inhalation:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 5 mg/L

**Skin contact:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

**Ingestion:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

# **Chronic Toxicity**

**Mutagenicity:** This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

**Specific target organ toxicity (repeat exposure):** This material has been classified as non-hazardous.

Product Name: Casali Reinforced Bitumen Sheets for Roof Reference No: BL007101

Waterproofing

Issued: 2019-07-26 Version: 1.0 Page 4 of 6



#### 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log  $K_{ow}$  < 4.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

# 14. TRANSPORT INFORMATION

#### **ROAD AND RAIL TRANSPORT**

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

#### MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

#### **AIR TRANSPORT**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

## 15. REGULATORY INFORMATION

#### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

## This material/constituent(s) is covered by the following requirements:

• All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

Product Name: Casali Reinforced Bitumen Sheets for Roof Reference No: BL007101

Waterproofing

Issued: 2019-07-26 Version: 1.0 Page 5 of 6



#### **16. OTHER INFORMATION**

Reason for issue: First Issue

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

Product Name: Casali Reinforced Bitumen Sheets for Roof Reference No: BL007101

Waterproofing

Issued: 2019-07-26 Version: 1.0 Page 6 of 6