

Manufacturers of UTHANE Polyurethane Coatings 14a Williamson Road, Ingleburn, N.S.W., 2565 Phone +612 9729-2000 1300 BCC OAT (222 628) Email: <u>orders@bccoatings.com.au</u> Text Orders/Enquiries: 0487 800 090

TECHNICAL DATA SHEET

PRODUCT BC2560 SPRAY PEEL COAT

DESCRIPTION	 BC2560 Spray Peel Coat is a specialty coating for use in spray booths, kitchens, doors & steel. BC2560 Spray Peel Coat is a single pack very flexible coating, moisture resistant, long lasting and very easy to apply. It is ideally used for the protection of spray booths, kitchen doors as well as cast metal. This product gives long term protection from over spray, moisture and dust. 		
PROPERTIES			
TECHNICAL DATA:	Heat Resistant: Toxicity: Thinning & Clean Theoretical Covers	To 100° Respirator recommended when spraying. Dry film is not toxic. Up: MEK at 10% age: 10 sq. m. / Litre of thinned material at 40um DFT	
<u>COLOR</u>	Clear, Light Blue & White.		
<u>GLOSS LEVEL</u>	Not Applicable.		
APPLICATIONS	BC2560 Spray Peel Coat can be applied over steel, timber, galvanised iron, aluminium and glass.		

APPLICATIONBest applied by spray gun but can also be dipped.
Please use the method best suited to your requirements and skill.
Recommended spraying pressure is 40 – 45 PSI with a spray gun nozzle of
1.8mm to 2.00mm

Apply in calm fine weather conditions and only during daylight hours. Cease painting 2 hours before sunset or if weather changes are forecast. Provide adequate ventilation during use.

<u>SURFACE PREPARATION</u>: Make sure surface to be coated is cleaned, dry and dust free.



BC2560 SPRAY PEEL COAT

<u>DRYING</u>	Drying Time Touch Dry	:	@ 25° & RH 60% 30 minutes		
LOW TEMPERATURES AND HEAVY FILM BUILDS WILL RETARD DRYING TIMES.					
PACKAGING	20 Litres.				
<u>SHELF LIFE</u>	24 months in original sealed containers				
<u>HEALTH & SAFETY</u>	Before handling, refe Information.	r to the	Material Safety Data Sheet for health and safety		

This data sheet is based on information in BC Coatings possession at the date of issue. BC Coatings supplies its products only on condition that the consumer is satisfied as to the performance of the product in meeting his particular requirements