



## TECHNICAL DATA SHEET

### PRODUCT

### BC320 GRAFFITI REMOVER

### DESCRIPTION

BC320 Graffiti Remover is a scientifically developed blend of water soluble non-flammable low toxicity environmentally friendly ingredients designed to remove graffiti or stubborn stains from a multitude of substrates.

### FEATURES

BC320 has been designed to remove

- Aerosol spray paints (Acrylic and Enamel)
- Permanent Marking Pen inks
- Fluorescent Paints
- Bitumen Stains
- Crayon
- Lipstick
- Adhesive Residue
- Ceramic Anilox Rolls
- Other Printing Rolls and Press components

**Note:** When treating a painted surface it is advisable to test an inconspicuous area first, as the BC320 may have a damaging effect on some Paints.

### APPLICATION METHODS

The most effective method of application is trigger spray. Other methods of cleaning would be soft cloth such as cotton, non-synthetic brushes or soft scourers. Larger exterior areas can be cleaned with Pressure washers. It is advisable to treat the affected area as soon as possible as markings are easily removed if treated within 24 hours.

### RIGID UNPAINTED SURFACES

Apply BC320 by spray or a soft cloth directly to the surface. Allow a short time to activate the graffiti and wipe off with a clean dry cloth. Water rinse or wipe with a damp cloth and allow to dry. If the graffiti is aged and difficult to remove, several applications of BC320 may need to be carried out.

### POROUS SURFACES

Apply BC320 by spray and with a brush, work the BC320 into the surface. Leave for 10 minutes and wipe off with a clean cloth. For exterior surfaces, the residue can be cleaned with a pressure spray.



Manufacturers of UTHANE Polyurethane Coatings  
14A Williamson Road, Ingleburn N.S.W 2565  
Phone +612 9729-2000 1300 BCC OAT (222 628)  
Email: [orders@bccoatings.com.au](mailto:orders@bccoatings.com.au)  
Text Orders/Enquiries: 0487 800 090

## TECHNICAL DATA SHEET

### BC320 GRAFFITI REMOVER

#### PREVIOUSLY PAINTED AND SENSITIVE

##### SURFACES (Such as some Plastics or Fabrics)

Test a small inconspicuous area first to see if the paint is effected by the BC320. Apply the BC320 to the surface and wipe off immediately with a clean cloth. Repeat until the graffiti is removed.

**Note:** some graffiti may attack the painted surface leaving a “shadow” effect on the coated surface. BC320 will not remove this ingrained “shadow”.

#### BITUMEN STAINS (Auto body Paintwork)

Treat as per previously painted surfaces

#### CERAMIC ANILOX ROLLS

Spray a liberal amount of BC320 onto a soft cloth and work it into the stained surface keeping it wet for two to three minutes. Wipe the area clean with an alcohol based solvent such as Methylated Spirits or Isopropanol. Apply a second rinse with the solvent and dry to provide a clean working surface. Other Printing rolls can be cleaned in the same manner.

This data sheet is based on information in BC Coatings possession at date of issue. BC Coatings supplies its products only on condition that the consumer is satisfied as to the performance of the product in meeting his particular requirements.