



Manufacturers of UTHANE Polyurethane Coatings
14a Williamson Road, Ingleburn, N.S.W., 2565
Phone +612 9729-2000 1300 BCC OAT (222 628)
Email: orders@bcccoatings.com.au
Text Orders/Enquiries: 0487 800 090

TECHINAL DATA SHEET

BC123 SLIPSTREAM – ANTIFOULING CUPROUS OXIDE BASED

SLIPSTREAM is a high strength, ablative antifouling that helps to minimise paint build up and marine organism growth.

BC Coatings has formulated a product that not only offers reduced maintenance but also helps with performance due to less growth.

SLIPSTREAM comes in 2 different colours.

It can be brushed, roller and where permitted, can be sprayed.

For more information contact BC Coatings.

DESCRIPTION

An outstanding cuprous oxide based, ablative type antifouling formulated to give the best level of protection against all types of marine growth.

USES

For below waterline areas on vessels that are continuously immersed in salt water.

PROPERTIES

COLOURS	Black & Blue.
FINISH	Low Sheen / Satin.
COVERAGE	7sq. metres / litre should not be exceeded.
DRYING TIME	Touch dry in 2 hours at 50% relative humidity @ 25 ° C.
RE-COATING	After 4 hours, 2 coats recommended.
THINNING	In hot water may be thinned by using SP thinners up to 10%.

This data sheet is based on information in BC Coatings possession at date of issue.
BC Coatings supplies its products only on condition that the consumer is satisfied as to the performance of the product in meeting his particular requirements.