

DIVERSEY GLADE FLORAL BOUQUET

Chemwatch Material Safety Data Sheet (REVIEW)
Issue Date: 25-Jan-2012
X9317SP

Hazard Alert Code: HIGH

CHEMWATCH 16-8302
Version No:4.1.1.1
Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

DIVERSEY GLADE FLORAL BOUQUET

PROPER SHIPPING NAME

AEROSOLS

PRODUCT NUMBERS

1001328

PRODUCT USE

Application is by spray atomisation from a hand held aerosol pack.
Air freshener.

SUPPLIER


Company: JohnsonDiversey
Address:
29 Chifley Street
Smithfield
NSW, 2164
Australia
Telephone: +61 2 9757 0300
Telephone: 1800 251 738 (AUS)
Emergency Tel: **1800 033 111**
Fax: +61 2 9725 5767
Email: aucustserv@diverse.com

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

DANGEROUS GOODS. NON-HAZARDOUS SUBSTANCE. According to NOHSC Criteria, and ADG Code.

CHEMWATCH HAZARD RATINGS



RISK

- Extremely flammable.
- Risk of explosion if heated under confinement.
- Vapours may cause drowsiness and dizziness.
- Inhalation and/or ingestion may produce health damage*.
- Cumulative effects may result following exposure*.

SAFETY

- Keep away from sources of ignition. No smoking.
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.

continued...

DIVERSEY GLADE FLORAL BOUQUET

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 25-Jan-2012

X9317SP

CHEMWATCH 16-8302

Version No:4.1.1.1

Page 2 of 8

Section 2 - HAZARDS IDENTIFICATION

- May produce discomfort of the respiratory system*.
- Repeated exposure potentially causes skin dryness and cracking*.
- * (limited evidence).
- Keep container tightly closed.
- This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
emulsifier		<10
perfume		<10
water	7732-18-5	>60
LPG (liquefied petroleum gas)	68476-85-7.	10-30

Section 4 - FIRST AID MEASURES

SWALLOWED

- Not considered a normal route of entry.

EYE

- If aerosols come in contact with the eyes:
 - Immediately hold the eyelids apart and flush the eye with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Seek medical attention without delay; if pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If solids or aerosol mists are deposited upon the skin:
 - Flush skin and hair with running water (and soap if available).
 - Remove any adhering solids with industrial skin cleansing cream.
 - DO NOT use solvents.
 - Seek medical attention in the event of irritation.

INHALED

- If aerosols, fumes or combustion products are inhaled:
 - Remove to fresh air.
 - Lay patient down. Keep warm and rested.
 - Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- SMALL FIRE:
 - Water spray, dry chemical or CO2
- LARGE FIRE:
 - Water spray or fog.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

continued...

DIVERSEY GLADE FLORAL BOUQUET

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 25-Jan-2012

X9317SP

CHEMWATCH 16-8302

Version No:4.1.1.1

Page 3 of 8

Section 5 - FIRE FIGHTING MEASURES

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat or flame.
 - Vapour forms an explosive mixture with air.
 - Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
- Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.
- Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

2YE

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.

MAJOR SPILLS

- Remove leaking cylinders to a safe place if possible.
- Release pressure under safe, controlled conditions by opening the valve.
- DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Radon and its radioactive decay products are hazardous if inhaled or ingested.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.

continued...

DIVERSEY GLADE FLORAL BOUQUET

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 25-Jan-2012

X9317SP

CHEMWATCH 16-8302

Version No:4.1.1.1

Page 4 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
Australia Exposure Standards	LPG (liquefied petroleum gas) (LPG (liquified petroleum gas))	1000	1800						

The following materials had no OELs on our records

• water:

CAS:7732- 18- 5

MATERIAL DATA

DIVERSEY GLADE FLORAL BOUQUET:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

WATER:

No exposure limits set by NOHSC or ACGIH.

LPG (LIQUEFIED PETROLEUM GAS):

For liquefied petroleum gases (LPG):

TLV TWA: 1000 ppm, 1800 mg/m³ (as LPG)

ES TWA: 1000 ppm, 1800 mg/m³ (as LPG)

OES TWA: 1000 ppm, 1750 mg/m³; STEL: 1250 ppm, 2180 mg/m³ (as LPG)

IDLH Level: 2000 ppm (lower explosive limit)

No chronic systemic effects have been reported from occupational exposure to LPG. The TLV-TWA is based on good hygiene practices and is thought to minimise the risk of fire or explosion.

Odour Safety Factor(OSF)

OSF=0.16 (hydrocarbon propellant).

For ethyl mercaptan:

Odour Threshold: 0.000098-0.0002 ppm (detection), 0.0004 ppm (recognition)

NOTE: Detector tubes for mercaptan, measuring in excess of 0.5 ppm (as ethyl mercaptan) are commercially available.

Ethyl mercaptan causes irritation of mucous membranes of the lips, mouth and nose in humans exposed at 4 ppm.

For butane:

Odour Threshold Value: 2591 ppm (recognition)

Butane in common with other homologues in the straight chain saturated aliphatic hydrocarbon series is not characterised by its toxicity but by its narcosis-inducing effects at high concentrations. The TLV is based on analogy with pentane by comparing their lower explosive limits in air.

Odour Safety Factor(OSF)

OSF=0.22 (n-BUTANE).

For thiols:

REL (thiols): 0.05 ppm/15 min (as n-alkane mono) NIOSH

NOTE: Detector tubes for mercaptan, measuring in excess of 0.05 ppm (as ethyl mercaptan) are commercially available.

For propane

Odour Safety Factor(OSF)

OSF=0.16 (PROPANE).

PERSONAL PROTECTION



RESPIRATOR

•Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

continued...

DIVERSEY GLADE FLORAL BOUQUET

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 25-Jan-2012

X9317SP

CHEMWATCH 16-8302

Version No:4.1.1.1

Page 5 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE

■ No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures:

- Safety glasses with side shields.
- NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

HANDS/FEET

• No special equipment needed when handling small quantities.

• OTHERWISE:

- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.

OTHER

■ No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
 - Skin cleansing cream.
 - Eyewash unit.
 - Do not spray on hot surfaces.
 - The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.
 - Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.
- BREITHERICK: Handbook of Reactive Chemical Hazards.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Supplied as an aerosol pack. Contents under PRESSURE.

Clear liquid with a mild fragrant odour; miscible with water.

PHYSICAL PROPERTIES

Liquid.

Gas.

Mixes with water.

State	Liquid	Molecular Weight	Not Available
Melting Range (°C)	<0	Viscosity	Not Available
Boiling Range (°C)	>100	Solubility in water (g/L)	Miscible
Flash Point (°C)	<20 (propellant)	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	2.4 @20C
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.76
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	>60 (water)	Evaporation Rate	as for water

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Elevated temperatures.

continued...

DIVERSEY GLADE FLORAL BOUQUET

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 25-Jan-2012

X9317SP

CHEMWATCH 16-8302

Version No:4.1.1.1

Page 6 of 8

Section 10 - STABILITY AND REACTIVITY

- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be damaging to the health of the individual.

Not normally a hazard due to physical form of product.

Considered an unlikely route of entry in commercial/industrial environments.

EYE

- Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

Not considered to be a risk because of the extreme volatility of the gas.

SKIN

- The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

Spray mist may produce discomfort.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. Vapour is heavier than air and may displace and replace air in breathing zone, acting as a simple asphyxiant.

WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

Exposure to hydrocarbons may result in irregularity of heart beat. Symptoms of moderate poisoning may include dizziness, headache, nausea. Serious poisoning can result in decreased respiratory function, this may lead to unconsciousness and death. C4 hydrocarbons are especially dangerous to the nervous system. Inhalation of petroleum gases (partly due to olefin impurities) can induce sleep. Serious cases can result in cyanosis due to reduced oxygen concentration and hence asphyxiation, with symptoms of fast breathing, mental dullness, inco-ordination, poor judgment, nausea and vomiting; leading to unconsciousness and death.

CHRONIC HEALTH EFFECTS

- Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

TOXICITY AND IRRITATION

- Not available. Refer to individual constituents.

continued...

DIVERSEY GLADE FLORAL BOUQUET

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet (REVIEW)

Issue Date: 25-Jan-2012

X9317SP

CHEMWATCH 16-8302

Version No:4.1.1.1

Page 7 of 8

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
LPG (liquefied petroleum gas)	No Data Available	No Data Available		

Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE GAS

HAZCHEM:

2YE (ADG7)

Land Transport UNDG:

Class or division	2.1	Subsidiary risk:	None
UN No.:	1950	UN packing group:	None
Shipping Name:	AEROSOLS		

Air Transport IATA:

ICAO/IATA Class:	2.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1950	Packing Group:	-
Special provisions:	A145		
Cargo Only			
Packing Instructions:	203	Maximum Qty/Pack:	150 kg
Passenger and Cargo		Passenger and Cargo	
Packing Instructions:	203	Maximum Qty/Pack:	75 kg
Passenger and Cargo Limited Quantity		Passenger and Cargo Limited Quantity	
Packing Instructions:	Y203	Maximum Qty/Pack:	30 kg G

Shipping name:AEROSOLS

Maritime Transport IMDG:

IMDG Class:	2	IMDG Subrisk:	SP63
UN Number:	1950	Packing Group:	None
EMS Number:	F-D,S-U	Special provisions:	63 190 277 327 344 959
Limited Quantities:	See SP277		
Shipping name:	AEROSOLS		

continued...

DIVERSEY GLADE FLORAL BOUQUET

Chemwatch Material Safety Data Sheet (REVIEW)
Issue Date: 25-Jan-2012
X9317SP

Hazard Alert Code: HIGH

CHEMWATCH 16-8302
Version No:4.1.1.1
Page 8 of 8

Section 14 - TRANSPORTATION INFORMATION

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

None

REGULATIONS

Regulations for ingredients

water (CAS: 7732-18-5) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway"

LPG (liquefied petroleum gas) (CAS: 68476-85-7) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD List of High Production Volume (HPV) Chemicals"

No data for Diversey Glade Floral Bouquet (CW: 16-8302)

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 25-Jan-2012
Print Date: 6-Aug-2012

This is the end of the MSDS.