

→ DESCRIPTION

A low-foaming non-caustic powder used for CIP (Clean-in-Place) applications in wineries to remove residue, staining and tartrate deposits.

→ BENEFITS

- Low-hazard product that is much safer than caustic-based cleaners
- Requires less PPE when using
- Fast rinsing
- Contains a special low foam surfactant to give rapid wetting and penetration of tartrate deposits
- Assists with brown film removal, especially if used during vintage
- Low foaming even when used through high pressure units such as Gamajet and Fury as well as CIP systems
- High levels of sequestrant gives rapid removal of built-up scale in tanks and equipment
- Will not form a hard residue if left to dry on hot surfaces
- Does not contain silicates which can block filling heads
- Can be used in recirculating systems

→ APPLICATION

Vincirc is recommended for cleaning tanks in wineries to remove light to medium tartrate deposits. It can also be used to clean inside wine tankers.



→ TECHNICAL INFO

Fragrance	Colour	Form	pH Level
No added fragrance	White	Powder	10.8-11.4 at 1% w/w

→ AVAILABLE IN

Product	Code
15kg Pail	C29996
200kg	C10469



RECYCLABLE PACKAGING

→ DIRECTIONS FOR USE

TARTRATE SOILING

Use the amounts shown below usage guide. After a while, the operators will be able to establish the optimum amounts needed for each tank. The thickness of the tartrate deposit can vary dependant on the age of the wine, type, how long it has been in the tank and process in use such as cold stabilisation. Waste storage tanks, for lees and must, may require higher concentrations of Vincirc.

Light: Small crystals up to 2mm scattered over the surface with a lot of uncovered stainless steel still exposed.

Medium: Small crystals up to 2mm covering most of the surface.

Heavy: Larger crystals over 2mm covering most, or all, of the surface.

Tank Size (L)	Light Deposit (kg)	Medium Deposit (kg)	Heavy Deposit
10,000	3kg	4kg	6kg
20,000	4kg	5kg	8kg
50,000	6kg	10kg	15kg
100,000	10kg	15kg	22kg
200,000	15kg	20kg	30kg
500,000	20kg	30kg	45kg

More directions over page →



→ DIRECTIONS FOR USE

TARTRATE SOILING

1. Mix with warm water to form a thin slurry before adding the tank. If added directly to the tank, the powder tends to clump, increasing the dissolution time. If the water is normally added to a 200L drum, then pumped in. Simply sprinkle the Vincirc into the drum whilst filling and then pump with the tank.
2. Circulate with sprayball or other system for 20-30 minutes.
3. Monitor by testing pH and by visual assessment. Maintain pH above 9 to ensure continued effectiveness.
4. Drain tank when clean, then rinse with water and finally a mildly acidic rinse. Vincirc is a cleaner not a sanitiser. If sanitising is required, sanitise tank using your preferred method.

TANK CLEANING

Use Vincirc at dilutions from 1kg/100L (1% w/v) to 2kg/100L (2% w/v) dependant on the degree of soiling. Warm water is recommended for slurry preparation before adding to the tank.

RE-CIRCULATING SYSTEMS

Use Vincirc at dilutions from 2kg/100L (1% w/v) to 4kg/100L (4% w/v), dependant on the degree of soiling.



A Safety Data Sheet for this product can be found at dominant.com.au or use the QR code



SAFETY INFORMATION

RECOMMENDED PPE