



## Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	11-6897-0	<b>Version number:</b>	11.00
<b>Issue Date:</b>	14/03/2022	<b>Supersedes date:</b>	10/11/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M (TM) 700 Adhesive Cleaner and Solvent

#### Product Identification Numbers

AS-0104-2629-9

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive Cleaner. Industrial use.

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1.  
Gas under pressure: Liquefied gas.  
Skin Corrosion/Irritation: Category 2.  
Specific Target Organ Toxicity (single exposure): Category 1.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

**Signal word**

Danger

**Symbols**

Flame | Gas cylinder | Exclamation mark | Health Hazard |

**Pictograms**



**Hazard statements**

- H222 Extremely flammable aerosol.
- H229 Pressurised container: may burst if heated.
- H280 Contains gas under pressure; may explode if heated.
  
- H315 Causes skin irritation.
  
- H370 Causes damage to organs: cardiovascular system.

**Precautionary statements**

**Prevention:**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.

**Response:**

- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308 + P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.
- P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

**Disposal:**

- P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards**

3M Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

**2.4. Other hazards which do not result in classification**

May be harmful if inhaled.

May cause drowsiness or dizziness.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Light aromatic solvent naphtha (petroleum)	64742-95-6	70 - 90
Butane	106-97-8	20 - 30
Propane	74-98-6	< 10

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation**

Remove person to fresh air. Get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

Substance

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

Hazchem Code: 2YE

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidising agents.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Butane	106-97-8	ACGIH	STEL:1000 ppm	
Butane	106-97-8	Australia OELs	TWA(8 hours):1900 mg/m <sup>3</sup> (800 ppm)	
Natural gas	106-97-8	ACGIH	Limit value not established:	asphyxiant
Propane	74-98-6	ACGIH	Limit value not established:	asphyxiant
Propane	74-98-6	Australia OELs	Limit value not established:	Explosion hazard, asphyxiant

ACGIH : American Conference of Governmental Industrial Hygienists  
AIHA : American Industrial Hygiene Association  
Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment  
CMRG : Chemical Manufacturer's Recommended Guidelines  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling  
Sen: Sensitiser  
Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Local exhaust ventilation with a minimum capture velocity of 100 linear feet per minute (0.5 m/sec) should be provided for applications at or above the boiling temperature.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:  
Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Select and use gloves according to AS/NZ 2161.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:  
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates  
Half facepiece or full facepiece supplied-air respirator.

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol

<b>Colour</b>	Colourless
<b>Odour</b>	Hydrocarbon, Solvent
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>Not applicable.</i>
<b>Melting point/Freezing point</b>	<i>Not applicable.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	>=88 °C [ <i>Test Method:Estimated</i> ] [ <i>Details:Light aromatic solvent naphtha</i> ]
<b>Flash point</b>	-1 °C [ <i>Test Method:Closed Cup</i> ] [ <i>Details:Liquid portion</i> ]
<b>Evaporation rate</b>	Approximately 1 [ <i>Ref Std:BUOAC=1</i> ] <i>No data available.</i>
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Vapor Density and/or Relative Vapor Density</b>	Approximately [ <i>Ref Std:AIR=1</i> ] <i>No data available.</i>
<b>Density</b>	0.79 g/ml
<b>Relative density</b>	0.79 [ <i>Ref Std:WATER=1</i> ]
<b>Water solubility</b>	<i>No data available.</i>
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity/Kinematic Viscosity</b>	Approximately 100 mPa-s
<b>Volatile organic compounds (VOC)</b>	700 g/l
<b>Percent volatile</b>	Approximately 100 %
<b>VOC less H2O &amp; exempt solvents</b>	<i>No data available.</i>

**Nanoparticles**

This material does not contain nanoparticles.

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3. Conditions to avoid**

Heat.

Sparks and/or flames.

Static discharge (Solids can generate static electricity charges when transferred and in mixing operations sufficient to be an ignition source.)

**10.4. Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.5 Incompatible materials**

Not determined

**10.6 Hazardous decomposition products****Substance**

None known.

**Condition**

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May be harmful if inhaled. Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

#### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >20 - ≤50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Inhalation-Vapour (4 hours)	Rat	LC50 > 5.2 mg/l
Light aromatic solvent naphtha (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Butane	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm

**3M (TM) 700 Adhesive Cleaner and Solvent**

Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
---------	--------------------------	-----	--------------------

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Light aromatic solvent naphtha (petroleum)	Rabbit	Irritant
Butane	Professional judgement	No significant irritation
Propane	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Light aromatic solvent naphtha (petroleum)	Rabbit	Mild irritant
Butane	Rabbit	No significant irritation
Propane	Rabbit	Mild irritant

**Skin Sensitisation**

Name	Species	Value
Light aromatic solvent naphtha (petroleum)	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Butane	In Vitro	Not mutagenic
Propane	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Light aromatic solvent naphtha (petroleum)	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for female reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for male reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for development	Rat	NOAEL 500 ppm	2 generation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------



Light aromatic solvent naphtha (petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Butane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Butane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Butane	Inhalation	heart	Not classified	Dog	NOAEL 5,000 ppm	25 minutes
Butane	Inhalation	respiratory irritation	Not classified	Rabbit	NOAEL Not available	
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Butane	Inhalation	kidney and/or bladder   blood	Not classified	Rat	NOAEL 4,489 ppm	90 days

**Aspiration Hazard**

Name	Value
Light aromatic solvent naphtha (petroleum)	Aspiration hazard

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

**Chronic aquatic hazard:**

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Light aromatic solvent naphtha (petroleum)	64742-95-6	Fathead minnow	Estimated	96 hours	LL50	8.2 mg/l
Light aromatic solvent naphtha (petroleum)	64742-95-6	Green Algae	Estimated	72 hours	EL50	7.9 mg/l
Light aromatic solvent naphtha (petroleum)	64742-95-6	Water flea	Estimated	48 hours	EL50	3.2 mg/l
Light aromatic solvent naphtha (petroleum)	64742-95-6	Green Algae	Estimated	72 hours	NOEL	0.22 mg/l
Light aromatic solvent naphtha (petroleum)	64742-95-6	Water flea	Experimental	21 days	NOEL	2.6 mg/l
Butane	106-97-8		Data not available or insufficient for classification			N/A
Propane	74-98-6		Data not available or insufficient for classification			N/A

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Light aromatic solvent naphtha (petroleum)	64742-95-6	Estimated Biodegradation	28 days	BOD	78 %BOD/CO D	OECD 301F - Manometric respirometry
Butane	106-97-8	Experimental Photolysis		Photolytic half-life (in air)	12.3 days (t 1/2)	Non-standard method
Propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	Non-standard method

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Light aromatic solvent naphtha (petroleum)	64742-95-6	Estimated BCF - Carp	42 days	Bioaccumulation factor	598	OECD 305E - Bioaccumulation flow-through fish test
Butane	106-97-8	Experimental Bioconcentration		Log Kow	2.89	Non-standard method
Propane	74-98-6	Experimental Bioconcentration		Log Kow	2.36	Non-standard method

		on				
--	--	----	--	--	--	--

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility.

### SECTION 14: Transport Information

#### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN1950

Proper shipping name: AEROSOLS

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

Special Instructions: Limited quantity may apply

Hazchem Code: 2YE

IERG: 49

#### International Air Transport Association (IATA) - Air Transport

UN No.: UN1950

Proper shipping name: AEROSOLS, FLAMMABLE

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

#### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1950

Proper shipping name: AEROSOLS

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Australian Inventory Status:

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance

with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## SECTION 16: Other information

### Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**