



SAFETY DATA SHEET

1. IDENTIFICATION OF THE HAZARDOUS CHEMICAL AND OF THE SUPPLIER

Product Name : **NIPPON ETCHING PRIMER 120 (BASE)**

Manufacturers Code : 868X

Intended Use : Paint for surface protection

Manufacturer : NIPPON PAINT (M) SDN. BHD. (7516-H)
Lot I-17, Taman Perindustrian Subang Utama,
Jalan SU 4, 40300 Shah Alam,
Selangor Darul Ehsan.

Emergency Tel No : 603-5125 0888

Fax Number : 603-5191 4849

2. HAZARD IDENTIFICATION

Class (GHS) Classification :

Physical Hazard

Flammable Liquids	Category 2
-------------------	------------

Health Hazard

Aspiration Hazard	Category 1
Reproductive Toxicity	Category 2
Skin Corrosion/irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 1
Specific Target Organ Toxicity-Repeated Exposure	Category 2
Specific Target Organ Toxicity-Single Exposure	Category 3
Skin Sensitisation	Category 1

Environmental Hazard

Hazardous To The Aquatic Environment-Chronic Hazard	Category 2
---	------------

Class (GHS) Pictogram



Signal Word

Danger

Hazard Statement

H225: Highly flammable liquid and vapour.

H373: May cause damage to organs through prolonged or repeated exposure.

H304: May be fatal if swallowed and enters airways.

H335: May cause respiratory irritation.

H315: Causes skin irritation.

H317: May cause allergic skin reaction.

H318: Causes serious eye damage.

H361: Suspected of damaging fertility or the unborn child (route of exposure inhalation or dermal).

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement

P210: Keep away from heat/sparks/open flames/hot surfaces No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ ventilating/lighting / equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P260: Do not breathe dust/fume/gas/mist/ vapours/spray.

P261: Avoid breathing dust/fume/ gas/mist/vapours/spray.

P271: Use only outdoors or in a well- ventilated area.

P264: Wash thoroughly after handling.

P272: Contaminated work clothing shall not be allowed out of the workplace

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P281: Use personal protective equipment as required.

P273: Avoid release to the environment

Response

P303+P361+P353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378: In case of fire: Evacuate area.

P314: Get medical advice/attention if you feel unwell.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P321: Specific treatment (see information on this label).

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362: Take off contaminated clothing and wash before reuse.

P333+P313: If skin irritation or rash occurs: Get medical advice/ attention.

P363: Wash contaminated clothing before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P391: Collect spillage.

Storage

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

Disposal

P501: Dispose of content/container to appropriate waste site or reclaimer in accordance with local or national regulations.

3. COMPOSITION AND INFORMATION OF THE INGREDIENTS OF THE HAZARDOUS CHEMICAL

This product is a mixture

Ingredient	CAS NO.	%
DIISOBUTYL KETONE; 2,6-DIMETHYLHEPTAN-4-ONE	108-83-8	0.02 - 0.03
FELDSPAR	68476-25-5	0.07 - 0.07
BISPHENOL-A EPOXY	25036-25-3	1.96 - 3.27
XYLENE	1330-20-7	0.33 - 0.98
VINYL BUTYRAL POLYMER	63148-65-2	7.96 - 8.21
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL	107-98-2	1.22 - 1.22
ISOBUTYL ALCOHOL; 2-METHYLPROPAN-1-OL; ISO-BUTANOL	78-83-1	4.59 - 4.59
ISOPROPYL ALCOHOL; PROPAN-2-OL; ISOPROPANOL	67-63-0	49.18 - 49.18
4-METHYLPENTAN-2-ONE; METHYL ISOBUTYL KETONE	108-10-1	4.59 - 4.59
TOLUENE	108-88-3	15.93 - 15.93
ETHYL BENZENE	100-41-4	0.04 - 0.25

4. FIRST AID MEASURES

Eye Contact :

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelid open. Do not use an eye oilmen. Seek medical attention.

Skin Contact :

Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition. Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Get medical attention if redness or irritation occurs.

Inhalation :

High vapour (>1000 ppm) are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anaesthesia. Drowsine unconsciousness and other central nervous system effects. Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform mouth to mouth resuscitation. Administer oxygen if available. Allow the victim to rest in a well ventilated area. Seek medical attention.

5. FIRE-FIGHTING MEASURES

Suitable Fire Extinguishing Media :

Small Fire : Use dry chemical. Foam or CO₂. Large Fire : Use water spray. Fog or foam. Water or foam may cause frothing.

Special Protective Actions For Fire Fighters

Cool container in water spray in order to prevent pressure build-up, auto ignition or explosion. Avoid flushing spilled material into sewers, stream or other bodies of water. For small out door fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. Respiratory and eye protection are required for fire fighting personnel.

Specific Hazards Arising From The Chemical:

Static discharge, material can accumulate static charges which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and / or vapour) and can be dangerous. DO NOT pressurize, cut, weld braze, solder, drill grind, or expose such containers to heat, flame sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURE

Eye / Skin Protection : Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment immediately available. Wear appropriate protective clothing and chemical resistant gloves to prevent skin contact. Wear a face shield and chemical resistant clothing such as rubber apron when splashing is likely.

Respiratory Protection :

Use JKPP / NIOSH approved respiratory protection (full face piece recommended) when exposure

limits are exceeded.

Ventilation :

Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. If practical, use local mechanical exhaust ventilation at source of air contamination such as open process equipment.

ENVIRONMENTAL PRECAUTIONS

Flammable liquid. Ventilate. Eliminate all sources of ignition. Prevent additional discharge of material. For small spills implement cleanup procedures; for large spills implement cleanup procedures and if in public area, keep public away and advise authorities, provide suitable personal protective, dike and contain spill with inert material (sand, earth, ect) and transfer liquid and solid separately to container for recovery or disposal. Report as per regulatory or disposal. Do not use combustible material such as sawdust. Report as per regulatory requirements.

METHODS AND MATERIALS FOR CONTAINMENTS AND CLEAN UP

For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:

Avoid smoking and use of open fire. Avoid inhalation of vapours and contact with skin and eyes. Observe good industrial practices.

CONDITION FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Store in tightly closed original container in well-ventilated area. Avoid expose to direct sunlight.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

CONTROL PARAMETERS / OCCUPATIONAL LIMITS

Ingredient	ACGIH TLV-TWA ppm	ACGIH TLV-TWA mg/m ³	OSHA PEL-TWA ppm	OSHA PEL-TWA mg/m ³
DIISOBUTYL KETONE; 2,6-DIMETHYLHEPTAN-4-ONE	-	-	25	145
FELDSPAR	-	3	-	-
BISPHENOL-A EPOXY	-	-	100	-
XYLENE	100	-	100	435
VINYL BUTYRAL POLYMER	-	10	-	-
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL	-	-	100	369
ISOBUTYL ALCOHOL; 2-METHYLPROPAN-1-OL; ISO-BUTANOL	-	-	50	152
ISOPROPYL ALCOHOL; PROPAN-2-OL; ISOPROPANOL	200	-	400	980
4-METHYLPENTAN-2-ONE; METHYL ISOBUTYL KETONE	-	-	50	205
TOLUENE	-	-	50	188
ETHYL BENZENE	-	-	100	434

APPROPRIATE ENGINEERING CONTROL MEASURES

If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

PERSONAL PROTECTION

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Recommended: Full mask with type Cartridge filter

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Recommended: safety glasses with side-shields.

Skin / Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Recommended: Wear protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : LIQUID

Odour : Aromatic Hydrocarbon

Odour Threshold : N/A

pH : Not Available

Melting Point (Cel) : Not Applicable

Initial Boiling Point (Cel) : 82.40

Maksimum Boiling Point (Cel) : 143.00

Flash Point : 8.98 Degree Celsius

Evaporation Rate : Not Applicable

Flammability (solid, gas) :

Lower Flammable Limit LEL or Explosion Limit(%) : 0.80

Upper Flammable Limit UEL or Explosion Limit(%) : 13.80

Vapour Pressure : Not Applicable

Vapour Density : Not Applicable (water = 1)

Relative Density : Not Available

Solubility : Not soluble in water

Partition Coefficient : Not Available

Auto-ignition Temperature (Cel) : Not Applicable

Decomposition temperature (Cel) : Not Available

Viscosity : 58.0 - 62.0 kU

Percent Volatile : 40-70%

Specific Gravity and other properties if applicable: 0.82 - 1.02
g/cm3

10. STABILITY AND REACTIVITY**REACTIVITY**

No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

Stable under normal temperature conditions and recommended use.

POSSIBILITY OF HAZARDOUS REACTION

Under normal conditions of storage and use, hazardous reaction will not occur

CONDITIONS TO AVOID

Heat, flames and sparks.

Nitric acid, sulfuric acid, strong oxidizing agents.

Electrostatic accumulation hazards? Yes, use proper grounding procedure.

HAZARDOUS DECOMPOSITION PRODUCTS

When exposed to high temperatures, may produce hazardous decomposition products such as Carbon dioxide, carbon monoxide, oxides of nitrogen and smoke.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.
Toxicological information of hazardous ingredients:

Specific Target Organ Toxicity-Repeated Exposure

Ingredient	Oral LD50	Dermal LD50	Inh(Gas) LC50	Inh(Vapor) LC50	Inh(Dust/mist) LC50
TOLUENE	5589	5000	DNA	28.1	DNA
ETHYL BENZENE	3500	17800	DNA	17.4	DNA

Aspiration Hazard

Ingredient	Oral LD50	Dermal LD50	Inh(Gas) LC50	Inh(Vapor) LC50	Inh(Dust/mist) LC50
TOLUENE	5589	5000	DNA	28.1	DNA
ETHYL BENZENE	3500	17800	DNA	17.4	DNA

Specific Target Organ Toxicity-Single Exposure

Ingredient	Oral LD50	Dermal LD50	Inh(Gas) LC50	Inh(Vapor) LC50	Inh(Dust/mist) LC50
DIISOBUTYL KETONE; 2,6-DIMETHYLHEPTAN-4-ONE	DNA	DNA	DNA	DNA	DNA
FELDSPAR	DNA	DNA	DNA	DNA	DNA
VINYL BUTYRAL POLYMER	5000	DNA	DNA	DNA	DNA
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL	6600	DNA	DNA	DNA	DNA
ISOBUTYL ALCOHOL; 2-METHYLPROPAN-1-OL; ISO-BUTANOL	2460	2000	DNA	18.8	DNA
ISOPROPYL ALCOHOL; PROPAN-2-OL; ISOPROPANOL	DNA	DNA	DNA	DNA	DNA
4-METHYLPENTAN-2-ONE; METHYL ISOBUTYL KETONE	DNA	DNA	DNA	DNA	DNA
TOLUENE	5589	5000	DNA	28.1	DNA

Skin Corrosion/irritation

Ingredient	Oral LD50	Dermal LD50	Inh(Gas) LC50	Inh(Vapor) LC50	Inh(Dust/mist) LC50
BISPHENOL-A EPOXY	DNA	DNA	DNA	DNA	DNA
XYLENE	5000	1000	DNA	10	DNA
VINYL BUTYRAL POLYMER	5000	DNA	DNA	DNA	DNA
ISOBUTYL ALCOHOL; 2-METHYLPROPAN-1-OL; ISO-BUTANOL	2460	2000	DNA	18.8	DNA
TOLUENE	5589	5000	DNA	28.1	DNA

Skin Sensitisation

Ingredient	Oral LD50	Dermal LD50	Inh(Gas) LC50	Inh(Vapor) LC50	Inh(Dust/mist) LC50
BISPHENOL-A EPOXY	DNA	DNA	DNA	DNA	DNA

Serious Eye Damage/Eye Irritation

Ingredient	Oral LD50	Dermal LD50	Inh(Gas) LC50	Inh(Vapor) LC50	Inh(Dust/mist) LC50
FELDSPAR	DNA	DNA	DNA	DNA	DNA
BISPHENOL-A EPOXY	DNA	DNA	DNA	DNA	DNA
VINYL BUTYRAL POLYMER	5000	DNA	DNA	DNA	DNA
ISOBUTYL ALCOHOL; 2-METHYLPROPAN-1-OL; ISO-BUTANOL	2460	2000	DNA	18.8	DNA
ISOPROPYL ALCOHOL; PROPAN-2-OL; ISOPROPANOL	DNA	DNA	DNA	DNA	DNA
4-METHYLPENTAN-2-ONE; METHYL ISOBUTYL KETONE	DNA	DNA	DNA	DNA	DNA

Reproductive Toxicity

Ingredient	Oral LD50	Dermal LD50	Inh(Gas) LC50	Inh(Vapor) LC50	Inh(Dust/mist) LC50
TOLUENE	5589	5000	DNA	28.1	DNA

12. ECOLOGICAL INFORMATION**ECOTOXICITY**

No data Available

PERSISTENCE AND DEGRADABILITY

No information available.

BIOACCUMULATIVE POTENTIAL

Has the potential to bioaccumulate.

MOBILITY IN SOIL

Floats on water. Adsorbs to soil and has low mobility.

OTHER ADVERSE EFFECTS

Do not allow product to reach ground water, water course or sewage system.

Ingredient**Fish 96****Crustacea 48****Algae 72 or 96**

	hour , LC50	hour , EC50	hour , ErC50
DIISOBUTYL KETONE; 2,6-DIMETHYLHEPTAN-4-ONE	DNA	DNA	DNA
FELDSPAR	DNA	DNA	DNA
BISPHENOL-A EPOXY	DNA	DNA	DNA
XYLENE	DNA	DNA	DNA
VINYL BUTYRAL POLYMER	DNA	DNA	DNA
1-METHOXY-2-PROPANOL; MONOPROPYLENE GLYCOL METHYL	DNA	DNA	1000
ISOBUTYL ALCOHOL; 2-METHYLPROPAN-1-OL; ISO-BUTANOL	1430	1100	632
ISOPROPYL ALCOHOL; PROPAN-2-OL; ISOPROPANOL	DNA	DNA	DNA
4-METHYLPENTAN-2-ONE; METHYL ISOBUTYL KETONE	DNA	DNA	DNA
TOLUENE	DNA	DNA	DNA
ETHYL BENZENE	DNA	DNA	DNA

13. DISPOSAL CONSIDERATIONS

Waste Disposal :

Recover or recycle if possible. Otherwise dispose in accordance with all applicable national environment laws and regulations.

Product Disposal :

This product when disposed of in its unused and uncontaminated state should be treated as a hazardous waste.

Container Disposal :

Drain container thoroughly. Rinse three times with suitable solvent. Treat rinsings as for product disposal. After draining, vent in a safe place away from sparks and fire. Send drum recoverer or metal reclaimer.

Residue may cause an explosion hazard. Do not puncture, cut or weld uncleared drums. Keep container labelled until cleaned and then remove or deface labels.

All federal and local environmental regulations shall be observed

14. TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for Air.

LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road &Regulations concerning the international carriage of Dangerous goods (RID) by Rail.

UN Number : 1263

Proper shipping name :

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound).

Class : 3

Packaging Group : II

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport of Sea.

UN Number : 1263

SEA TRANSPORT

Proper shipping name / Nama penghantaran :

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound).

Class : 3

Packaging Group : II

Marine Pollutant : Yes

SEA (Annex II of MARPOL 73/78 and the IBC code) / LAUT (Annex II of MARPOL 73/78 and the IBC code)

Not applicable

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by Air

UN Number : 1263

Proper shipping name :

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and

liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound).

Class : 3

Packaging Group : II

15. REGULATORY INFORMATION

Applicable national regulations :

- a) OHSA 1994 and relevant regulation;
- b) Factories and Machinery Act 1967 and relevant regulations;
- c) Environmental Quality Act 1974 and regulations;
- d) Pesticide Act 1974 and regulations;
- e) Occupational Safety and Health (Classification, Labelling And Safety Data Sheet of Hazardous Chemicals) Reg 2013.
- d) Industry Code Of Practice (On Chemicals Classification And Hazard Communication)

16. OTHER INFORMATION

Date Of Preparation : 01 April 2015

Version : 006

Revision Date : 29 January 2024

ABBREVIATION

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median lethal concentration

IACR International Agency for Research in Cancer

CAS Registry Numbers Chemical Abstracts Service Registry Numbers

ICOP Industry Code Of Practice on Chemicals Classification and Health approved by Minister under section 37 of the Act

C Ceiling limit

CEIL Ceiling limit airborne concentration

STEL Short term exposure limit

DNA Data not available

N/R Not Regulated

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.