

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: 194-85640 FASTCOAT

Recommended use of the chemical

and restrictions on use:

Supplier:

Surface coating.

Dulux Australia, a division of DuluxGroup (Australia) Pty Ltd

ABN: 67 000 049 427

Street Address: 1956 Dandenong Road,

Clayton, Victoria

Australia

Telephone Number: +61 3 9263 5678 **Facsimile:** +61 3 9263 5777

Emergency Telephone: 1 800 033 111 (ALL HOURS)

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Pigments	-	30-60%	-
Sand (Crystalline silica)	-	30-60%	R48/20, Carc. Cat. 1
, ,			R49
Synthetic polymer(s)	-	30-60%	-
Water	7732-18-5	30-60%	-
Propylene glycol	57-55-6	1-<10%	-
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Eye Contact:

Substance No: 000014557379

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Product Name: 194-85640 FASTCOAT Issued: 19/03/2013



Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the substance or mixture:

Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes.

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling:

Substance No: 000014557379

Keep out of reach of children. Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Conditions for safe storage, including any incompatibilities:

Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Propane-1,2-diol (propylene glycol) (total: vapour & particulates): 8hr TWA = 474 mg/m³ (150 ppm); (particulates only): 8hr TWA = 10 mg/m³

Product Name: 194-85640 FASTCOAT Issued: 19/03/2013



As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: B - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.







Wear overalls, safety glasses and impervious gloves. Avoid breathing dust when sanding. Wet sand or use a dust mask. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If spraying wear an organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Viscous liquid Colour: Coloured

Solubility: Miscible with water.

Specific Gravity: 1-1.9 @ 20°C

Relative Vapour Density (air=1): >1

Vapour Pressure (20 °C):

Flash Point (°C):

Flammability Limits (%):

Autoignition Temperature (°C):

Volatile by Volume:

Solubility in water (g/L):

Not available

Not applicable

Not applicable

Not available

Complete

Melting Point/Range (°C):

Boiling Point/Range (°C):

Decomposition Point (°C):

Not applicable
100 (water)
Not available

pH: 8-10

Substance No: 000014557379

Viscosity: Not available Evaporation Rate: Not available

Product Name: 194-85640 FASTCOAT Issued: 19/03/2013



10. STABILITY AND REACTIVITY

Reactivity: No information available.

Chemical stability: Stable under normal conditions of use.

Possibility of hazardous reactions: Hazardous polymerisation will not occur.

Conditions to avoid: Avoid contact with foodstuffs. Avoid exposure to frost.

Incompatible materials: Incompatible with oxidising agents.

Hazardous decomposition

products:

Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:No adverse effects expected, however, large amounts may cause nausea and vomiting.

Eye contact: May be an eye irritant.

Skin contact: Contact with skin may result in irritation.

Inhalation: Where this material is used in a poorly ventilated area, at elevated temperatures or in

confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea. Breathing in mists or aerosols may produce respiratory

irritation.

Acute toxicity: No LD50 data available for the product.

Chronic effects: No information available for the product. Repeated or prolonged breathing of crystalline silica dust may result in chronic lung diseases such as silicosis. However, due to the physical state of this product this is not relevant unless it is sanded, abraded or crushed. In such cases, precautions should be taken to avoid the breathing of dust.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.

14. TRANSPORT INFORMATION

Road and Rail Transport

Substance No: 000014557379

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail: NON-DANGEROUS GOODS.

Product Name: 194-85640 FASTCOAT Issued: 19/03/2013



Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

Based on available information, not classified as hazardous according to Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule (SUSMP): None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Reason(s) for Issue:

Revised Primary SDS

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: 194-85640 FASTCOAT Issued: 19/03/2013 Substance No: 000014557379