

# 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

# Product name: SELLEYS 635 MULTIPURPOSE FLEXIBLE **SEALANT**

Synonyms	Product Code	Bar Code
SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Black,	-	-
600mL		
SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Black,	-	-
300mL		
SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Grey,	-	-
600mL		
SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Grey,	-	-
300mL		
SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT	-	-
White, 600mL		
SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT	-	-
White, 300mL		
	SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Black, 600mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Black, 300mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Grey, 600mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Grey, 300mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT White, 600mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT	SÉLLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Black, - 600mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Black, - 300mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Grey, - 600mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT Grey, - 300mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT - White, 600mL SELLEYS 635 MULTIPURPOSE FLEXIBLE SEALANT -

Recommended use: Sealant

Nippon Paint (Singapore) Co. Pte Ltd Supplier: Street Address:

1 First Lok Yang Road, Jurong

Singapore 629728

Telephone: +65 6265 5355

Emergency Telephone number: +613 9663 2130

# 2. HAZARDS IDENTIFICATION

This material is not classified as hazardous according to Singapore Standard SS 586: 2014.

# DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the United Nations "Recommendations on the Transport of Dangerous Goods."

# 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]- Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl) ester Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- Ingredients determined to be Non-Hazardous	1760-24-3 52829-07-9 22673-19-4 -	0.1 -< 1 % 0.1 -< 1 % 0.1 -< 1 % Balance

100%

Reference No: SELSGPEN001305 Product Name: SELLEYS 635 MULTIPURPOSE FLEXIBLE

**SEALANT** 

Issued: 2022-07-26 Version: 1.1 Page 1 of 6



### 4. FIRST AID MEASURES

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

**Eye contact:** If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**PPE for First Aiders:** Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Notes to physician:** Treat symptomatically.

### **5. FIRE FIGHTING MEASURES**

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

**Fire fighting further advice:** On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

# **6. ACCIDENTAL RELEASE MEASURES**

## **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

### LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

# 7. HANDLING AND STORAGE

Product Name: SELLEYS 635 MULTIPURPOSE FLEXIBLE Reference No: SELSGPEN001305

**SEALANT** 

Issued: 2022-07-26 Version: 1.1 Page 2 of 6



Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**National occupational exposure limits:** No value assigned for this specific material by the Workplace Safety and Health (General Provisions) Regulations, 2006.

**Biological Limit Values:** As per the Workplace Health and Safety Guidelines – Statutory Medical Examinations, 2011 the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES.

When handling individual retail packs no personal protection equipment is required.

Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Paste
Colour: White
Odourless

Solubility: Immiscible in water

**Specific Gravity:** 1.55 Relative Vapour Density (air=1): N Av Vapour Pressure (20 °C): N Av Flash Point (°C): N App Flammability Limits (%): N Av **Autoignition Temperature (°C):** N Av Melting Point/Range (°C): N Av Boiling Point/Range (°C): N Av pH: N Av Viscosity: N App Total VOC (g/Litre): N Av

> (Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

Product Name: SELLEYS 635 MULTIPURPOSE FLEXIBLE Reference No: SELSGPEN001305

**SEALANT** 

Issued: 2022-07-26 Version: 1.1 Page 3 of 6



### 10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: None known.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

# 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

**Skin contact:** Contact with skin may result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Eye contact:** May be an eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

# **Acute toxicity**

**Inhalation:** This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients):  $LC_{50} > 5.0$  mg/L for dust.

**Skin contact:** This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients):  $LD_{50} > 2,000 \text{ mg/Kg}$  bw

**Ingestion:** This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients):  $LD_{50} > 2,000 \text{ mg/Kg}$  bw

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as not an aspiration hazard.

**Specific target organ toxicity (single exposure):** This material has been classified as not a specific hazard to target organs by a single exposure.

# **Chronic Toxicity**

Mutagenicity: This material has been classified as not a mutagen.

Product Name: SELLEYS 635 MULTIPURPOSE FLEXIBLE Reference No: SELSGPEN001305

**SEALANT** 

Issued: 2022-07-26 Version: 1.1 Page 4 of 6



Carcinogenicity: This material has been classified as not a carcinogen.

**Reproductive toxicity (including via lactation):** This material has been classified as not a reproductive toxicant.

**Specific target organ toxicity (repeat exposure):** This material has been classified as not a specific hazard to target organs by repeat exposure.

### 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

**Long-term aquatic hazard:** This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log  $K_{ow}$  < 4.

**Ecotoxicity:** No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

**Mobility:** No information available.

# 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

### 14. TRANSPORT INFORMATION

# **ROAD AND RAIL TRANSPORT**

Not classified as Dangerous Goods by the criteria of the United Nations "Recommendations on the Transport of Dangerous Goods."

# MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

# **AIR TRANSPORT**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

# 15. REGULATORY INFORMATION

Product Name: SELLEYS 635 MULTIPURPOSE FLEXIBLE Reference No: SELSGPEN001305

**SEALANT** 

Issued: 2022-07-26 Version: 1.1 Page 5 of 6



# This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

## This material/constituent(s) is covered by the following requirements:

- Environmental Protection and Management (Hazardous Substances) Regulations
- Workplace Safety and Health (General Provisions) Regulations

# Environmental Protection and Management (Hazardous Substances) Regulations

Ingredient names Control Quantity
Tin, dibutylbis(2,4-pentanedionatoO,O')-, (OC-6-11)
Control Quantity
0 kg

# **16. OTHER INFORMATION**

Reason for issue: Revised

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the company cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product Name: SELLEYS 635 MULTIPURPOSE FLEXIBLE Reference No: SELSGPEN001305

**SEALANT** 

Issued: 2022-07-26 Version: 1.1 Page 6 of 6