

# Safety Data Sheet



Hazardous, Dangerous Goods

## 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

### Product name: 482-LINE REFINISH AUTOSOLV LACQUER TINTERS AND MIXED COLOURS

#### Synonyms

Refinish Autosolv Lacquer B Gold 1L  
Refinish Autosolv Lacquer B Metallic 1L  
Refinish Autosolv Lacquer Black 1L  
Refinish Autosolv Lacquer Black 20L  
Refinish Autosolv Lacquer Black 4L  
Refinish Autosolv Lacquer Bluish Pearl 1L  
Refinish Autosolv Lacquer Bright Orange 1L  
Refinish Autosolv Lacquer Bright Red 1L  
Refinish Autosolv Lacquer Bright Yellow 1L  
Refinish Autosolv Lacquer Coarse Al 1L  
Refinish Autosolv Lacquer Coarse Met 1L  
Refinish Autosolv Lacquer Control Add 1L  
Refinish Autosolv Lacquer Dark Red Oxide 1L  
Refinish Autosolv Lacquer Deep Black 4L  
Refinish Autosolv Lacquer Deep Blue 1L  
Refinish Autosolv Lacquer Deep Red 1L  
Refinish Autosolv Lacquer Diamond Met 1L  
Refinish Autosolv Lacquer Extra Fine Al 1L  
Refinish Autosolv Lacquer Fast Red 1L  
Refinish Autosolv Lacquer Fine Al 1L  
Refinish Autosolv Lacquer Flat Base 1L  
Refinish Autosolv Lacquer Garnet 1L  
Refinish Autosolv Lacquer Green Blue 1L  
Refinish Autosolv Lacquer Green Pearl 1L  
Refinish Autosolv Lacquer Greenish Gold 1L  
Refinish Autosolv Lacquer Hi Opacity White 4L  
Refinish Autosolv Lacquer Lemon Yellow 1L  
Refinish Autosolv Lacquer Lilac Pearl 1L  
Refinish Autosolv Lacquer Lime 1L  
Refinish Autosolv Lacquer Lt Red Oxide 1L  
Refinish Autosolv Lacquer Lush Blue 1L  
Refinish Autosolv Lacquer Magenta 1L  
Refinish Autosolv Lacquer Maroon Base 1L  
Refinish Autosolv Lacquer Med Al 1L  
Refinish Autosolv Lacquer Medium Metallic 1L  
Refinish Autosolv Lacquer Micro Met 1L  
Refinish Autosolv Lacquer Mid Blue 1L  
Refinish Autosolv Lacquer Mid Yellow 1L  
Refinish Autosolv Lacquer Organic Orange 1L  
Refinish Autosolv Lacquer Pearl 1L  
Refinish Autosolv Lacquer Perm Green 1L  
Refinish Autosolv Lacquer Red Black 4L  
Refinish Autosolv Lacquer Red Blue 1L  
Refinish Autosolv Lacquer Red Green 1L  
Refinish Autosolv Lacquer Red Maroon 1L  
Refinish Autosolv Lacquer Red Red Oxide 1L  
Refinish Autosolv Lacquer Red Yellow Ochre 1L  
Refinish Autosolv Lacquer Reddish Gold 1L  
Refinish Autosolv Lacquer Rich Brn 1L  
Refinish Autosolv Lacquer Rich Maroon 1L

#### Product Code

482S3010-1L  
482S3030-1L  
482S3000-1L  
482S3000-20L  
482S3000-4L  
482S3840-1L  
482S3040-1L  
482S3940-1L  
482S3050-1L  
482S3720-1L  
482S3090-1L  
482S3991-1L  
482S3110-1L  
482S3120-4L  
482S3130-1L  
482S3140-1L  
482S3150-1L  
482S3690-1L  
482S3160-1L  
482S3700-1L  
482S3170-1L  
482S3210-1L  
482S3180-1L  
482S3870-1L  
482S3190-1L  
482S3990-4L  
482S3020-1L  
482S3810-1L  
482S3230-1L  
482S3220-1L  
482S3570-1L  
482S3240-1L  
482S3250-1L  
482S3710-1L  
482S3260-1L  
482S3270-1L  
482S3280-1L  
482S3290-1L  
482S3320-1L  
482S3890-1L  
482S3330-1L  
482S3370-4L  
482S3440-1L  
482S3380-1L  
482S3360-1L  
482S3390-1L  
482S3450-1L  
482S3350-1L  
482S3460-1L  
482S3470-1L

#### Bar Code

9300611479488  
9300611479501  
9300611478726  
9300611503961  
9300611479471  
9300611480019  
9300611479518  
9300611480064  
9300611479525  
9300611479983  
9300611479556  
9300611480095  
9300611479549  
9300611479532  
9300611479563  
9300611479570  
9300611479587  
9300611479952  
9300611479594  
9300611479969  
9300611479600  
9300611479679  
9300611479655  
9300611480040  
9300611480590  
9300611480088  
9300611479495  
9300611480002  
9300611479693  
9300611479686  
9300611479914  
9300611479709  
9300611479723  
9300611479976  
9300611479730  
9300611479747  
9300611479754  
9300611479761  
9300611479778  
9300611480057  
9300611479785  
9300611496645  
9300611479846  
9300611479822  
9300611479808  
9300611479839  
9300611479853  
9300611479792  
9300611479860  
9300611479877

Product Name: 482-LINE REFINISH AUTOSOLV LACQUER  
TINTERS AND MIXED COLOURS

Reference No: DLXGHSEN000511

# Safety Data Sheet



Refinish Autosolv Lacquer Rich Red 1L	482S3480-1L	9300611479884
Refinish Autosolv Lacquer Russet Pearl 1L	482S3860-1L	9300611480033
Refinish Autosolv Lacquer Solar Yellow 1L	482S3490-1L	9300611479891
Refinish Autosolv Lacquer Trans Maroon 1L	482S3560-1L	9300611479907
Refinish Autosolv Lacquer Violet 1L	482S3580-1L	9300611479921
Refinish Autosolv Lacquer White 4L	482S3950-4L	9300611480071
Refinish Autosolv Lacquer White Pearl 1L	482S3800-1L	9300611479990
Refinish Autosolv Lacquer Yellow Gold 1L	482S3590-1L	9300611479938
Refinish Autosolv Lacquer Yellow Ochre 1L	482S3660-1L	9300611479945
Refinish Autosolv Lacquer Yellow Pearl 1L	482S3850-1L	9300611480026
Refinish Autosolv Mixed Colour Gp 1 100mL	482S9991-100ML	9300611489692
Refinish Autosolv Mixed Colour Gp 2 100mL	482S9992-100ML	9300611489708
Refinish Autosolv Mixed Colour Gp 3 100mL	482S9993-100ML	9300611489715
Refinish Autosolv Mixed Colour Gp1 1L	482S9991-1L	9300611489623
Refinish Autosolv Mixed Colour Gp1 2l	482S9991-2L	9300611489630
Refinish Autosolv Mixed Colour Gp1 4L	482S9991-4L	9300611489661
Refinish Autosolv Mixed Colour Gp1 500mL	482S9991-500ML	9300611489593
Refinish Autosolv Mixed Colour Gp2 1L	482S9992-1L	9300611489616
Refinish Autosolv Mixed Colour Gp2 2l	482S9992-2L	9300611489647
Refinish Autosolv Mixed Colour Gp2 4L	482S9992-4L	9300611489678
Refinish Autosolv Mixed Colour Gp2 500mL	482S9992-500ML	9300611489722
Refinish Autosolv Mixed Colour Gp3 1L	482S9993-1L	9300611489609
Refinish Autosolv Mixed Colour Gp3 2l	482S9993-2L	9300611489654
Refinish Autosolv Mixed Colour Gp3 4L	482S9993-4L	9300611489685
Refinish Autosolv Mixed Colour Gp3 500mL	482S9993-500ML	9300611489739
Refinish Autosolv Monroe Springs Misc 1L	482S0037-1L	

**Recommended use:** Lacquer tinters and mixed colours used in car repairs. Applied by spray.

**Supplier:** Dulux Australia, a division of DuluxGroup (Australia) Pty Ltd  
**ABN:** 67 000 049 427  
**Street Address:** 1956 Dandenong Road  
Clayton VIC 3168  
Australia  
**Telephone:** 13 25 25

**Emergency Telephone number:** Australia – 1800 220 770; New Zealand – 0800 220 770

## 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



### Signal Word

Danger

### Hazard Classifications

Flammable Liquids - Category 2

Aspiration Hazard - Category 1

Skin Corrosion/Irritation - Category 2

Eye Damage/Irritation - Category 1

Sensitisation - Skin - Category 1

Reproductive Toxicity - Category 1A

Specific Target Organ Toxicity (Single Exposure) - Category 3 Respiratory Tract Irritation

**Product Name:** 482-LINE REFINISH AUTOSOLV LACQUER  
TINTERS AND MIXED COLOURS

**Reference No:** DLXGHSEN000511

# Safety Data Sheet



Specific Target Organ Toxicity (Single Exposure) - Category 3 Narcotic Effects  
Specific Target Organ Toxicity (Repeated Exposure) - Category 2

## Hazard Statements

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360 May damage fertility or the unborn child .
- H373 May cause damage to organs through prolonged or repeated exposure.

## Prevention Precautionary Statements

- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust, fume, gas, mist, vapours or spray.
- P264 Wash hands, face and all exposed skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing including eye/face protection and suitable respirator.

## Response Precautionary Statements

- P101 If medical advice is needed, have product container or label at hand.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor/insert appropriate source of emergency medical advice.
- P331 Do NOT induce vomiting.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse

## Storage Precautionary Statements

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

## Disposal Precautionary Statement

- P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

**Poison Schedule:** Not Applicable

## DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

**Product Name: 482-LINE REFINISH AUTOSOLV LACQUER  
TINTERS AND MIXED COLOURS**

**Reference No: DLXGHSEN000511**

**Issued: 17 May 2021**

**Version: 4.0**

**Page 3 of 10**

# Safety Data Sheet



Dangerous Goods Class: 3

## 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
n-Butyl acetate	123-86-4	30 - 60 % (w/w)
Propylene glycol monomethyl ether acetate	108-65-6	30 - 60 % (w/w)
Toluene	108-88-3	10 - 30 % (w/w)
Xylene	1330-20-7	10 - 30 % (w/w)
Acetone	67-64-1	1 - 10 % (w/w)
Benzyl butyl phthalate	85-68-7	1 - 10 % (w/w)
Butanol	78-83-1	1 - 10 % (w/w)
Chlorobenzotrifluoride	98-56-6	1 - 10 % (w/w)
Methylisobutyl ketone	108-10-1	1 - 10 % (w/w)
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	1 - 10 % (w/w)
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - 10 % (w/w)
Stoddard solvent	8052-41-3	1 - 10 % (w/w)
Ingredients determined to be non-hazardous or below reporting limits		Balance
		100%

## 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:** Effects may be delayed. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

**Ingestion:** Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

**PPE for First Aiders:** Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Notes to physician:** Treat symptomatically. Effects may be delayed. Can cause corneal burns.

## 5. FIRE FIGHTING MEASURES

**Hazchem Code:** •3YE

**Suitable extinguishing media:** If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Highly flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Fire fighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

### SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

### LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

**Dangerous Goods - Initial Emergency Response Guide No:** 14

## 7. HANDLING AND STORAGE

**Handling:** Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**National occupational exposure limits:**

	TWA	STEL	NOTICES	
	ppm	mg/m3	ppm	mg/m3

# Safety Data Sheet



1-Methoxy-2-propanol acetate	50	274	100	548	Sk
Acetone	500	1185	1000	2375	-
Isobutyl alcohol	50	152	-	-	-
Methyl isobutyl ketone	50	205	75	307	-
n-Butyl acetate	150	713	200	950	-
Toluene	50	191	150	574	Sk
White spirits	-	790	-	-	-
Xylene	80	350	150	655	-

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

**Personal Protection Equipment:** SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR.

Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Form:** Liquid  
**Colour:** Various  
**Odour:** Solvent

**Solubility:** Insoluble in water. Soluble in organic solvents.

**Product Name:** 482-LINE REFINISH AUTOSOLV LACQUER  
TINTERS AND MIXED COLOURS

**Reference No:** DLXGHSEN000511

# Safety Data Sheet



Specific Gravity:	0.90 - 1.20
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	24.7 kPa @ 20 °C
Flash Point (°C):	-18
Flammability Limits (%):	1 - 12.8
Autoignition Temperature (°C):	N Av
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	56 - 145
pH:	N App
Viscosity:	<21 mm <sup>2</sup> /s @ 40 °C
Total VOC (g/Litre):	N Av

(Typical values only - consult specification sheet)

N Av = Not available, N App = Not applicable

## 10. STABILITY AND REACTIVITY

**Chemical stability:** This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes.

**Hazardous reactions:** No known hazardous reactions.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Effects

**Inhalation:** Material is an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

**Skin contact:** Contact with skin will result in irritation. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

**Eye contact:** A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

### Acute toxicity

**Inhalation:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 20.0 mg/L for vapours or LC50 > 5.0 mg/L for dust and mist or LC50 > 20,000 ppm for gas

**Skin contact:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

# Safety Data Sheet



**Ingestion:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

**Aspiration hazard:** This material has been classified as Aspiration Hazard - Category 1

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation. This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

## Chronic Toxicity

**Mutagenicity:** This material has been classified as non-hazardous.

**Carcinogenicity:** This material has been classified as non-hazardous.

**Reproductive toxicity (including via lactation):** This material has been classified as non-hazardous.

**Specific target organ toxicity (repeat exposure):** This material has been classified as a Category 2 Hazard.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log  $K_{ow}$  < 4.

**Ecotoxicity:** No information available.

**Persistence and degradability:** No information available.

**Bioaccumulative potential:** No information available.

**Mobility:** No information available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

## 14. TRANSPORT INFORMATION



# Safety Data Sheet



## ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** II  
**Hazchem Code:** •3YE  
**Emergency Response Guide No:** 14

**Proper Shipping Name:** PAINT

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

## MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** II

**Proper Shipping Name:** PAINT

## AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** II

**Proper Shipping Name:** PAINT

## 15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

**Product Name:** 482-LINE REFINISH AUTOSOLV LACQUER  
TINTERS AND MIXED COLOURS

**Reference No:** DLXGHSEN000511

# Safety Data Sheet



Montreal Protocol (Ozone depleting substances)  
The Stockholm Convention (Persistent Organic Pollutants)  
The Rotterdam Convention (Prior Informed Consent)  
Basel Convention (Hazardous Waste)  
International Convention for the Prevention of Pollution from Ships (MARPOL)

**This material/constituent(s) is covered by the following requirements:**

- All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIIC).

<b>16. OTHER INFORMATION</b>
------------------------------

Reason for issue: Revised

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd ([chemdata.com.au](http://chemdata.com.au)) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.