

Safety Data Sheet



Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **031-94988 Handi Decking Oil**

Synonyms:

Handi Decking Oil, 4L

Product Code

03194988-4L

Bar Code

9300611516374

Recommended use: Coating for decks and pergolas. Applied by brush, roller or pad.

Supplier: Dulux Australia, a division of
DuluxGroup (Australia) Pty Ltd

ABN: 67 000 049 427

Street Address: 1956 Dandenong Road
Clayton VIC 3168
Australia

Telephone: 13 25 25

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word

Warning

Hazard Classification

Flammable Liquids – Category 3

Aspiration Hazard – Category 2

Sensitisation – Skin – Category 1A

Specific Target Organ Toxicity (Single Exposure) – Category 3

Hazard Statement(s)

H226 Flammable liquid and vapour

H305 May be harmful if swallowed and enters airways

H317 May cause an allergic skin reaction

H336 May cause drowsiness or dizziness

Prevention Precautionary Statement(s)

P102 Keep out of reach of children

P103 Read label before use

P210 Keep away from all sources of ignition - No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical, ventilating, lighting and all other equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P261 Avoid breathing mist, vapours or spray

Product name: 031-94988 Handi Decking Oil

SDS No: DLXGHSEN001056

Issued: 28 June 2016

Version: 5.0

Page: 1 of 9

Safety Data Sheet



- P271 Use only outdoors or in a well-ventilated area
P272 Contaminated work clothing should not be allowed out of the workplace
P280 Wear protective clothing, gloves, eye/face protection and suitable respirator as required

Response Precautionary Statement(s)

- P101 If medical advice is needed, have product container or label at hand
P301+310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician
P331 Do NOT induce vomiting
P302+352 IF ON SKIN: Wash with soap and water
P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P363 Wash contaminated clothing before reuse
P333+313 If skin irritation or a rash occurs: Get medical advice/attention
P370+378 In case of fire: Use alcohol resistant foam for extinction

Storage Precautionary Statement(s)

- P405 Store locked up
P403+235 Store in a well ventilated place. Keep cool

Disposal Precautionary Statement(s)

- P501 Dispose of contents/container in accordance with local, regional, national and international regulations

Poisons Schedule (Aust): S5

DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Class: 3 Flammable Liquid

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Kerosene	64742-81-0	> 60%
2-Octyl-2H-isothiazol-3-one (Octhilinone)	26530-20-1	< 0.2%
Ingredients determined to be non-hazardous	-	Balance
		<hr/> 100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Safety Data Sheet



Skin contact: For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. Seek medical attention.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Hazchem Code: •3Y

Suitable extinguishing media: Alcohol resistant foam is the preferred fire-fighting medium. If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Flammable liquid. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning may emit toxic fumes, including oxides of carbon and nitrogen. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Use a spark-free shovel. If contamination of sewers or waterways has occurred advise local emergency services.

Safety Data Sheet



Dangerous Goods – Initial Emergency Response Guide No: 14

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Dangerous Good Class 3 Flammable Liquid as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

Personal protection equipment: G: OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.

Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid skin and eye contact and inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

Safety Data Sheet



9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Brown liquid with a solvent odour.

Solubility:	Dispersible in water. Soluble in organic solvents.
Specific Gravity (20 °C):	0.876
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	>23
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
% Volatile by Volume:	>60
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	N Av
Decomposition Point (°C):	N Av
pH:	N Av
Viscosity:	N Av
Total VOC (g/Litre):	N Av

(Typical values only - consult specification sheet)
N Av = Not available N App = Not applicable

10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Incompatible with oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

Skin contact: Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is uncoordinated there is greater likelihood of vomit entering the lungs and causing subsequent complications. Aspiration pneumonia (inflammation of the lung) may result.

Eye contact: May be an eye irritant.

Acute toxicity

Inhalation: This material has been classified as non-hazardous.

Skin contact: This material has been classified as non-hazardous.

Ingestion: This material has been classified as non-hazardous.

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes.
Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitizer.
Skin: this material has been classified as a Category 1A Hazard (skin sensitizer).

Aspiration hazard: This material has been classified as a Category 2 Hazard.

Specific target organ toxicity (single exposure): This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

Safety Data Sheet



12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: No information is available to complete an assessment.

Long-term aquatic hazard: No information is available to complete an assessment.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN No: 1263
Dangerous Goods Class: 3 Flammable Liquid
Packing Group: III
Hazchem Code: •3Y
Emergency Response Guide No: 14

Proper Shipping Name: PAINT

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2) or radioactive substances (Class 7), however exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1263
Dangerous Goods Class: 3 Flammable Liquid
Packing Group: III

Proper Shipping Name: PAINT

Safety Data Sheet



AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA)
Dangerous Goods Regulations for transport by air.

UN No: 1263
Dangerous Goods Class: 3 Flammable Liquid
Packing Group: III

Proper Shipping Name: PAINT

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

- Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish

International Convention for the Prevention of Pollution from Ships (MARPOL)

- Annex III - Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements:

- The Standard for the *Uniform Scheduling of Medicines and Poisons (SUSMP)* established under the *Therapeutic Goods Act (Commonwealth)*.
- All the constituents of this material are listed on the *Australian Inventory of Chemical Substances (AICS)*.

16. OTHER INFORMATION

Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Reason(s) For Issue: Format change
Minor Text Changes.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent

Product name: 031-94988 Handi Decking Oil

SDS No: DLXGHSEN001056

Issued: 28 June 2016

Version: 5.0

Page: 8 of 9

Safety Data Sheet



to our customers and is also available upon request.