

## Hazardous, Dangerous Goods

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **800-61064 BRITISH PAINTS ENAMEL GLOSS BLACK BEAUTY**

**Synonyms**

British Paints Enamel Gloss Black Beauty 1L

**Product Code**

80061064-1L

**Bar Code**

9300611346100

**Recommended use:** Solvent based surface coating. Applied by brush, roller or spray.

**Supplier:** Dulux Australia, a division of DuluxGroup (Australia) Pty Ltd

**ABN:** 67 000 049 427

**Street Address:** 1956 Dandenong Road  
Clayton VIC 3168

Australia

**Telephone:** 13 25 25

**Emergency Telephone number:** Australia – 1800 220 770; New Zealand – 0800 220 770

### 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.

**Signal Word**

Danger

**Hazard Classifications**

Flammable Liquids - Category 3

Aspiration Hazard - Category 1

Skin Corrosion/Irritation - Category 2

Specific Target Organ Toxicity (Single Exposure) - Category 3 Narcotic Effects

**Hazard Statements**

- H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.

**Prevention Precautionary Statements**

- P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing dust, fume, gas, mist, vapours or spray..  
P264 Wash hands, face and all exposed skin thoroughly after handling.

**Product Name: 800-61064 BRITISH PAINTS ENAMEL GLOSS BLACK BEAUTY**

**Reference No: DLXGHSEN001427**

# Safety Data Sheet

P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing including eye/face protection and suitable respirator.

## Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P331 Do NOT induce vomiting.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse

## Storage Precautionary Statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

## Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

**Poison Schedule:** Not Applicable

## DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

**Dangerous Goods Class:** 3

## 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Naphtha, petroleum, hydrodesulfurized heavy	64742-82-1	10 - 30 % (w/w)
Solvent naphtha, petroleum, light aromatic	64742-95-6	10 - 30 % (w/w)
Naphtha, petroleum, hydrotreated heavy	64742-48-9	1 - 10 % (w/w)
Ingredients determined to be non-hazardous or below reporting limits		Balance
		100%

## 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:** If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble).

# Safety Data Sheet

For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

**PPE for First Aiders:** Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Notes to physician:** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Hazchem Code:** •3Y

**Suitable extinguishing media:** If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Fire fighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

### SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

### LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

**Dangerous Goods - Initial Emergency Response Guide No:** 14

## 7. HANDLING AND STORAGE

# Safety Data Sheet

**Handling:** Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**National occupational exposure limits:** No value assigned for this specific material by Safe Work Australia.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering Measures:** Natural ventilation should be adequate under normal use conditions.

**Personal Protection Equipment:** SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES, RESPIRATOR.

Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Form:** Liquid  
**Colour:** Various  
**Odour:** Solvent

**Solubility:** Insoluble in water. Soluble in organic solvents.  
**Specific Gravity:** 0.946  
**Relative Vapour Density (air=1):** >1  
**Vapour Pressure (20 °C):** N Av  
**Flash Point (°C):** >23  
**Flammability Limits (%):** N Av  
**Autoignition Temperature (°C):** N Av  
**Melting Point/Range (°C):** N Av  
**Boiling Point/Range (°C):** N Av  
**pH:** N App  
**Viscosity:** <21 mm<sup>2</sup>/s @ 40 °C  
**Total VOC (g/Litre):** N Av

(Typical values only - consult specification sheet)  
N Av = Not available, N App = Not applicable

## 10. STABILITY AND REACTIVITY

**Chemical stability:** This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes.

**Hazardous reactions:** No known hazardous reactions.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Effects

**Inhalation:** Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

**Skin contact:** Contact with skin will result in irritation.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

**Eye contact:** May be an eye irritant.

### Acute toxicity

**Inhalation:** This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients):  $LC_{50} > 20.0$  mg/L for vapours or  $LC_{50} > 5.0$  mg/L for dust and mist.

**Skin contact:** This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients):  $LD_{50} > 2,000$  mg/Kg bw

**Ingestion:** This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients):  $LD_{50} > 2,000$  mg/Kg bw

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

**Aspiration hazard:** This material has been classified as Aspiration Hazard - Category 1

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

### Chronic Toxicity

**Mutagenicity:** This material has been classified as not a mutagen.

**Carcinogenicity:** This material has been classified as not a carcinogen.

**Reproductive toxicity (including via lactation):** This material has been classified as not a reproductive toxicant.

**Specific target organ toxicity (repeat exposure):** This material has been classified as not a specific hazard to target organs by repeat exposure.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

**Long-term aquatic hazard:** This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K<sub>ow</sub> < 4.

**Ecotoxicity:** No information available.

**Persistence and degradability:** No information available.

**Bioaccumulative potential:** No information available.

**Mobility:** No information available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

## 14. TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** III  
**Hazchem Code:** •3Y  
**Emergency Response Guide No:** 14

**Proper Shipping Name:** PAINT

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents

**Product Name:** 800-61064 BRITISH PAINTS ENAMEL GLOSS  
BLACK BEAUTY

**Reference No:** DLXGHSEN001427

# Safety Data Sheet

(Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

## MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** III  
**Proper Shipping Name:** PAINT

## AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** III  
**Proper Shipping Name:** PAINT

## 15. REGULATORY INFORMATION

### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)  
The Stockholm Convention (Persistent Organic Pollutants)  
The Rotterdam Convention (Prior Informed Consent)  
Basel Convention (Hazardous Waste)  
International Convention for the Prevention of Pollution from Ships (MARPOL)

### This material/constituent(s) is covered by the following requirements:

AIICS Status: Formulations where all components AIIC listed.

## 16. OTHER INFORMATION

Reason for issue: Revised

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

# Safety Data Sheet



This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the company cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.