

Hazardous, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: 976-89935 WEATHERMAX HBR ACCELERATOR PART C

Synonyms Product Code Bar Code Protective Coatings Weathermax HBR Accelerator Part C, 112g 97689935-112G 9300611466365

Recommended use: Accelerator for Weathermax HBR.

Supplier: Dulux Protective Coatings Australia, a division of DuluxGroup (New Zealand)

Company No.: 55 133 404 118 / Co. 2355191

Street Address: 150 Hutt Park Road

> Lower Hutt New Zealand

Telephone: 0800 800 424

Emergency Telephone number: Australia - 1800 033 111 New Zealand - 0800 734 607

2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of EPA New Zealand.

EPA Group Standard: HSR002667 - Surface Coatings and Colourants (Flammable, Toxic [6.1]) Group Standard











Signal Word

Danger

Hazard Classifications

3.1C - Flammable liquids

6.1C - Substances that are acutely toxic - Oral

6.1C - Substances that are acutely toxic - Dermal

6.1B - Substances that are acutely toxic - Inhalation - vapours, dusts or mists

6.3A - Substances that are irritating to the skin

8.3A - Substances that are corrosive to ocular tissue

6.5B - Substances that are contact sensitisers

6.9B (Single exposure) - Substances that are harmful to human target organs or systems

9.1B - Substances that are ecotoxic in the aquatic environment (H411)

9.3B - Substances that are ecotoxic to terrestrial vertebrates

Hazard Statements

H226 Flammable liquid and vapour.

H301 Toxic if swallowed. H311 Toxic in contact with skin. H315 Causes skin irritation.

Product Name: 976-89935 WEATHERMAX HBR ACCELERATOR Reference No: DLXNZLEN001595

PART C

Issued: 27 January 2020 Version: 1.0 Page 1 of 9



| H317 | May cause an allergic skin reaction. |
|------|--|
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H371 | May cause damage to organs. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H432 | Toxic to terrestrial vertebrates. |

Prevention Precautionary Statements

| P102 | Keep out of reach of children. |
|------|--|
| P103 | Read label before use. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical, ventilating, lighting and all other equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P260 | Do not breathe dust, fume, gas, mist, vapours or spray. |
| P264 | Wash hands, face and all exposed skin thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective clothing, gloves, eye/face protection and suitable respirator. |
| P284 | Wear respiratory protection. |

Response Precautionary Statements

| If medical advice is needed, have product container or label at hand. |
|--|
| IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. |
| IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| IF IN EYES: Rinse cautiously with water for several minutes. Remove contact |
| lenses, if present and easy to do. Continue rinsing. |
| Immediately call a POISON CENTRE or doctor/physician. |
| Rinse mouth. |
| If skin irritation or rash occurs: Get medical advice/attention. |
| Remove/Take off immediately all contaminated clothing. |
| Take off contaminated clothing and wash before reuse. |
| Collect spillage. |
| |

Storage Precautionary Statements

| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |

P405 Store locked up.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 6.1

Subrisk 1: 3

Product Name: 976-89935 WEATHERMAX HBR ACCELERATOR Reference No: DLXNZLEN001595

PART C

Issued: 27 January 2020 Version: 1.0 Page 2 of 9

Ingredients determined to be non-hazardous or below reporting limits



| 3. COMPOSITION INFORMATION | | | | |
|---|------------|---------------|--|--|
| CHEMICAL ENTITY | CAS NO | PROPORTION | | |
| Acetylacetone | 123-54-6 | 30-60 % (w/w) | | |
| Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | 41556-26-7 | 10-30 % (w/w) | | |
| Methyl (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | 82919-37-7 | 1-15 % (w/w) | | |

5593-70-4 1-10 % (w/w) Balance

100%

4. FIRST AID MEASURES

Butanol, titanium salt of

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin Contact: Effects may be delayed. This material, or a component of the material, can be absorbed through the skin with resultant toxic effects. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor. Transport to a doctor or hospital quickly.

PPE for First Aiders: Wear safety shoes, overalls, gloves, face shield, air mask. Use with adequate ventilation. If inhalation risk exists, wear air-supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Hazchem Code: •3W

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Product Name: 976-89935 WEATHERMAX HBR ACCELERATOR Reference No: DLXNZLEN001595

PART C

Issued: 27 January 2020 Version: 1.0 Page 3 of 9



Specific hazards: Flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 17

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Division 6.1 Toxic Substance, Class 3 Flammable Liquid as per the criteria of the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and/or the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by WorkSafe New Zealand.

Biological Limit Values: As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions...

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, FACE SHIELD, AIR MASK.

Product Name: 976-89935 WEATHERMAX HBR ACCELERATOR Reference No: DLXNZLEN001595

PART C

Issued: 27 January 2020 Version: 1.0 Page 4 of 9



Wear safety shoes, overalls, gloves, face shield, air mask. Use with adequate ventilation. If inhalation risk exists, wear air-supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid Colourless Odour: Solvent

Solubility: Soluble in water

Specific Gravity: 0.98 Relative Vapour Density (air=1): >1 Vapour Pressure (20 °C): N Av Flash Point (°C): 30 Flammability Limits (%): 1.0 - 11.4**Autoignition Temperature (°C):** N Av Melting Point/Range (°C): N Av **Boiling Point/Range (°C):** 127 N App Viscosity: N Av Total VOC (g/Litre): N Av

> (Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Fatal if inhaled. Material may be an irritant to mucous membranes and respiratory tract.

Product Name: 976-89935 WEATHERMAX HBR ACCELERATOR Reference No: DLXNZLEN001595

PART C

Issued: 27 January 2020 Version: 1.0 Page 5 of 9



Skin contact: Toxic in contact with skin. Can be absorbed through the skin with resultant toxic effects. Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Toxic if swallowed. Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Acute toxicity

Inhalation: This material has been classified as a 6.1B - Substances that are acutely toxic. Acute toxicity estimate (based on ingredients): $0.5 < LC50 \le 2.0$ mg/L for vapours or $0.05 < LC50 \le 0.5$ mg/L for dust and mist

Skin contact: This material has been classified as a 6.1C - Substances that are acutely toxic. Acute toxicity estimate (based on ingredients): 200 - 1,000 mg/Kg bw

Ingestion: This material has been classified as a 6.1C - Substances that are acutely toxic. Acute toxicity estimate (based on ingredients): 50 - 300 mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as a 8.3A - Substances that are corrosive to ocular tissue. Skin: this material has been classified as a 6.3A - Substances that are irritating to the skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified 6.5B - Substances that are contact sensitisers.

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as a 6.9B - Substances that are harmful to human target organs or systems.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation):

This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

Long-term aquatic hazard: This material has been classified as a 9.1B - Substances that are ecotoxic in the aquatic environment. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 1 - 10 mg/L, where the substance is not rapidly degradable and/or BCF \geq 500 and/or log $K_{ow} \geq$ 4.

Product Name: 976-89935 WEATHERMAX HBR ACCELERATOR Reference No: DLXNZLEN001595

PART C

Issued: 27 January 2020 Version: 1.0 Page 6 of 9



Ecotoxicity in the soil environment: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates: This material has been classified as a 9.3B - Substances that are ecotoxic to terrestrial vertebrates.

Ecotoxicity to terrestrial invertebrates: This material has been classified as non-hazardous.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".





UN No: 2929
Dangerous Goods Class: 6.1
Subrisk 1: 3
Packing Group: II
Hazchem Code: •3W
Emergency Response Guide No: 17

Proper Shipping Name: TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S.

(DECANEDIOIC ACID ESTER; PENTANEDIONE)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), nitromethane, food and food packaging in any quantity. Note 1: Dangerous Goods of Class 6 which are fire risk substances are incompatible with dangerous goods of Class 1, Class 5.1 and Class 5.2. Note 2: Dangerous Goods of Class 6 which are cyanides are incompatible with acids. Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.

Product Name: 976-89935 WEATHERMAX HBR ACCELERATOR Reference No: DLXNZLEN001595

PART C

Issued: 27 January 2020 Version: 1.0 Page 7 of 9







UN No: 2929
Dangerous Goods Class: 6.1
Subrisk 1: 3
Packing Group: II

Proper Shipping Name: TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S. (DECANEDIOIC ACID ESTER; PENTANEDIONE)

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.





UN No: 2929
Dangerous Goods Class: 6.1
Subrisk 1: 3
Packing Group: ||

Proper Shipping Name: TOXIC LIQUID, FLAMMABLE, ORGANIC, N.O.S. (DECANEDIOIC ACID ESTER; PENTANEDIONE)

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

· Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish

International Convention for the Prevention of Pollution from Ships (MARPOL)

• Annex III - Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements:

 All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

 All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

EPA Group Standard: HSR002667 - Surface Coatings and Colourants (Flammable, Toxic [6.1]) Group Standard

Approved handler Yes Location test certificate Yes

Product Name: 976-89935 WEATHERMAX HBR ACCELERATOR Reference No: DLXNZLEN001595

PART C

Issued: 27 January 2020 Version: 1.0 Page 8 of 9



Fire extinguishers Yes
Signage Yes
Emergency response Yes
Hazardous atmosphere zone Yes

16. OTHER INFORMATION

Reason for issue: First Issue

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product Name: 976-89935 WEATHERMAX HBR ACCELERATOR Reference No: DLXNZLEN001595

PART C

Issued: 27 January 2020 Version: 1.0 Page 9 of 9