

### **Hazardous Substance, Dangerous Goods**

#### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

### Product name: 780-Line Duremax GPE Part A

Synonyms:	<b>Product Code</b>	Bar Code
Protective Coatings Duremax GPE N35 Light Grey Part A, 12L	78038678-12L	9300611286512
Protective Coatings Duremax GPE Zinc Phos Grey Part A, 12L	78052033-12L	9300611187222
Protective Coatings Duremax GPE White/Light Base Part A, 12L	78063001-12L	9300611188236
Protective Coatings Duremax GPE White/Light Base Part A, 3.2L	78063001-3.2L	9300611188243
Protective Coatings Duremax GPE Deep Base Part A, 12L	78063002-12L	9300611190161
Protective Coatings Duremax GPE Clear Base Part A, 12L	78063003-12L	9300611190161
Protective Coatings Duremax GPE Part A MTO Colours	-	_

Recommended use: Part A of a two pack protective coating. Also refer to the SDS for Part B.

Supplier: Dulux Protective Coatings Australia, a

division of DuluxGroup (New Zealand)

Pty Ltd

**ABN:** 55 133 404 118 / Co. 2355191

Street Address: 150 Hutt Park Road

Lower Hutt New Zealand

**Telephone:** 0800 800 424

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

#### 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of EPA New Zealand

**EPA Group Standard:** Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006; HSR002669







# **Signal Word** Warning

#### **HSNO Hazard Classification**

3.1C	Flammable liquid
6.1D	Substances that are acutely toxic
6.3A	Substances that are irritating to the skin
6.4A	Substances that are irritating to the eye
6.5B	Substances that are contact sensitisers
6.7B	Substances that are suspected human carcinogens
6.8B	Substances that are suspected human reproductive or developmental toxicants
6.9B	Substances that are harmful to human target organs or systems (repeated exposure)
6.9	Narcotic
9.1B	Substances that are ecotoxic in the aquatic environment
9.3C	Substances that are harmful to terrestrial vertebrates

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 1 of 10



#### **Hazard Statement(s)**

H226	Flammable liquid and vapour
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

H332 Harmful if inhaled

H336 May cause drowsiness or dizziness H351 Suspected of causing cancer

H361 Suspected of damaging fertility or the unborn child

H373 May cause damage to organs through prolonged or repeated exposure

Toxic to aquatic life with long lasting effects H411

Harmful to terrestrial vertebrates H433

#### Prevention Precautionary Statement(s)

Prevention Precautionary Statement(s)				
P102	Keep out of reach of children			
P103	Read label before use			
P201	Obtain special instructions before use			
P202	Do not handle until all safety precautions have been read and understood			
P210	Keep away from all sources of ignition - No smoking			
P233	Keep container tightly closed			
P240	Ground/bond container and receiving equipment			
P241	Use explosion-proof electrical, ventilating, lighting and all other equipment			
P242	Use only non-sparking tools			
P243	Take precautionary measures against static discharge			
P260	Do not breathe mist, vapours or spray			
P264	Wash hands, face and all exposed skin thoroughly after handling			
P270	Do not eat, drink or smoke when using this product			
P271	Use only outdoors or in a well-ventilated area			
P272	Contaminated work clothing should not be allowed out of the workplace			
D. 0 = 0				

P273 Avoid release to the environment

P280 Wear protective clothing, gloves, eye/face protection and suitable respirator as required

# Response Precautionary Statement(s)

P101	If medical advice is needed, have product container or label at hand
P301+310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician
P330	Rinse mouth
D000 - 050	IF ONLOWING West 1911 and a second section

IF ON SKIN: Wash with soap and water P302+352

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower

P362 Take off contaminated clothing and wash before reuse P333+313 If skin irritation or a rash occurs: Get medical advice/attention

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

P312 Call a POISON CENTRE or doctor/physician if you feel unwell

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if

present and easy to do - continue rinsing

P337+313 If eye irritation persists get medical advice/attention P370+378 In case of fire: Use alcohol resistant foam for extinction

Collect spillage P391

#### **Storage Precautionary Statement(s)**

P405 Store locked up

P403+235 Store in a well ventilated place. Keep cool

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 2 of 10



#### **Disposal Precautionary Statement(s)**

P501 Dispose of contents/container in accordance with local, regional, national and international

regulations

#### DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Class: 3 Flammable Liquid

3. COMPOSITION INFORMATION			
CHEMICAL ENTITY	CAS NO.	PROPORTION	
Bisphenol A-Epichlorhydrin reaction product	25068-38-6	10 - 30%	
Xylene, mixture of isomers	1330-20-7	10 - 30%	
Zinc phosphate	7779-90-0	10 - 30%*	
Benzyl alcohol	100-51-6	1 - 10%	
Ethyl benzene	100-41-4	< 1%	
Ingredients determined to be non-hazardous	-	Balance	
		100%	

<sup>\*</sup> For Zinc Phos Grey colour only.

#### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

**Skin contact:** For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance. A component of the material can be absorbed through the skin with resultant toxic effects. Seek medical advice.

**Eye contact:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 3 of 10



**PPE for First Aiders:** Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

Hazchem Code: •3Y

**Suitable extinguishing media:** Alcohol resistant foam is the preferred fire-fighting medium. If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Flammable liquid. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Fire fighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

#### **6. ACCIDENTAL RELEASE MEASURES**

#### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

#### **LARGE SPILLS**

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Use a spark-free shovel. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 14

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 4 of 10



#### 7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Store away from foodstuffs. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Dangerous Good Class 3 Flammable Liquid as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

#### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**National occupational exposure limits:** No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

However for:

	TWA		STEL		CARCINOGEN	NOTICES
	ppm	mg/m3	ppm	mg/m3	CATEGORY	
Xylene	50	217	-	-	-	-
Ethyl benzene	100	434	125	543	-	-

As published by the Safe Work Australia or Department of Labour New Zealand.

WES-TWA (Workplace Exposure Standard – Time-weighted Average). The time-weighted average exposure standard designed to protect the worker for the effects of long-term exposure.

WES-STEL (Workplace Exposure Standard - Short-Term Exposure Limit). The 15-minute average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue changes, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

**Personal protection equipment:** H: OVERALLS, CHEMICAL GOGGLES, SAFETY GLASSES, GLOVES, RESPIRATOR.

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 5 of 10



Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid skin and eye contact and inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Coloured, viscous liquid with a solvent odour.

**Solubility:** Soluble in organic solvents. Insoluble in water.

Specific Gravity (20 ℃): 1.7 Relative Vapour Density (air=1): >1 Vapour Pressure (20 ℃): N Av Flash Point (℃): >23 Flammability Limits (%): N Av Autoignition Temperature (℃): N Av % Volatile by Volume: N Av Solubility in water (g/L): N Av Melting Point/Range (℃): N Av Boiling Point/Range (℃): N Av Decomposition Point ( $\mathfrak{C}$ ): N Av N Av

Viscosity (40 ℃): >21 mm²/sec

Total VOC (g/Litre): N Av

#### 10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

**Chemical stability:** This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes.

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 6 of 10



#### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

**Inhalation:** Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

**Skin contact:** Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis. A component of this material can be absorbed through the skin. Effects can include those described for 'INGESTION'.

**Ingestion:** Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is uncoordinated there is greater likelihood of vomit entering the lungs and causing subsequent complications.

Eye contact: An eye irritant.

#### **Acute toxicity**

**Inhalation:** This material has been classified as a Category 6.1D Hazard. Acute toxicity estimate (based on ingredients): 10 - 20 mg/L

**Skin contact:** This material has been classified as a Category 6.1D Hazard. Acute toxicity estimate (based on ingredients): 1,000 - 2,000 mg/Kg

**Ingestion:** This material has been classified as a Category 6.1D Hazard. Acute toxicity estimate (based on ingredients): 300 - 2,000 mg/Kg

**Corrosion/Irritancy:** Eye: this material has been classified as a Category 6.4A Hazard (reversible effects to eyes).

Skin: this material has been classified as a Category 6.3A Hazard (irritant to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 6.5B Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 6.9 Hazard. Exposure via inhalation may result in depression of the central nervous system.

#### **Chronic Toxicity**

**Mutagenicity:** This material has been classified as non-hazardous.

**Carcinogenicity:** This material has been classified Category 6.7B Hazard.

**Reproductive toxicity (including via lactation):** This material has been classified as a Category 6.8B Hazard. Toxic to reproduction.

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 7 of 10



**Specific target organ toxicity (repeat exposure):** This material has been classified as a Category 6.9B Hazard. Exposure via inhalation may result in effects on the central nervous system.

#### 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as a Category Acute 9.1B Hazard. Acute toxicity estimate (based on ingredients): 1 - 10 mg/L

**Long-term aquatic hazard:** No information is available to complete an assessment.

**Ecotoxicity:** Harmful to terrestrial species.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

#### 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

#### 14. TRANSPORT INFORMATION

#### **ROAD AND RAIL TRANSPORT**

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

**UN No:** 1263

Dangerous Goods Class: 3 Flammable Liquid

Packing Group: III
Hazchem Code: •3Y
Emergency Response Guide No: 14

Proper Shipping Name: PAINT

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2) or radioactive substances (Class 7), however exemptions may apply.

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 8 of 10



#### MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

(\* For Zinc Phos Grey colour only - This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.)

**UN No:** 1263

**Dangerous Goods Class:** 3 Flammable Liquid

Packing Group:

Proper Shipping Name: PAINT

#### **AIR TRANSPORT**

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

**UN No:** 1263

**Dangerous Goods Class:** 3 Flammable Liquid

Packing Group:

Proper Shipping Name: PAINT

#### 15. REGULATORY INFORMATION

#### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

#### This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

- Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish International Convention for the Prevention of Pollution from Ships (MARPOL)
  - Annex III Harmful Substances carried in Packaged Form

#### This material/constituent(s) is covered by the following requirements:

- The Standard for the *Uniform Scheduling of Medicines and Poisons (SUSMP*) established under the *Therapeutic Goods Act (Commonwealth*).
- All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 9 of 10



#### 16. OTHER INFORMATION

#### Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Reason(s) For Issue: Format change

Change in Hazardous Substances Classification.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: 780-Line Duremax GPE Part A SDS No: DLXNZLEN001488

Issued: 11 April 2016 Version: 6.0 Page: 10 of 10