

Safety Data Sheet



Hazardous Substance, Dangerous Goods

1: IDENTIFICATION OF MATERIAL AND SUPPLY COMPANY

Product name: Sceney's Quality Bituminous Black

Synonyms: Cutback 100
Bitumen Paint

Recommended use: General purpose bitumen paint applied using roller, brush or spray.
Outdoor protection for roofing, guttering, barge boards, brickwork, wooden stockyards, storage shed, etc.

Supplier: Sceney's
ABN: 33 006 721 213
Street Address: 17 Third Ave
Sunshine VIC 3020
Australia
Telephone: (03) 9311 7477 (Mon-Fri, 9am-4pm, AEST)
Facsimile: (03) 9312 6911

2: HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION: Classified as hazardous according to Safe Work Australia



Signal Word
Warning

Hazard Classification
Flammable Liquids – Category 3

Hazard Statement(s)
H226 Flammable liquid and vapour

Prevention Precautionary Statement(s)
P102 Keep out of reach of children
P103 Read label before use
P210 Keep away from all sources of ignition – No smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion-proof electrical, ventilating, lighting and all other

Product Name: Sceney's Quality Bituminous Black

Safety Data Sheet



- equipment.
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.

Response Precautionary Statement(s)

- P101 If medical advice is needed, have product container or label at hand
P303+P361+P353 If ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378 In case of fire: Use alcohol resistant foam, standard foam or dry agent for extinguishing

Storage Precautionary Statement(s)

- P403+P233 Store in a well ventilated place. Keep container tightly closed.

Disposal Precautionary Statement(s)

- P501 Dispose of container in accordance with regional and national regulations.

Dangerous Goods Classification

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code for the Transport of Dangerous Goods by Road & Rail.

Class: 3 Flammable Liquid

3: COMPOSITION INFORMATION

<u>CHEMICAL ENTITY</u>	<u>CAS NUMBER</u>	<u>PROPORTION</u>
BITUMEN	(8052-42-4)	40 - < 60 %
LIQUID HYDROCARBONS	(64742-88-7)	40 - < 60 %

4: First Aid Measures

If poisoning occurs seek medical assistance or contact:

Poisons Information Centre on 131 126

INGESTION/SWALLOWED: Do not induce vomiting. Rinse mouth with water. Give a glass of water to drink. If vomiting occurs give further water to drink. **SEEK MEDICAL ASSISTANCE.**

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. **SEEK MEDICAL ADVICE.**

Safety Data Sheet



SKIN CONTACT: For large scale contamination, drench with water and remove contaminated clothing. Wash skin and hair thoroughly with soap and water. If blistering occurs, cover with a clean bandage and SEEK MEDICAL ASSISTANCE.

INHALATION: Remove casualty to fresh air and keep at rest until recovered. If not breathing, apply artificial respiration. If in cardiac arrest, apply external cardiac massage. SEEK MEDICAL ASSISTANCE.

PPE for FIRST AIDERS: Overalls, safety glasses, PVC or Nitrile gloves. If exposed to vapours, use respirator with organic vapour filter.

ADVICE TO DOCTOR: Product may be removed from skin using cotton wool pads soaked in castor oil or hand cleaner. Treatment should be directed toward control of symptoms and conditions.

5: Fire Fighting Measures

HAZCHEM CODE: 2W

FIRE EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide, and water fog.

SPECIFIC HAZARDS: Flammable Liquid. Can form flammable vapour mixtures with air. Avoid ignition sources. Flameproof/explosion proof equipment to be used where vapours are present. No smoking.

FIRE AND EXPLOSION HAZARD: Closed containers may explode when exposed to heat (fire). Keep containers cool with water spray. This product will emit flammable vapours. Will produce toxic fumes when burning – wear breathing apparatus.

6: Accidental Release Measures

SMALL SPILLS: Wear safety glasses, impermeable gloves and organic vapour respirator if required. Clean up with rags or paper towels. Allow to dry in well ventilated area and dispose of with dray waste.

LARGE SPILLS: Stop source of leak/loss of containment if safe to do so. Isolate and eliminate ignition sources. Remove all non - essential personnel from area. Clean up personnel to wear boots overalls, solvent proof gloves, goggles or face visor and organic vapour respirator. Work upwind and/or provide intrinsically safe ventilation. Prevent contamination of drains and waterways. Use absorbent to clean up spilt material using non sparking tools. Collect spent absorbent material in sealed drums or containers and dispose of according to local environmental authority requirements. Seek assistance of EPA and emergency services if there is

Safety Data Sheet



a chance of entering drains and water ways.

7: Handling and Storage

DANGEROUS GOODS CLASS: 3 PKG III **SUB RISK:** None

Handling: Avoid skin contact and inhalation of vapour and mist. Do not use pressure to empty drums.

Storage: Store in a cool dry place according to the requirements for a manufactured packaged product containing class 3 flammable liquid. Store in areas/building designed to comply with the appropriate dangerous goods regulations. Protect from physical damage. Keep container closed when not in use.

Transport: should be in accordance with the Australian Dangerous Goods Code for the transport of dangerous goods by road and rail.

8: Exposure Controls, Personal Protection

National Exposure Standards: There is no Australian Workplace Standard for this product.

However, TWA for white spirits is 790 mg/m³ according to Safe Work Australia.

TWA is **T**ime **W**eighted **A**verage airborne concentration over an eight hour period five days per week over an entire working life.

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use. These directions should prevent the TWA being exceeded.

Biological Limit Values: No Biological Limit Value allocated as per the National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia).

ENGINEERING CONTROLS: Keep containers closed when not in use. Ensure ventilation is adequate to maintain air concentrations below exposure standards. Use only in well ventilated areas. If ventilation cannot be provided, wear organic vapour respirator. Do not enter confined spaces where vapours may have accumulated.

PERSONAL PROTECTION EQUIPMENT: YELLOW: OVERALL, SAFETY SHOES OR BOOTS, SAFETY GLASSES, GLOVES, RESPIRATOR.

Safety Data Sheet



A respirator suitable for organic vapours must be used In poorly ventilated areas. Air supplied respirators should be used in areas with inadequate oxygen and high vapour concentrations.

Glove type - PVC gloves or other solvent proof gloves should be used when handling material.

Eye protection - Use close fitting chemical safety goggles, otherwise use safety glasses fitted with side shields. If splashing is possible use a face shield over safety glasses as added protection.

Clothing protection – Wear industrial-type work clothing or overalls and safety footwear.

Workplace- Ensure that eyewash and safety shower are available and in good working condition wherever this product is being used or manufactured.

Hygiene measures: Keep away from food and drink. Do not eat or drink while using this product. Always wash hands thoroughly prior to eating, drinking or using the toilet. Always launder or replace contaminated clothing or PPE before storing or reusing.

9: Physical and Chemical Properties

FORM:	Liquid
APPEARANCE:	Black paint
ODOUR:	Mineral Turps characteristic odour
PACK SIZE(S):	20 litre, 205 litre
BOILING POINT (°C):	> 149° C
MELTING POINT (°C):	Not Applicable
VAPOUR PRESSURE (KPa) :	<3.3
SPECIFIC GRAVITY @ 25 °C:	0.92
SOLUBILITY IN WATER (% BY WT.):	Not soluble
FLASH POINT (°C)-METHOD:	38° C (closed cup)
FLAMMABILITY LIMITS IN AIR (% VOLUME):	LOWER UPPER
	0.4 7
VOLATILE ORGANIC COMPOUNDS:	50%
AUTOIGNITION TEMPERATURE:	250 ° C

Safety Data Sheet



10: Stability and Reactivity

Reactivity: Strong oxidising agents will violently react with this product otherwise, no reactivity hazards are known.

Chemical Stability: This product is thermally stable at ambient temperatures.

Conditions to avoid: Elevated temperatures and ignition sources.

Incompatible materials: Oxidising Agents.

Hazardous Decomposition Products: Carbon monoxide and carbon dioxide.

11: Toxicological Information

No adverse health effects can be expected provided that the product is handled and used in accordance with the directions of this Safety Data Sheet.

Possible health effects from overexposure or misuse:

ACUTE EFFECTS:

Swallowed: Ingestion of material may cause gastrointestinal disturbance, including irritation, nausea and vomiting.

Eyes: Direct eye contact may cause irritation.

Skin: Contact with skin may result in skin reactions.

Inhalation: Inhalation of vapours may cause headaches and/or dizziness. Overexposure to vapour may result in respiratory tract irritation.

CHRONIC:

Mutagenicity: Not classified as a mutagen

Carcinogenicity: Not classified as a carcinogen

Reproductive toxicity: Not classified.

Specific Target Organ Toxicity (repeat exposure): Not classified.

12: Ecological Information

Do not allow product to enter waste water, stormwater, rivers or creeks.

Acute Aquatic Hazard: Not determined as a marine pollutant however, before drying, will form a slick on top of water which could be hazardous to birds and fish. Residual bitumen is non-toxic and non-soluble in water.

Long term Aquatic Hazard: No information is available

Ecotoxicity: No information is available.

Persistence and degradability: No information is available.

Bioaccumulative potential: No information is available.

Mobility: No information is available.

Safety Data Sheet



13: Disposal Considerations

Disposal Methods:

Wherever possible, re-use, reprocess or recycle any reclaimed material to reduce waste.

Contained spills need to be soaked up and disposed into a metal container (avoid using plastic containers).

Once dry, the absorbed material may be disposed of as solid waste in conformity with the requirements of the Regulatory Authorities.

Refer Section 8 for Exposure Controls

14: Transport Information

Road and Rail Transport: Classified as Dangerous Goods by the Australian Dangerous Goods Code for Transport by Road and Rail

U.N. Number: 1999

Proper Shipping Name: Tars, liquid, including road oils and cutback bitumen

DG Class: 3

Packing Group: III

Hazchem Code: 2W

Emergency Response Guide No 15

Segregation: Not to be loaded with Class 1 Explosives, Class 2.1 Flammable Gases, Class 2.3 Toxic Gases, Class 4.2 Spontaneously Combustible Substances, Class 5.1 Oxidising Agents, Class 5.2 Organic Peroxides or Class 7 Radioactive Substances. Segregation devices and exemptions may apply.

Marine Transport: Classified as Dangerous Goods by the International Maritime Dangerous Goods Code (IMDG Code) for Transport by Sea.

Air Transport: Classified as Dangerous Goods by the International Air Transport Association (IATA). Dangerous Goods Regulations for transport by air.

15: Regulatory Information

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Safety Data Sheet



This material is subject to the following requirements:

Australian Dangerous Goods Code, IMDG, IATA

Class: Class 3 PG III

U.N. Number: 1999

Proper Shipping Name: Tars Liquid, including Road Oils and Cutback Bitumen

The Standard for the Uniform Scheduling of Medicines and Poisons

(SUSMP) Therapeutic Goods Act (Commonwealth)

Poisons Schedule: S5

Storage:

AS1940 AND AS3833 FOR STORAGE REQUIREMENTS.

16: Other Information

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the manufacturer/supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

END OF SDS