

Safety Data Sheet



POWDER & INDUSTRIAL COATINGS

Hazardous Chemical, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **405G0080 VELOCITY CLEAR SEALER**

Synonyms

405G0080 Velocity Clear Sealer 20 kg

Product Code

405G0080-20Kg

Bar Code

Recommended use: Primer/sealer for industrial use by Roll coat

Supplier: Dulux Powder & Industrial Coatings, a division of DuluxGroup (Australia) Pty Ltd

ABN: 67 000 049 427

Street Address: 1956 Dandenong Road
Clayton VIC 3168
Australia

Telephone: 13 25 25

Emergency Telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word

Warning

Hazard Classifications

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Irritation - Category 2A

Sensitisation - Skin - Category 1

Specific Target Organ Toxicity (Single Exposure) - Category 3 Respiratory Tract Irritation

Hazard Statements

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

Prevention Precautionary Statements

- P102 Keep out of reach of children.
- P103 Read label before use.
- P261 Avoid breathing dust, fume, gas, mist, vapours or spray..
- P264 Wash hands, face and all exposed skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.

Response Precautionary Statements

Product Name: 405G0080 VELOCITY CLEAR SEALER

Reference No: DLXGHSEN003343

Issued: 1 February 2019

Version: 1.0

Page 1 of 8

Safety Data Sheet



POWDER & INDUSTRIAL COATINGS

P101 If medical advice is needed, have product container or label at hand.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

Storage Precautionary Statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule: Not Applicable

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 9

Australian Special Provisions; AU01: Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subject to this Code (ADG 07) when transported by road or rail in;

- (a) packagings that do not incorporate a receptacle exceeding 500 Kg (L); or
- (b) IBCs.

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Bisphenol A diglycidyl ether di-acrylate	55818-57-0	30-60 % (w/w)
1,6-Hexandiol diacrylate	13048-33-4	10-30 % (w/w)
Tri(propylene glycol) diacrylate	42978-66-5	10-30 % (w/w)
Ingredients determined to be Non-Hazardous		Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: Effects may be delayed. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

Safety Data Sheet



Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Hazchem Code: •3Z

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 47

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

Safety Data Sheet



POWDER & INDUSTRIAL COATINGS

This material is classified as a Class 9 Miscellaneous Dangerous Good as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES, RESPIRATOR.

Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Colour: Clear
Odour: Typical, acrylic

Solubility: Insoluble in water
Specific Gravity: 1.13
Relative Vapour Density (air=1): >1
Vapour Pressure (20 °C): N Av
Flash Point (°C): >100
Flammability Limits (%): N App
Autoignition Temperature (°C): N Av
Melting Point/Range (°C): N Av
Boiling Point/Range (°C): >100
pH: N App
Viscosity: >21 mm²/sec @ 40 °C
Total VOC (g/Litre): N Av

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Product Name: 405G0080 VELOCITY CLEAR SEALER

Reference No: DLXGHSEN003343

Issued: 1 February 2019

Version: 1.0

Page 4 of 8

Safety Data Sheet



Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material is an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant.

Acute toxicity

Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 20.0 mg/L for vapours or LC50 > 5.0 mg/L for dust and mist or LC50 > 20,000 ppm for gas

Skin contact: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

Ingestion: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Safety Data Sheet



Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

Long-term aquatic hazard: This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K_{ow} < 4.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Australian Special Provisions; AU01: Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subject to this Code (ADG 07) when transported by road or rail in;

- (c) packagings that do not incorporate a receptacle exceeding 500 Kg (L); or
- (d) IBCs.



UN No: 3082
Dangerous Goods Class: 9
Packing Group: III
Hazchem Code: •3Z
Emergency Response Guide No: 47

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A DIGLYCIDYL ETHER DI-ACRYLATE; HEXAMETHYLENE DIACRYLATE)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1). Note 1: Materials that are fire risks are incompatible with oxidising agents (Class 5.1) or organic peroxides (Class 5.2). Exemptions may apply.

Safety Data Sheet



MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



UN No: 3082
Dangerous Goods Class: 9
Packing Group: III

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A DIGLYCIDYL ETHER DI-ACRYLATE; HEXAMETHYLENE DIACRYLATE)

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 3082
Dangerous Goods Class: 9
Packing Group: III

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A DIGLYCIDYL ETHER DI-ACRYLATE; HEXAMETHYLENE DIACRYLATE)

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

- All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Reason for issue: First Issue

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its

Safety Data Sheet



client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.