

Hazardous, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: SELLEYS 635 MULTIPURPOSE ELASTIC SEALANT CLEAR

SynonymsProduct CodeBar CodeSelleys 635 Multipurpose Elastic Sealant Clear 290mL1033559300697132956

Recommended use: Sealant

Supplier: Selleys, a division of DuluxGroup (Australia) Pty Ltd

ABN: 67 000 049 427

Street Address: 1956 Dandenong Road

Clayton VIC 3168

Australia

Telephone: 1300 555 205

Emergency Telephone number: Australia – 1800 220 770; New Zealand – 0800 220 770

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7.



Signal Word

Warning

Hazard Classifications

Eye Damage/Irritation - Category 2A Sensitisation - Skin - Category 1

Hazard Statements

H317 May cause an allergic skin reaction.H319 Causes serious eye irritation.

Prevention Precautionary Statements

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust, fume, gas, mist, vapours or spray.

P264 Wash hands, face and all exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing including eye/face protection.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.

Product Name: SELLEYS 635 MULTIPURPOSE ELASTIC Reference No: SELGHSEN001463

SEALANT CLEAR

Issued: 20 November 2023 Version: 1.0 Page 1 of 7



P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse

Storage Precautionary Statement

Not allocated

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

Poison Schedule: Not Applicable

3. COMPOSITION INFORMATION

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

CHEMICAL ENTITY	CAS NO	PROPORTION
1-Propanamine, 3-(trimethoxysilyl)-	13822-56-5	1 - 10 % (w/w)
Silane, trimethoxy[3-(oxiranylmethoxy)propyl]-	2530-83-8	1 - 10 % (w/w)
Trimethoxyvinylsilane	2768-02-7	1 - 10 % (w/w)
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	<1 % (w/w)
Hydroxyphenylbenzotriazole derivative	104810-47-1	<1 % (w/w)
Methyl (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	82919-37-7	<1 % (w/w)
Ingredients determined to be non-hazardous or below reporting limits		Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: Effects may be delayed. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink.

Product Name: SELLEYS 635 MULTIPURPOSE ELASTIC Reference No: SELGHSEN001463

SEALANT CLEAR

Issued: 20 November 2023 Version: 1.0 Page 2 of 7



Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of dust.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

Product Name: SELLEYS 635 MULTIPURPOSE ELASTIC Reference No: SELGHSEN001463

SEALANT CLEAR

Issued: 20 November 2023 Version: 1.0 Page 3 of 7



Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES.

Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Paste Colour: Clear

Odour: Characteristic

Solubility: Insoluble in water

Specific Gravity: Relative Vapour Density (air=1): >1 Vapour Pressure: N Av Flash Point (°C): N App Flammability Limits (%): N App **Autoignition Temperature (°C):** N Av Melting Point/Range (°C): N Av **Boiling Point/Range (°C):** N Av pH: N App

Viscosity: >20.5 mm²/s @ 40 °C

Total VOC (g/Litre): N Av

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.


Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

Product Name: SELLEYS 635 MULTIPURPOSE ELASTIC Reference No: SELGHSEN001463

SEALANT CLEAR

Issued: 20 November 2023 Version: 1.0 Page 4 of 7



11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin may result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 5.0$ mg/L for dust.

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Corrosion/Irritancy: Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as not a specific hazard to target organs by a single exposure.

Chronic Toxicity

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as not a carcinogen.

Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.

Specific target organ toxicity (repeat exposure): This material has been classified as not a specific hazard to target organs by repeat exposure.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Product Name: SELLEYS 635 MULTIPURPOSE ELASTIC Reference No: SELGHSEN001463

SEALANT CLEAR

Issued: 20 November 2023 Version: 1.0 Page 5 of 7



Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Long-term aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K_{ow} < 4.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): Not Applicable.

Product Name: SELLEYS 635 MULTIPURPOSE ELASTIC Reference No: SELGHSEN001463

SEALANT CLEAR

Issued: 20 November 2023 Version: 1.0 Page 6 of 7



AICIS Status: All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).

NZ EPA Status: All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

HSNO Group Standard: HSR002670 - Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020

16. OTHER INFORMATION

Reason for issue: First Issue

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the company cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product Name: SELLEYS 635 MULTIPURPOSE ELASTIC Reference No: SELGHSEN001463

SEALANT CLEAR

Issued: 20 November 2023 Version: 1.0 Page 7 of 7