

Reference No: SELVNMEN001239

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: SELLEYS EPOXY FIX SUPER FAST - PART B

Synonyms Product Code Bar Code

SELLEYS EPOXY FIX SUPER FAST - PART B, 17.5mL - SELLEYS EPOXY FIX SUPER FAST - PART B, 7.5mL - SELLEYS EPOXY FIX SUPER FAST - PART B, 10mL - -

Recommended use: Adhesive.

Supplier: Nippon Paint (Vietnam) Co., Ltd

Street Address: No. 14, 3A Road, Bien Hoa Industrial Zone 2, Lon Binh Tan Ward, Bien Hoa,

Dong Nai, Vietnam

Telephone: +84 251 3836 579

Emergency Telephone number: +613 9663 2130

2. HAZARDS IDENTIFICATION

This material is classified as hazardous according to Circular No. 32/2017/TT-BCT dated December 28, 2017 specifying and providing guidelines for implementation of certain articles of the Law on Chemicals and Decree 113/2017/ND-CP specifying and providing guidelines for implementation of certain articles of the Law on Chemicals.



Signal Word

Warning

Hazard Classifications

Sensitisation - Skin - Category 1

Chronic Hazard to the Aquatic Environment - Category 3

Hazard Statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Prevention Precautionary Statements

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing fume, gas, mist, vapours or spray.

Product Name: SELLEYS EPOXY FIX SUPER FAST - PART B

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing including eye/face protection.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.

Issued: 2022-09-21 Version: 2.0 Page 1 of 7



P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse

Storage Precautionary Statement

Not allocated

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Decree No. 104/2009/ND-CP of November 09, 2009, providing for the list of dangerous goods and the transport of dangerous goods by road motor vehicles."

3. COMPOSITION INFORMATION

CHEMICAL ENTITY CAS NO PROPORTION

Pentaerythritol-propylene oxide-mercaptoglycerol polymer

Ingredients determined to be Non-Hazardous

72244-98-5 >= 90 % (w/w)

Balance

100%

4. FIRST AID MEASURES

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: Effects may be delayed. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray),

Product Name: SELLEYS EPOXY FIX SUPER FAST - PART B Reference No: SELVNMEN001239

Issued: 2022-09-21 Version: 2.0 Page 2 of 7



alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES.

Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

Product Name: SELLEYS EPOXY FIX SUPER FAST - PART B Reference No: SELVNMEN001239
Issued: 2022-09-21 Version: 2.0 Page 3 of 7



9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid Clear Odour: Nauseating

Solubility: Immiscible in water

Density: 1.13 g/mL

Relative Vapour Density (air=1): N Av Vapour Pressure: N Av Flash Point (°C): N Av Flammability Limits (%): N Av **Autoignition Temperature (°C):** N Av Melting Point/Range (°C): N Av Boiling Point/Range (°C): N Av pH: ggA N

Viscosity: 9,000 - 15,000 cP

Total VOC (g/Litre): N Av

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon, nitrogen and sulphur, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin may result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: May be an eye irritant.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity

Product Name: SELLEYS EPOXY FIX SUPER FAST - PART B Reference No: SELVNMEN001239 Issued: 2022-09-21 Version: 2.0 Page 4 of 7



Reference No: SELVNMEN001239

estimate (based on ingredients): LC₅₀ > 20.0 mg/L for vapours or LC₅₀ > 5.0 mg/L for dust and mist.

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as not a specific hazard to target organs by a single exposure.

Chronic Toxicity

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as not a carcinogen.

Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.

Specific target organ toxicity (repeat exposure): This material has been classified as not a specific hazard to target organs by repeat exposure.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Long-term aquatic hazard: This material has been classified as a Category Chronic 3 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 10 - 100 mg/L, where the substance is not rapidly degradable and/or BCF \geq 500 and/or log $K_{ow} \geq 4$.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Product Name: SELLEYS EPOXY FIX SUPER FAST - PART B

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal

Issued: 2022-09-21 Version: 2.0 Page 5 of 7



protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Decree No. 104/2009/ND-CP of November 09, 2009, providing for the list of dangerous goods and the transport of dangerous goods by road motor vehicles."

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 3334

Dangerous Goods Class: 9

Packing Group: III

Proper Shipping Name: AVIATION REGULATED LIQUID, N.O.S. (MERCAPTAN-

TERMINATED POLMER)

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

Decree No. 113 - 2017 ND-CP- Chemicals subject to conditional production or import None of the components are listed.

Decree No. 113 - 2017 ND-CP- Chemicals restricted from production or trade None of the components are listed.

Decree No. 113 - 2017 ND-CP- Banned and toxic chemicals

None of the components are listed.

Product Name: SELLEYS EPOXY FIX SUPER FAST - PART B

Issued: 2022-09-21

Version: 2.0

Page 6 of 7



Decree No. 113 - 2017 ND-CP- Hazardous chemicals for which chemical incident prevention and response plans are required

None of the components are listed

Decree No. 113 - 2017 ND-CP- Chemicals subject to compulsory declarations

None of the components are listed

16. OTHER INFORMATION

Reason for issue: Revised

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the company cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product Name: SELLEYS EPOXY FIX SUPER FAST - PART B Reference No: SELVNMEN001239
Issued: 2022-09-21 Version: 2.0 Page 7 of 7