

Material Safety Data Sheet



Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **31K-Line Dulux Duramax High Performance Enamel Flat Metal Primer Grey Spray Pack**

| | | |
|---|--------------------------------------|------------------------|
| Synonyms: Dulux Duramax High Performance Enamel Flat Metal Primer Grey, 340g | Product Code 31KD1231-340G | Bar Code TBC |
|---|--------------------------------------|------------------------|

Recommended use: Aerosol spray pack paint for general small project painting.

Supplier: Dulux Australia, a division of
DuluxGroup (Australia) Pty Ltd
ABN: 67 000 049 427
Street Address: 1956 Dandenong Road
Clayton VIC 3168
Australia
Telephone: 13 25 25

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.

Hazard Category:
Xi Irritant

Risk Phrase(s):
R12: Extremely Flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Safety Phrase(s):
S1/2: Keep locked up and out of the reach of children.
S16: Keep away from sources of ignition.
S23: Do not breathe vapour.
S36/39: Wear suitable protective clothing and eye/face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible).

Poisons Schedule (Aust): Not applicable

Product name: 31K-Line Dulux Duramax High Performance Enamel Flat Metal Primer Grey Spray Pack SDS No: DLXTOLEN000422

Issued: 29 May 2014

Version: 1.0

Page: 1 of 8

Material Safety Data Sheet



DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Class: 2.1 Flammable Gas

3. COMPOSITION INFORMATION

| CHEMICAL ENTITY | CAS NO. | PROPORTION |
|--|----------|------------|
| Acetone | 67-64-1 | 30 - 60% |
| n-Butyl acetate | 123-86-4 | 10 - 30% |
| Propane | 74-98-6 | 10 - 30% |
| Butane | 106-97-8 | 1 - 10% |
| Isobutane | 75-28-5 | * |
| Refined naphtha (petroleum) | - | * |
| Propan-2-ol | 67-63-0 | * |
| 2-Methoxy-1-methylethyl acetate | 108-65-6 | * |
| Ingredients determined to be non-hazardous | - | Balance |
| | | <hr/> 100% |

*Additive total is 10%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. A component of this material, can be absorbed through the skin with resultant toxic effects. Seek medical advice.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. Seek medical advice.

Notes to physician: Treat symptomatically.

Product name: 31K-Line Dulux Duramax High Performance Enamel Flat Metal Primer Grey Spray Pack SDS No: DLXTOLEN000422

Issued: 29 May 2014

Version: 1.0

Page: 2 of 8

Material Safety Data Sheet



5. FIRE-FIGHTING MEASURES

Specific hazards: Flammable liquid and flammable gas. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: 2YE

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: 49

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Dangerous Good Class 2.1 Flammable Gas as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

Material Safety Data Sheet



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

However for:

| | TWA | | STEL | | CARCINOGEN CATEGORY | NOTICES |
|---------------------------------|-----|-------|-------|-------|------------------------|------------|
| | ppm | mg/m3 | ppm | mg/m3 | | |
| Acetone | 500 | 1,185 | 1,000 | 2,375 | - | - |
| n-Butyl acetate | 150 | 713 | 200 | 950 | - | - |
| Propane | - | - | - | - | - | Asphyxiant |
| Butane | 800 | 1,900 | - | - | - | - |
| Propan-2-ol | 400 | 983 | 500 | 1,230 | - | - |
| 2-Methoxy-1-methylethyl acetate | 50 | 274 | 100 | 548 | - | Sk |

As published by the Safe Work Australia or Department of Labour New Zealand.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Asphyxiant - gases which can lead to reduction of oxygen concentration by displacement or dilution. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.

`Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Keep containers closed when not in use.

Personal protection equipment: B: OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.

Wear overalls, safety glasses and impervious gloves. Available information suggests that gloves made from butyl rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Product name: 31K-Line Dulux Duramax High Performance Enamel Flat Metal Primer Grey Spray Pack **SDS No:** DLXTOLEN000422

Issued: 29 May 2014

Version: 1.0

Page: 4 of 8

Material Safety Data Sheet



Hygiene measures: Avoid skin and eye contact and inhalation of vapour, mist or aerosols. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Grey aerosol with a solvent odour.

| | |
|---|--|
| Solubility: | Soluble in organic solvents. Insoluble in water. |
| Specific Gravity (20 °C): | 0.89 |
| Relative Vapour Density (air=1): | >1 |
| Vapour Pressure (20 °C): | 8300 hPa |
| Flash Point (°C): | N Av |
| Flammability Limits (%): | LEL – 1.2; UEL – 13.0 |
| Autoignition Temperature (°C): | N Av |
| Melting Point/Range (°C): | N Av |
| Boiling Point/Range (°C): | N Av |
| pH: | N App |
| Viscosity: | N Av |
| Total VOC (g/Litre): | 725.3 g/L |

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness. A component of this material is an asphyxiant; exposure to high concentrations can cause suffocation.

Material Safety Data Sheet



Skin contact: Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis. A component of this material can be absorbed through the skin. Effects can include those described for 'INGESTION'.

Ingestion: Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is uncoordinated there is greater likelihood of vomit entering the lungs and causing subsequent complications.

Eye contact: An eye irritant.

Long Term Effects: No information available for product.

Acute toxicity / Chronic toxicity: No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

| | |
|-------------------------------------|---------------|
| UN No: | 1950 |
| Dangerous Goods Class: | 2.1 |
| Packing Group: | Not allocated |
| Hazchem Code: | 2YE |
| Emergency Response Guide No: | 49 |

Proper Shipping Name: AEROSOLS

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable liquids (Class 3), if both are in bulk, flammable solids (Class 4.1), spontaneously combustible substances (Class 4.2), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2) or radioactive substances (Class 7), however exemptions may apply.

Product name: 31K-Line Dulux Duramax High Performance Enamel Flat Metal Primer Grey Spray Pack **SDS No:** DLXTOLEN000422

Issued: 29 May 2014

Version: 1.0

Page: 6 of 8

Material Safety Data Sheet



MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1950
Dangerous Goods Class: 2.1
Packing Group: Not allocated

Proper Shipping Name: AEROSOLS

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1950
Dangerous Goods Class: 2.1
Packing Group: Not allocated

Proper Shipping Name: AEROSOLS, FLAMMABLE

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

- Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish

International Convention for the Prevention of Pollution from Ships (MARPOL)

- Annex III - Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements:

- All the constituents of this material are listed on the *Australian Inventory of Chemical Substances (AICS)*.

Product name: 31K-Line Dulux Duramax High Performance Enamel Flat Metal Primer Grey Spray Pack **SDS No:** DLXTOLEN000422

Issued: 29 May 2014

Version: 1.0

Page: 7 of 8

Material Safety Data Sheet



16. OTHER INFORMATION

Literary reference

This Material Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Reason(s) For Issue: First Issue

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.