

constructive solutions

Hazardous, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: FOSROC RENDEROC LA55

SynonymsProduct CodeBar CodeFosroc Renderoc LA55 20KGFC302030-20KG9330221006132

Recommended use: Cementitious repair mortar. Applied by pump.

Supplier: Parchem Construction Supplies Pty Ltd

Company No.: 80 069 961 968
Street Address: 7 Lucca Road

Wyong NSW 2259

Australia

Telephone: (02) 4350 5000

Emergency Telephone number: Australia – 1800 220 770; New Zealand – 0800 220 770

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of EPA New Zealand GHS 7.

EPA Group Standard: HSR002670 - Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020



Signal Word

Danger

Hazard Classifications

Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Irritation - Category 1

Specific target organ toxicity following single exposure - Category 3 - Respiratory Tract Irritation

Hazard Statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Prevention Precautionary Statements

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust, fume, gas, mist, vapours or spray...

P264 Wash hands, face and all exposed skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing including eye/face protection and suitable

respirator.

Product Name: FOSROC RENDEROC LA55 Reference No: PARNZ7EN000068 Issued: 26 October 2021 Version: 3.0 Page 1 of 7



constructive solutions

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/insert appropriate source of emergency

medical advice.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing.

Storage Precautionary Statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Crystalline silica (contains <0.1% respirable) Cement, portland, chemicals Calcium oxide 1,3-Propanediol, 2,2-dimethyl- Ingredients determined to be non-hazardous or below reporting limits	14808-60-7 65997-15-1 1305-78-8 126-30-7	>60 % (w/w) 10 - 30 % (w/w) 1 - 10 % (w/w) <1 % (w/w) Balance
		100%

100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

Eye contact: Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Product Name: FOSROC RENDEROC LA55 Reference No: PARNZ7EN000068

Issued: 26 October 2021 Version: 3.0 Page 2 of 7



PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses, dust mask. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of dust.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

Product Name: FOSROC RENDEROC LA55

TWA STEL NOTICES

Reference No: PARNZ7EN000068

ppm mg/m3 ppm mg/m3

Issued: 26 October 2021 Version: 3.0 Page 3 of 7



Calcium oxide 2
Portland cement 10(a)
Silica-Crystalline (Quartz) respirable dust 0.2

6.7A 2011

As published by WorkSafe New Zealand.

WES-TWA (Workplace Exposure Standard - Time-weighted average). The average airborne concentration of a substance calculated over an eight-hour working day.

WES-Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not be exceeded at any time during any part of the working day.

WES-STEL (Workplace Exposure Standard - Short-term exposure limit). The 15-minute time weighted average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Exposures at concentrations between the WES-TWA and the WES-STEL should be less than 15 minutes, should occur no more than four times per day, and there should be at least 60 minutes between successive exposures in this range.

Confirmed carcinogen. Carcinogen - known or presumed human carcinogen: the substance is either known to be carcinogenic to humans, or data indicates sufficient evidence in animal studies to demonstrate a causal relationship between human exposure and the development of cancer, or an increase in tumours.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Avoid generating and inhaling dusts. Use with local exhaust ventilation or while wearing dust mask.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES, DUST MASK.

Wear safety shoes, overalls, gloves, safety glasses, dust mask. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or reusing.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Powder
Colour: Grey
Odour: Cementitious

Product Name: FOSROC RENDEROC LA55 Reference No: PARNZ7EN000068

Issued: 26 October 2021 Version: 3.0 Page 4 of 7



Reference No: PARNZ7EN000068

Solubility: Insoluble in water.

Specific Gravity: 1.65 Relative Vapour Density (air=1): >1 Vapour Pressure (20 °C): N Av Flash Point (°C): N App Flammability Limits (%): N App **Autoignition Temperature (°C):** N App Melting Point/Range (°C): N Av Boiling Point/Range (°C): N Av Decomposition Point (°C): N Av :Hq N Av Viscosity: N Av Total VOC (g/Litre): N Av

> (Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material is an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in irritation.

Product Name: FOSROC RENDEROC LA55

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 5.0$ mg/L for dust.

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity

Issued: 26 October 2021 Version: 3.0 Page 5 of 7



Reference No: PARNZ7EN000068

estimate (based on ingredients): LD₅₀ > 2,000 mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as a Category 1 Hazard (irreversible effects to eyes). Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Chronic aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log Kow < 4.

Ecotoxicity in the soil environment: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial invertebrates: This material has been classified as non-hazardous.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Product Name: FOSROC RENDEROC LA55

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

Issued: 26 October 2021 Version: 3.0 Page 6 of 7



14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

NZ EPA Status: All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

AIICS Status: All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).

EPA Group Standard: HSR002670 - Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020

16. OTHER INFORMATION

Reason for issue: Revised

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the company cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product Name: FOSROC RENDEROC LA55 Reference No: PARNZ7EN000068

Issued: 26 October 2021 Version: 3.0 Page 7 of 7