

Print Date: 04-27-2017

MAXBOND CONSTRUCTION
ADHESIVE
832727PM**SAFETY DATA SHEET**

REVISION DATE: 04-26-2017

SUPERSEDES: 10-14-2016

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER**PRODUCT INFORMATION**

PRODUCT: MAXBOND CONSTRUCTION ADHESIVE
PRODUCT DESCRIPTION: Solvent based adhesive
INTENDED USE: Industrial adhesive
PRODUCT IDENTIFIER: 832727PM

COMPANY INFORMATION

H.B. Fuller Company Australia Pty. Ltd.
16 - 22 Red Gum Drive
Dandenong South, VIC 3175
Telephone: (03) 9797 6222
Emergency telephone No: 1800 033 111
Emergency Tel NZ: 0800 734 607 (or IDD +64 473 4607)

SECTION 2: HAZARDS IDENTIFICATION**GHS Hazard Symbols:**

GHS Symbol name(s): Flame
GHS Signal Word: Danger
GHS Classification: Flammable Liquid Category 2
GHS Hazard Phrases: Highly flammable liquid and vapour.
GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to extinguish.

Storage: Keep container tightly closed.
Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
---------------	-------	---------	----------------	------

Print Date: 04-27-2017

SAFETY DATA SHEET

Kaolin clay	1332-58-7	30 - 50		* (see below)
Aliphatic petroleum distillate	64742-49-0	10 - 30	Asp. Tox. 1; H304 Flam. Liq. 1; H224	Note P
Aromatic petroleum distillate	64742-95-6	1 - 5	Asp. Tox. 1; H304 Flam. Liq. 1; H224	Note P
Ethyl alcohol	64-17-5	1 - 5	Eye Irrit. 2; H319 Flam. Liq. 2; H225	
Crystalline silica	14808-60-7	1 - 5	Carc. 1A; H350 STOT RE 1; H372	* (see below)
Inorganic Filler	12001-26-2	1 - 5		* (see below)
Toluene	108-88-3	0.1 - 1	Asp. Tox. 1; H304 Acute Tox. 4; H302 Flam. Liq. 2; H225 Repr. 2; H361 Skin Irrit. 2; H315 STOT RE 2; H373 STOT SE 3; H335, H336	
Silane	Proprietary	0.1 - 1	Eye Dam. 1; H318 Muta. 2; H341	
Ingredients determined to be not hazardous		63		

*This material is only hazardous when present as an airborne dust. As supplied, and during normal use, the material is encapsulated within the product and will not present an exposure risk.

SECTION 4: FIRST AID MEASURES

IF IN EYES: None expected to be needed, however, use an eye wash to remove a chemical from your eye regardless of the level of hazard.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Vapours are heavier than air and can travel to a source of ignition and flash back.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: No adverse health effects expected from the clean-up of spilled material. Follow personal protective equipment recommendations found in Section 8 of this SDS. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.
Shut off ignition sources; including electrical equipment and flames. Do

Print Date: 04-27-2017

SAFETY DATA SHEET

not allow smoking in the area.

SECTION 7: HANDLING AND STORAGE

Handling: No special handling instructions due to toxicity.
 Keep away from heat, sparks and flame. Wash thoroughly after handling. Keep container closed. Emptied container retains vapour and product residue. Observe all labeled precautions until container is cleaned. Drums of this material should be grounded when pouring. **DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.**
 This product contains an ingredient that may release formaldehyde at heated cure temperatures.
 This product contains an ingredient that may react with water or humidity to release methanol (67-56-1). The TWA for methanol is 200 ppm.

Storage: Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and other sources of ignition. Keep container closed. This product is a Class 3 flammable liquid and must be stored according to the provisions of AS/NZ 1940.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
EXPOSURE LIMITS:

Chemical Name	Note	AUSTRALIAN EXPOSURE LIMITS	ACGIH EXPOSURE LIMITS
Kaolin clay	* (see below)	10 mg/m ³ TWA (containing no asbestos and <1% crystalline silica, inhalable dust) None	2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
Ethyl alcohol		1000 ppm TWA; 1880 mg/m ³ TWA None	No data available. 1000 ppm STEL
Crystalline silica	* (see below)	0.1 mg/m ³ TWA (respirable dust) None	0.025 mg/m ³ TWA (respirable fraction)
Inorganic Filler	* (see below)	2.5 mg/m ³ TWA (inspirable) None	3 mg/m ³ TWA (respirable fraction)
Toluene		50 ppm TWA; 191 mg/m ³ TWA 150 ppm STEL; 574 mg/m ³ STEL skin notation	20 ppm TWA

*This material is only hazardous when present as an airborne dust. As supplied, and during normal use, the material is encapsulated within the product and will not present an exposure risk.

Biological Limit Values (ACGIH)

Chemical Name	ACGIH Biological Exposure Index (BEI)
Toluene	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene; 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene; 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

ENGINEERING CONTROL METHODS:

VENTILATION: General room ventilation might be required under normal conditions of use.

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Not normally required. Wear chemically resistant gloves to prevent prolonged or repeated contact. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate

Print Date: 04-27-2017

SAFETY DATA SHEET

measures should be taken to prevent absorption so that the TLV is not invalidated.

GLOVES: Not normally required. Use nitrile gloves if conditions warrant.

RESPIRATORY PROTECTION: No respiratory protection required under normal conditions of use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Semi-solid
COLOR:	Tan
ODOR:	Solvent
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	-1°C; 30°F
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
WEIGHT PER GALLON (lbs.):	8.76
SPECIFIC GRAVITY:	1.050
SOLUBILITY:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
AUTOIGNITION TEMPERATURE:	Not established
DECOMPOSITION TEMPERATURE:	Not established
VISCOSITY:	No data available.
SOLIDS (% by weight):	66.5

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Not established
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION**Component Toxicity / Toxicology Data:**

COMPONENT NAME	LD50/LC50
Crystalline silica	Oral LD50 Rat 500 mg/kg

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: No irritation hazard in normal industrial use.

Serious eye damage / irritation: No irritation hazard in normal industrial use.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Print Date: 04-27-2017

SAFETY DATA SHEET

Reproductive toxicity: Contains a substance that is a possible reproductive hazard based on animal studies.
Specific target organ toxicity-single exposure: No data available.
Respiratory irritation / Narcotic effects: No data available.
Specific target organ toxicity-single exposure: No data available.
Target organs potentially affected by exposure: Lungs Blood Liver Central nervous system Reproductive system
Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Lung disease, Liver disease, Blood disorders (like anemia)

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.
MOBILITY: No data available.
PERSISTENCE: No data available.
BIOACCUMULATION: No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Aromatic petroleum distillate	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L Acute Toxicity (Daphnia): 48 Hr EC50 Daphnia magna: 6.14 mg/L Acute Toxicity (Algae): Not established
Ethyl alcohol	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: 12.0 - 16.0 mL/L [static] Acute Toxicity (Daphnia): 48 Hr EC50 Daphnia magna: 2 mg/L [Static] Acute Toxicity (Algae): Not established

SECTION 13: DISPOSAL CONSIDERATIONS

This product is a prescribed waste and may only be disposed of in accordance with applicable State and local regulations. These regulations vary from jurisdiction to jurisdiction and hence the user is counselled to seek advice from the local authority and classify the waste before considering disposal. The disposal information given below is a general guide and does not replace the requirement of the local regulations.

DISPOSAL: If possible recycle, otherwise dispose strictly in accordance with local industrial waste or environmental protection regulations. This substance may, if permitted by local authorities, be disposed of in an approved incineration facility or be considered for landfill.

SPECIAL PRECAUTIONS: Do not allow this material to contaminate soil, sewerage systems or surface or ground water.

When large amounts of this product need to be disposed of the services of a registered, professional waste disposal organisation is highly recommended.

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

ADG: UN1133, ADHESIVES, 3, III
IATA: UN1133, ADHESIVES, 3, III
HazChem Code: •3Y

SECTION 15: REGULATORY INFORMATION

Print Date: 04-27-2017

SAFETY DATA SHEET**INVENTORY STATUS**

AUSTRALIA AICS:	All ingredients in this mixture are listed in the Australian Inventory of Chemical Substances.
U.S. EPA TSCA:	The product contains a substance that is not listed on the TSCA inventory.
CANADIAN CEPA DSL:	This product contains one or more components which have not been determined to be on the DSL. If you are the importer of this product into Canada, contact H.B. Fuller for chemical tracking and notification information.
EUROPEAN REACH:	As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.

If you need more information about the inventory status of this product call 1+ 651-236-5858.

New Zealand:

Classified as Hazardous according to the Hazardous Substances (Minimum degrees of hazard) Regulations 2001.
Group standard: Surface Coatings and Colourants (Flammable) Group Standard 2006
HSNO Approval Number: HSR002662.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

Exempt

SECTION 16: OTHER INFORMATION

SDS Date of Issue:	26-04-2017
Replaces:	14-10-2016
Changes made to previous issue:	Conversion to GHS format

ACRONYMS and DEFINITIONS:

ACGIH	American Conference of Governmental Industrial Hygienists
ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail
AICS	Australian Inventory of Chemical Substances
BEI	Biological Exposure Index
CAS Number	Chemical Abstracts Service Registry Number
CNS	Central nervous system
DG	Dangerous Goods
Hazchem Code	An emergency action code of numbers and letters, which gives information to emergency services.
IARC	International Agency for Research on Cancer
IATA Code	International Air Transport Association Code
IMDG Code	International Maritime Dangerous Goods Code
N.O.S.	Not otherwise specified
NOHSC	National Health and Safety Commission
PPE	Personal protection equipment
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
UN Number	United Nations Number

Prepared by: The Global Regulatory Department Phone: 1-651-236-5842

Print Date: 04-27-2017

SAFETY DATA SHEET

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Company Australia Pty. Ltd. from its suppliers, and because H.B. Fuller Company Australia Pty. Ltd. has no control over the conditions of handling and use, H.B. Fuller Company Australia Pty. Ltd. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Company Australia Pty. Ltd. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company Australia Pty. Ltd. products to comply with all applicable federal, state and local laws and regulations.