

Safety Data Sheet

DRYDEN

Hazardous, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **DRYDEN WOODMASTER**

Synonyms

Dryden Woodmaster Timber Stain Clear 1L
Dryden Woodmaster Timber Stain Clear 4L
Dryden Woodmaster Timber Stain Clear 10L
Dryden Woodmaster Timber Stain Spray Clear 10L
Dryden Woodmaster Timber Stain Spray Tint 10L
Dryden Woodmaster Timber Stain Tint 1L
Dryden Woodmaster Timber Stain Tint 10L
Dryden Woodmaster Timber Stain Tint 4L

Product Code

DMTW0417-1L
DMTW0417-4L
DMTW0417-10L
DMSW0419-10L
DMSW0451-10L
DMTW0418-1L
DMTW0418-10L
DMTW0418-4L

Bar Code

942100809322-0
942100809323-7
942100809324-4
9400513208442
9400513208459
9400513208473
9400513208435
9400513208466

Recommended use: Timber protectant

Supplier: Dulux New Zealand, a division of DuluxGroup (New Zealand) Pty Ltd
Company No.: 55 133 404 118 / Co. 2355191
Street Address: 150 Hutt Park Road
Lower Hutt
New Zealand
Telephone: 0800 800 424

Emergency Telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of EPA New Zealand.

EPA Group Standard: HSR002662 - Surface Coatings and Colourants (Flammable) Group Standard



Signal Word

Danger

Hazard Classifications

3.1C - Flammable liquids
6.1E - Substances that are acutely toxic - Aspiration hazard (H304)
6.3A - Substances that are irritating to the skin
6.5B - Substances that are contact sensitisers
6.8B - Substances that are suspected human reproductive or developmental toxicants
6.9B (Single exposure) - Substances that are harmful to human target organs or systems - Narcotic
9.1B - Substances that are ecotoxic in the aquatic environment (H411)

Hazard Statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child .

Product Name: DRYDEN WOODMASTER

Reference No: DLXNZLEN003576

Issued: 1 July 2020

Version: 1.1

Page 1 of 8

Safety Data Sheet

DRYDEN

H411 Toxic to aquatic life with long lasting effects.

Prevention Precautionary Statements

P102 Keep out of reach of children.
P103 Read label before use.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust, fume, gas, mist, vapours or spray..
P264 Wash hands, face and all exposed skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P281 Use personal protective equipment as required.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
P331 Do NOT induce vomiting.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.
P391 Collect spillage.

Storage Precautionary Statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Solvent naphtha, petroleum, light aliphatic	64742-89-8	>60 % (w/w)
Solvent naphtha, petroleum, light aromatic	64742-95-6	10-30 % (w/w)
Dichlofluanid	1085-98-9	<1 % (w/w)
Permethrin 25:75	52645-53-1	<1 % (w/w)
Tebuconazole	107534-96-3	<1 % (w/w)
Ingredients determined to be non-hazardous or below reporting limits		Balance

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: Effects may be delayed. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Hazchem Code: •3Y

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Safety Data Sheet

DRYDEN

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 14

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and/or the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by WorkSafe New Zealand.

Biological Limit Values: As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions..

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES, RESPIRATOR.

Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Colour:	Various
Odour:	Solvent

Safety Data Sheet

DRYDEN

Solubility:	Insoluble in water
Specific Gravity:	0.81 - 0.83
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	44
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	N Av
pH:	N App
Viscosity:	<21 mm ² @ 40 oC
Total VOC (g/Litre):	N Av

(Typical values only - consult specification sheet)

N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

Skin contact: Contact with skin will result in irritation. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

Eye contact: May be an eye irritant.

Acute toxicity

Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 20.0 mg/L for vapours or LC50 > 5.0 mg/L for dust and mist or LC50 > 5,000 ppm gas

Skin contact: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >5,000 mg/Kg bw

Ingestion: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >5,000 mg/Kg bw

Safety Data Sheet

DRYDEN

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a 6.3A - Substances that are irritating to the skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified 6.5B - Substances that are contact sensitisers.

Aspiration hazard: This material has been classified as a 6.1E - Substances that are acutely toxic - Aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation):

This material has been classified as a 6.8B - Substances that are suspected human reproductive or developmental toxicants.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

Long-term aquatic hazard: This material has been classified as a 9.1B - Substances that are ecotoxic in the aquatic environment. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 1 - 10 mg/L, where the substance is not rapidly degradable and/or BCF \geq 500 and/or log K_{ow} \geq 4.

Ecotoxicity in the soil environment: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial invertebrates: This material has been classified as non-hazardous.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No: 1263
Dangerous Goods Class: 3
Packing Group: III
Hazchem Code: •3Y
Emergency Response Guide No: 14

Proper Shipping Name: PAINT

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



UN No: 1263
Dangerous Goods Class: 3
Packing Group: III

Proper Shipping Name: PAINT

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 1263
Dangerous Goods Class: 3
Packing Group: III

Proper Shipping Name: PAINT

15. REGULATORY INFORMATION

Safety Data Sheet

DRYDEN

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

- All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

EPA Group Standard: HSR002662 - Surface Coatings and Colourants (Flammable) Group Standard

Approved handler	Yes
Location test certificate	Yes
Fire extinguishers	Yes
Signage	Yes
Emergency response	Yes
Hazardous atmosphere zone	Yes

16. OTHER INFORMATION

Reasons for issue: Change in Physical Properties
Change in Hazardous Substance Classification
Minor Text Changes

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.