

Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Parfix Epoxy Adhesive 5 Minute Everyday (Class 8)

Synonyms: **Product Code Bar Code**

Parfix Epoxy Adhesive 5 Minute Everyday

Recommended use: Two pack epoxy adhesive. For bonding glass, metal, china, ceramics, porcelain,

rubber and wood.

Supplier: DuluxGroup (New Zealand) Pty Ltd ABN: 55 133 404 118 / Co. 2355191

Street Address: 150 Hutt Park Road

> Lower Hutt New Zealand

Telephone: 0800 735 539

Australia - 1800 033 111 New Zealand - 0800 734 607 **Emergency telephone number:**

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of ERMA New Zealand

ERMA Group Standard: Construction Products (Corrosive) Group Standard 2006; HSR002542



Signal Word

Danger

HSNO Hazard Classification

Substances that are acutely toxic. 6.1D

8.2C Substances that are corrosive to dermal tissue 8.3A Substances that are corrosive to ocular tissue

6.5B Substances that are contact sensitisers

9.1B Substances that are ecotoxic in the aquatic environment

Hazard Statement(s)

H302 Harmful if swallowed H312 Harmful in contact with skin

H314 Causes severe skin burns and eye damage

Causes serious eye damage H318 May cause an allergic skin reaction H317

Toxic to aquatic life with long lasting effects H411

Prevention Precautionary Statement(s)

P102 Keep out of reach of children P103 Read label before use

SDS No: SELNZLEN000280 Product name: Parfix Epoxy Adhesive 5 Minute Everyday (Class 8) Issued: 5 August 2015

Version: 2.2 Page: 1 of 8



P260 Do not breathe fume, gas, mist, vapours or spray
P270 Do not eat, drink or smoke when using this product

P272 Contaminated work clothing should not be allowed out of the workplace

P273 Avoid release to the environment

P280 Wear protective clothing, gloves, eye/face protection and suitable respirator as required

Response Precautionary Statement(s)

P101 If medical advice is needed, have product container or label at hand

P301+310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician

P330 Rinse mouth

P302+352 IF ON SKIN: Wash with soap and water

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower

P363 Wash contaminated clothing before reuse

P333+313 If skin irritation or a rash occurs: Get medical advice/attention

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

P312 Call a POISON CENTRE or doctor/physician if you feel unwell

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if

present and easy to do - continue rinsing

P310 Immediately call a POISON CENTRE or doctor/physician

P319 Collect spillage

Storage Precautionary Statement(s)

P405 Store locked up

Disposal Precautionary Statement(s)

P501 Dispose of contents/container in accordance with local, regional, national and international

regulations

DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Class: 8 Corrosive

3. COMPOSITION INFORMATION

PART A

CHEMICAL ENTITY	CAS NO.	PROPORTION	
Bisphenol A-Epichlorhydrin reaction product Ingredients determined to be non-hazardous	25068-38-6 -	> 60% Balance	
		100%	
PART B CHEMICAL ENTITY	CAS NO.	PROPORTION	
OHEIMICAE EIVITT	OAO NO.	THOI ORTION	
2,4,6-tris(Dimethylaminomethyl)phenol Ingredients determined to be non-hazardous	90-72-2 -	10 - 30% Balance	
		100%	

Product name: Parfix Epoxy Adhesive 5 Minute Everyday (Class 8) SDS No: SELNZLEN000280

Issued: 5 August 2015 Version: 2.2 Page: 2 of 8



4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin contact: For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

PPE for First Aiders: Wear overalls, face shield, elbow-length impervious gloves, splash apron and rubber boots. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Notes to physician: Treat symptomatically. Can cause corneal burns.

5. FIRE-FIGHTING MEASURES

Hazchem Code: 2X

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

Product name: Parfix Epoxy Adhesive 5 Minute Everyday (Class 8) SDS No: SELNZLEN000280

Issued: 5 August 2015 Version: 2.2 Page: 3 of 8



LARGE SPILLS

Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: 36

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from foodstuffs. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Dangerous Good Class 8 Corrosive as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Use only in well ventilated areas. Keep containers closed when not in use.

Personal protection equipment: ORANGE: OVERALLS, RUBBER BOOTS, FACE SHIELD, SAFETY SHOES, GLOVES, APRON.

MANUFACTURING, PACKAGING AND TRANSPORT:

Wear overalls, face shield, elbow-length impervious gloves, splash apron and rubber boots. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

RECOMMENDATIONS FOR CONSUMER USE:

Wear safety glasses and gloves. Avoid inhaling vapour. Wash hands after use.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid skin and eye contact and inhalation of vapour. Ensure that eyewash stations and safety showers are close to the workstation location.

Product name: Parfix Epoxy Adhesive 5 Minute Everyday (Class 8) SDS No: SELNZLEN000280

Issued: 5 August 2015 Version: 2.2 Page: 4 of 8



9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Clear (Part A) or Light yellow (Part B), viscous liquid with a characteristic odour.

Solubility: Insoluble in water. Soluble in organic solvents.

Relative Density (20 ℃): 1.16 (Part A)

>1 **Relative Vapour Density (air=1):** Vapour Pressure (20 ℃): N Av Flash Point (℃): >150 Flammability Limits (%): N Av Autoignition Temperature (℃): N Av % Volatile by Volume: N Av Melting Point/Range (℃): N Av Boiling Point/Range (℃): >200 **Decomposition Point (℃):** N Av pH: N App

Viscosity (25 ℃): 6,000 − 8,000 mPa.s (Part A) **Viscosity (30 ℃):** 10,000 − 15,000 mPa.s (Part B)

Total VOC (g/Litre): N Av

10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Incompatible with acids, alkalis and oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

Product name: Parfix Epoxy Adhesive 5 Minute Everyday (Class 8) SDS No: SELNZLEN000280

Issued: 5 August 2015 Version: 2.2 Page: 5 of 8



Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Acute toxicity

Inhalation: This material has been classified as non-hazardous.

Acute toxicity estimate (based on ingredients): >20 mg/L

Skin contact: This material has been classified as a Category 6.1D Hazard.

Acute toxicity estimate (based on ingredients): 1,000 - 2,000 mg/Kg

Ingestion: This material has been classified as a Category 6.1D Hazard.

Acute toxicity estimate (based on ingredients): 300 - 2,000 mg/Kg

Corrosion/Irritancy: Eye: this material has been classified as a Category 8.3A Hazard (irreversible effects

to eyes)

Skin: this material has been classified as a Category 8.2C Hazard (corrosive to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser.

Skin: this material has been classified as a Category 6.5B Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as a Category Acute 9.1B Hazard.

Acute toxicity estimate (based on ingredients): 1 - 10 mg/L

Long-term aquatic hazard: This material has been classified as a Category Chronic 9.1B Hazard.

Acute toxicity estimate (based on ingredients): 1 - 10 mg/L

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

Product name: Parfix Epoxy Adhesive 5 Minute Everyday (Class 8) SDS No: SELNZLEN000280

Issued: 5 August 2015 Version: 2.2 Page: 6 of 8



13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN No: 2735

Dangerous Goods Class: 8

Packing Group: III

Hazchem Code: 2X

Emergency Response Guide No: 36

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), cyanides of Class 6, radioactive substances (Class 7) or food and food packaging in any quantity, however exemptions may apply. Note that concentrated strong acids are incompatible with concentrated strong alkalis.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.

UN No: 2735

Dangerous Goods Class: 8

Packing Group: III

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 2,4,6-

TRIS(DIMETHYLAMINOMETHYL)PHENOL)

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 2735

Dangerous Goods Class: 8

Packing Group: III

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 2,4,6-

TRIS(DIMETHYLAMINOMETHYL)PHENOL)

Product name: Parfix Epoxy Adhesive 5 Minute Everyday (Class 8) SDS No: SELNZLEN000280

Issued: 5 August 2015 Version: 2.2 Page: 7 of 8



15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

- Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives International Convention for the Prevention of Pollution from Ships (MARPOL)
 - Annex III Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements:

- The Standard for the *Uniform Scheduling of Medicines and Poisons (SUSMP*) established under the *Therapeutic Goods Act (Commonwealth*).
- All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Reason(s) For Issue: Format Change Minor Text Changes.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: Parfix Epoxy Adhesive 5 Minute Everyday (Class 8) SDS No: SELNZLEN000280

Issued: 5 August 2015 Version: 2.2 Page: 8 of 8