

## **Hazardous Substance, NON-Dangerous Goods**

### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: PM3-D0839 Porter's Liquid Zinc Ageing

**Solution** 

Synonyms:Product CodeBar CodePorter's Liquid Zinc Ageing Solution, 500mLPM3D0839-500ML9328119013645

**Recommended use:** Coating, designed to cause oxidation of metallic particles contained within an appropriate paint. It does not form a durable paint film itself, but changes the appearance of the paint that it is applied to. May be applied to Porter's Liquid Zinc.

**Supplier:** Porter's Paints, a division of

DuluxGroup (New Zealand) Pty Ltd

**ABN:** 55 133 404 118 / Co. 2355191

Street Address: 150 Hutt Park Road

Lower Hutt New Zealand

**Telephone:** 0800 800 424

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

### 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of EPA New Zealand

**EPA Group Standard:** Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006; HSR002670



### Signal Word

Warning

### **HSNO Hazard Classification**

6.1E Substances that are acutely toxic
6.3A Substances that are irritating to the skin
6.4A Substances that are irritating to the eye

6.9 Respiratory tract irritant

### **Hazard Statement(s)**

H303 May be harmful if swallowed
 H315 Causes skin irritation
 H319 Causes serious eye irritation
 H335 May cause respiratory irritation

### **Prevention Precautionary Statement(s)**

P102 Keep out of reach of children P103 Read label before use

Issued: 14 March 2016 Version: 1.0 Page: 1 of 7

Product name: PM3-D0839 Porter's Liquid Zinc Ageing Solution

SDS No: DLXNZLEN001328



P261 Avoid breathing mist, vapours or spray

P264 Wash hands, face and all exposed skin thoroughly after handling

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective clothing, gloves, eye/face protection and suitable respirator as required

### Response Precautionary Statement(s)

P101 If medical advice is needed, have product container or label at hand

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

P312 Call a POISON CENTRE or doctor/physician if you feel unwell

P302+352 IF ON SKIN: Wash with soap and water

P362 Take off contaminated clothing and wash before reuse P332+313 If skin irritation occurs: Get medical advice/attention

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if

present and easy to do - continue rinsing

P337+313 If eye irritation persists get medical advice/attention

### **Storage Precautionary Statement(s)**

P405 Store locked up

P403+233 Store in a well ventilated place. Keep container tightly closed

### **Disposal Precautionary Statement(s)**

P501 Dispose of contents/container in accordance with local, regional, national and international

regulations

#### DANGEROUS GOODS CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

### 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION	
Copper acetate Hydrochloric acid Ingredients determined to be non-hazardous	142-71-2 7647-01-0 -	1 - 10% 1 - 10% Balance	
		100%	

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin contact:** If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

Product name: PM3-D0839 Porter's Liquid Zinc Ageing Solution SDS No: DLXNZLEN001328

Issued: 14 March 2016 Version: 1.0 Page: 2 of 7



**Eye contact:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**PPE for First Aiders:** Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Hazchem Code: Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

**Fire fighting further advice:** On decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

### 6. ACCIDENTAL RELEASE MEASURES

### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

### LARGE SPILLS

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Use a spark-free shovel. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable.

### 7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from foodstuffs. Keep containers closed when not in use - check regularly for leaks.

Product name: PM3-D0839 Porter's Liquid Zinc Ageing Solution SDS No: DLXNZLEN001328

Issued: 14 March 2016 Version: 1.0 Page: 3 of 7



### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**National occupational exposure limits:** No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

However for:

	TWA		STEL		CARCINOGEN	NOTICES
	ppm	mg/m3	ppm	mg/m3	CATEGORY	
Hydrogen chloride	5	7.5		Ceiling		

As published by the Safe Work Australia or Department of Labour New Zealand.

WES-TWA (Workplace Exposure Standard – Time-weighted Average). The time-weighted average exposure standard designed to protect the worker for the effects of long-term exposure.

WES-Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not be exceeded during any part of the working day.

WES-STEL (Workplace Exposure Standard - Short-Term Exposure Limit). The 15-minute average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue changes, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

**Engineering measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

**Personal protection equipment:** H: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.

Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid skin and eye contact and inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

Product name: PM3-D0839 Porter's Liquid Zinc Ageing Solution SDS No: DLXNZLEN001328

Issued: 14 March 2016 Version: 1.0 Page: 4 of 7



### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Blue coloured liquid with a mild, acid odour.

**Solubility:** Soluble in water.

Specific Gravity (20 ℃): 1.05 Relative Vapour Density (air=1): >1 Vapour Pressure (20 ℃): N Av Flash Point (℃): N App Flammability Limits (%): N App Autoignition Temperature (℃): N App % Volatile by Volume: N Av Melting Point/Range (℃): N Av Boiling Point/Range (℃): Approx. 100 **Decomposition Point (℃):** N Av N Av pH:

pH: N Av
Viscosity: N Av
Total VOC (g/Litre): N Av

### 10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents and alkalis.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

**Inhalation:** Material is an irritant to mucous membranes and respiratory tract.

**Skin contact:** Contact with skin will result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant.

Product name: PM3-D0839 Porter's Liquid Zinc Ageing Solution SDS No: DLXNZLEN001328

Issued: 14 March 2016 Version: 1.0 Page: 5 of 7



### **Acute toxicity**

Inhalation: This material has been classified as non-hazardous.

**Skin contact:** This material has been classified as non-hazardous.

**Ingestion:** This material has been classified as a Category 6.1E Hazard. Acute toxicity estimate (based on ingredients): 2,000 – 5,000 mg/Kg

Corrosion/Irritancy: Eye: this material has been classified as a Category 6.4A Hazard (reversible effects

to eyes).

Skin: this material has been classified as a Category 6.3A Hazard (irritant to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser.

Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 6.9 Hazard. Exposure via inhalation may result in respiratory irritation.

### **Chronic Toxicity**

**Mutagenicity:** This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

### 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: No information is available to complete an assessment.

**Long-term aquatic hazard:** No information is available to complete an assessment.

**Ecotoxicity:** No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

**Mobility:** No information available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

Product name: PM3-D0839 Porter's Liquid Zinc Ageing Solution SDS No: DLXNZLEN001328

Issued: 14 March 2016 Version: 1.0 Page: 6 of 7



### 14. TRANSPORT INFORMATION

### **ROAD AND RAIL TRANSPORT**

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

#### MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

### **AIR TRANSPORT**

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

### 15. REGULATORY INFORMATION

### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

### This material/constituent(s) is covered by the following requirements:

- The Standard for the *Uniform Scheduling of Medicines and Poisons (SUSMP*) established under the *Therapeutic Goods Act (Commonwealth*).
- All the constituents of this material are listed on the *Australian Inventory of Chemical Substances* (AICS).

### **16. OTHER INFORMATION**

### Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Reason(s) For Issue: First Issue

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: PM3-D0839 Porter's Liquid Zinc Ageing Solution SDS No: DLXNZLEN001328

Issued: 14 March 2016 Version: 1.0 Page: 7 of 7