

# Hazardous, NON-Dangerous Goods

**1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION** 

# Product name: 193-85978 ACRATEX RENDERWALL ACRAPRO P400

Synonyms AcraTex RenderWall P400 20KG AcraTex RenderWall 4001 Direct 20KG AcraTex RenderWall Plus AcraPro P400 20KG Product Code 19385978-20KG 193DIR78-20KG 19385978-20KG Bar Code 9300611490902 9300611490902

Recommended use: Cement render for brick, masonary and concrete walls. Applied by trowel.

| Supplier:<br>ABN: | Dulux Australia, a division of DuluxGroup (Australia) Pty Ltd 67 000 049 427 |
|-------------------|--|
| Street Address:   | 1956 Dandenong Road<br>Clayton VIC 3168<br>Australia                         |
| Telephone:        | Australia - 1800 810 114   |

Emergency Telephone number: Australia – 1800 220 770; New Zealand – 0800 220 770

# 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word Danger

# **Hazard Classifications**

Skin Corrosion/Irritation - Category 2 Eye Damage/Irritation - Category 1 Carcinogenicity - Category 1A Specific Target Organ Toxicity (Single Exposure) - Category 3 Respiratory Tract Irritation Specific Target Organ Toxicity (Repeated Exposure) - Category 1

### **Hazard Statements**

- H315 Causes skin irritation.
  H318 Causes serious eye damage.
  H335 May cause respiratory irritation.
- H350 May cause cancer .
- H372 Causes damage to organs through prolonged or repeated exposure.

# **Prevention Precautionary Statements**

- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.

#### Product Name: 193-85978 ACRATEX RENDERWALL ACRAPRO P400



- P201 Obtain special instructions before use. P202
- Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust, fume, gas, mist, vapours or spray.
- P264 Wash hands, face and all exposed skin thoroughly after handling.
- Do not eat, drink or smoke when using this product. P270
- Use only outdoors or in a well-ventilated area. P271
- Use personal protective equipment as required. P281

### **Response Precautionary Statements**

| P101   |           | If medical advice is needed, have product container or label at hand.       |
|--------|-----------|---|
| P302+F | P352      | IF ON SKIN: Wash with plenty of water .                                     |
| P304+F | P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.  |
| P305+F | P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact |
|        |           | lenses, if present and easy to do. Continue rinsing.                        |
| P312   |           | Call a POISON CENTER/doctor if you feel unwell.                             |
| P332+F | P313      | If skin irritation occurs: Get medical advice/attention.                    |
| P362   |           | Take off contaminated clothing.   |
|        |           |   |

### **Storage Precautionary Statements**

| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
|-----------|--|
| P405      | Store locked up.   |

# **Disposal Precautionary Statement**

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule: Not Applicable

# DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

| 3. COMPOSITION INFORMATION   |            |                 |
|--|------------|-----------------|
| CHEMICAL ENTITY  | CAS NO     | PROPORTION      |
| Crystalline silica, respirable                                       | 14808-60-7 | >60 % (w/w)     |
| Cement, portland, chemicals  | 65997-15-1 | 10 - 30 % (w/w) |
| Calcium hydroxide (Ca(OH)2)  | 1305-62-0  | <1 % (w/w)      |
| Calcium oxide  | 1305-78-8  | <1 % (w/w)      |
| Ingredients determined to be non-hazardous or below reporting limits |            | Balance         |
|  |            | 100%            |

# 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

| Product Name: 193-85978 ACRATE | X RENDERWALL ACRAPRO | Reference No: DLXGHSEN000402 |
|--------------------------------|----------------------|------------------------------|
| P400                           |                      |                              |
| Issued: 8 April 2021           | Version: 7.0         | Page 2 of 8                  |



**Skin Contact:** If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

**Eye contact:** Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**PPE for First Aiders:** Wear safety shoes, overalls, gloves, chemical goggles, dust mask. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Can cause corneal burns.

# 5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

Fire fighting further advice: Not applicable.

# 6. ACCIDENTAL RELEASE MEASURES

### SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

### LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

### Dangerous Goods - Initial Emergency Response Guide No: Not applicable

### 7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of dust.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition.

Product Name: 193-85978 ACRATEX RENDERWALL ACRAPRO Reference No: DLXGHSEN000402 P400



Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### National occupational exposure limits:

|   | TWA |       | STEL |       | NOTICES  |
|---|-----|-------|------|-------|----------|
|   | ppm | mg/m3 | ppm  | mg/m3 |          |
| Calcium hydroxide                             | -   | 5     | -    | -     | -        |
| Calcium oxide                                 | -   | 2     | -    | -     | -        |
| Portland cement                               | -   | 10    | -    | -     | -        |
| Quartz (respirable dust)                      | -   | 0.05  | -    | -     | Carc. 1A |
| Silica Crystalline - Quartz (respirable dust) | -   | 0.05  | -    | -     | Carc. 1A |

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Avoid generating and inhaling dusts. Use with local exhaust ventilation or while wearing dust mask.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, DUST MASK.

Wear safety shoes, overalls, gloves, chemical goggles, dust mask. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.



### 9. PHYSICAL AND CHEMICAL PROPERTIES

| Form:   | Crystalline Powder |
|---------|--------------------|
| Colour: | Off-white          |
| Odour:  | Odourless          |

Solubility: Specific Gravity: Relative Vapour Density (air=1): Vapour Pressure (20 °C): Flash Point (°C): Flammability Limits (%): Autoignition Temperature (°C): Melting Point/Range (°C): Boiling Point/Range (°C): pH: Viscosity: Total VOC (g/Litre): Insoluble in water 1.55 -1.65 N App N Ayp

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

#### **10. STABILITY AND REACTIVITY**

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

#### **11. TOXICOLOGICAL INFORMATION**

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### Acute Effects

Inhalation: Material is an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Eye contact:** A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

### Acute toxicity

 Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients):

 Product Name: 193-85978 ACRATEX RENDERWALL ACRAPRO

 P400

Reference No: DLXGHSEN000402



LC50 > 5 mg/L

**Skin contact:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

**Ingestion:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

**Specific target organ toxicity (single exposure):** This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

### **Chronic Toxicity**

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as a Category 1A Hazard.

**Reproductive toxicity (including via lactation):** This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as a Category 1 Hazard.

# 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log  $K_{ow}$  < 4.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

# **13. DISPOSAL CONSIDERATIONS**

Issued: 8 April 2021

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.



If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

### **14. TRANSPORT INFORMATION**

### ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

### MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

### AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

### **15. REGULATORY INFORMATION**

### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent) Basel Convention (Hazardous Waste) International Convention for the Prevention of Pollution from Ships (MARPOL)

### This material/constituent(s) is covered by the following requirements:

 All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).

 All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

HSNO Group Standard: HSR002545 - Construction Products (Toxic [6.7A]) Group Standard

### **16. OTHER INFORMATION**

Reason for issue: Revised

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to



our customers and is also available upon request.

