Leatherique

Crack Filler

"Simply The Best Since 1968"

Please read all directions thoroughly before proceeding. For further information about the full leather restoration and dyeing process, and leather care, visit <u>www.leatherique.com.au</u>.

Leatherique[®] Crack Filler should only be used after Leatherique[®] Rejuvenator, Pristine Clean and Prepping Agent.

Materials

- Leatherique[®] Crack Filler
- Leatherique[®] Custom Dye
- Leatherique[®] Prepping Agent
- Masking tape
- Spatula
- 600 grit wet and dry sandpaper
- Microfibre cloth or paper towel

Instructions

- Mask off each side of crack to be filled.
- Mix one drop of dye (no more) with the Crack Filler to assist colour matching.
- Using a spatula, toothpick or similar, apply Crack Filler only into the cracks, not on the leather surface.
- For deep cracks, build up Crack Filler in layers, allowing to dry for 30-60 minutes between layers.
- Fill crack slightly proud of the leather surface and allow to dry.
- Using 600 grit wet and dry sandpaper and Leatherique[®] Prepping Agent, wet sand off excess so that Crack Filler is flush with the leather surface.

Patch Repair

- Cut a matching piece of leather to match the hole. You may have to enlarge the are with a sharp blade to define the area.
- Apply a suitable leather glue to the patch, insert into the hole and tape or pin until dry.
- Follow procedures above to fill joint around patch with Crack Filler.

Disclaimer: Leatherique[®] products are intended for use as described in the provided product documentation. It is important to read and follow all instructions and warnings. Leatherique[®] makes no representations or warranties of any kind, express or implied, about the completeness, accuracy, reliability, suitability, or availability of the product for any purpose and we disclaim liability for any damage or injury resulting from product use.