

FORTIS ACID STAIN



Fortis Acid Stain colours concrete to a beautiful variegated and mottled appearance. Staining imparts a luxurious richness that can't be achieved by any other colouring medium. Fortis Acid Stain is a staining agent that uses mineral salts to chemically react with the free lime at the surface of the slab to produce a permanent colour change. Rather than produce a solid, opaque effect like paint, Fortis Acid stain permeates the concrete to infuse it with luminous, translucent tones that vary depending on the surface they are applied to and the application techniques used. The results can mimic everything from polished marble to tanned leather, natural stone or even stained wood.

- Features and Benefits**
- Excellent UV stability
 - Interior / Exterior
 - Excellent wear resistance
 - Variegated colour
 - Concentrated
 - Water thinnable
 - Reduces glare
 - Easily coated
 - Zero VOC

- Typical Applications**
- Penetration chemical stain
 - Seamless

- Properties**
- Recoat / Dry: 4-6hrs
 - New Concrete: minimum 14 days old
 - Work time: 30-60 minutes
 - Coverage Rate: 5-7m²/L
 - Foot traffic: 24 hours

Colours Blue, Black, Brown, Green, Red, Tan

Pack Size 1L, 5L, 15L

Shelf Life 24 months @ 25°C unopened

- Safety**
- Refer to Safety Data Sheet prior to use
 - Good industrial hygiene practices should be observed at all times
 - Appropriate PPE should be worn including impervious gloves & eye wear

Storage Store in cool, dry conditions, out of direct sunlight and in a well-ventilated area. Do not store below 5°C or over 50°C

Surface Preparation **Fortis Acid Stain** must be able to soak into the concrete to achieve full colour saturation. They should not be applied to surfaces covered by anything that can inhibit stain penetration, such as dirt, grease, glues, coatings, curing membranes and sealers. Prior to application ensure that the substrate is clean, dry and free of wax, oil or any loose, flaking material or substances that may inhibit the stain from soaking into the concrete.

When applying **Fortis Acid Stain**, always use all-plastic spray bottles. **ALWAYS** test your dilution concentrations to ensure you obtain the colour you are after.

DO NOT use hydrochloric acid to prepare the concrete.

Concrete needs to be a minimum of 14 days old before applying **Fortis Acid Stain**. Mask off any areas not intended for staining as the acid stain can be tough and sometimes impossible to remove

Application Staining concrete successfully requires a skilful hand and a discerning eye. Here are a few tips for getting the best results:

FORTIS ACID STAIN



- To produce various concentrations of colour, you can dilute the stain by adding water, either by wetting the concrete before the stain is applied or by spritzing the concrete after stain application with water from a spray bottle.
- Don't expect colour consistency or perfection. Variations are inherent in the staining process.
- When spraying, apply liberally with an even and continuous pattern over the slab.
- Maintain a wet edge.
- Avoid puddling of stain.
- When applying to vertical surfaces start from the bottom and work your way up.
- One person should spray the stain just ahead of another person scrubbing the surface. Avoid over application and drips. Alternatively use a light random spray pattern to form cloud like formation.
- Exterior applications should be completed in the early morning hours when the concrete is cool and allows the stain to dry slowly.
- Protect your newly stained surface with a sealer. Be sure to select a product that's compatible with the stain you're using.

Clean-Up

Neutralise containers with water and a little sodium bicarbonate.

Limitations

Fortis Acid Stain may not be effective on many surfaces, including old, weathered concrete or sealed concrete. In addition, some surfaces may have varying or little to no reaction as the density of the surface may prevent the product from penetrating and reacting. Fortis strongly recommends testing representative samples in different sections of the concrete to determine suitability of the stain and final appearance.

For further information, including Safety Data Sheets and Technical Bulletins, refer to the Fortis website www.fortisadhesives.com.au.

Disclaimer - Fortis products should be used in accordance with the information contained herein. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained herein is to the best of our knowledge at the date of publication, Fortis makes no representation about the accuracy of the information. If you need clarification or more information, you should contact Fortis Adhesives & Coatings. Fortis products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, Fortis accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of Fortis Adhesives & Coatings products or reliance upon the information contained herein.

Fortis Adhesives & Coatings Pty Ltd

ABN 65 1333 915 732
14 Commercial Drive
Dandenong South
Victoria, Australia, 3175
www.fortisadhesives.com.au
+61 3 9706 5448

Manufacturers of a range of Industrial Adhesives, Floor Coatings and Concrete Repair Systems. From Epoxy to Polyaspartic, Polyurethane to PVA, and with our Industry leading Technical Support, Fortis has you covered.