Technical Data Sheet

FORTIS NON-SLIP ADDITIVE



Fortis Non-Slip Additive embeds into the coating to provide a textured finish which reduces the slip hazard associated with coated floor surfaces. Compatible with many coatings, including all Fortis epoxy and polyurethane coatings.

Features and Benefits	 Creates non-slip surface Improved safety Eliminates car tyre squeal
Typical Applications	 Coated floors, concrete, stairs, ramps Interior and exterior
Pack Size	200g, 400g
Shelf Life	Indefinite
Safety	 Refer to Safety Data Sheet prior to use Good industrial hygiene practices should be observed at all times Appropriate PPE should be worn including impervious gloves & eye wear
Storage	Store in cool, dry conditions, out of direct sunlight and in a well-ventilated area. Do not store below 5°C or over 40°C
Surface Preparation	As per coating application instructions
Mixing	If required, remove portion of coating from can to minimise spillage when adding additive and stirring. Add Fortis Non-Slip Additive to coating at a rate of 2 - 5% (ie 20-50 grams* / litre of coating). Stir thoroughly with flat blade to achieve even distribution of additive throughout coating.
	Stir regularly during application of coating to prevent settling and un-even distribution of additive.
	* 1 tablespoon additive = 8 grams
Application	As per coating application instructions. If applying more than one coat, add Fortis Non-Slip Additive to the top coat
Clean-Up	As per coating application instructions

For further information, including Safety Data Sheets and Technical Bulletins on adhesive applications and surface preparation, refer to the Fortis website www.fortisadhesives.com.au.

Disclaimer - Fortis products should be used in accordance with the information contained herein. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained herein is to the best of our knowledge at the date of publication, Fortis makes no representation about the accuracy of the information. If you need clarification or more information, you should contact Fortis Adhesives & Coatings. Fortis products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, Fortis accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of Fortis Adhesives & Coatings products or reliance upon the information contained herein.

Technical Data Sheet

FORTIS NON-SLIP ADDITIVE



Fortis Adhesives & Coatings Pty Ltd ABN 65 1333 915 732 14 Commercial Drive Dandenong South Victoria, Australia, 3175 www.fortisadhesives.com.au +61 3 9706 5448

Manufacturers of a range of Industrial Adhesives, Floor Coatings and Concrete Repair Systems. From Epoxy to Polyaspartic, Polyurethane to PVA, and with our Industry leading Technical Support, Fortis has you covered.