

FORTIS PRIME 520



FORTIS PRIME 520 is a two component, clear, water based polyurethane primer and build coat, suitable for brush or roller application. For use as a high-performance clear polyurethane primer and build coat for wood and concrete substrates, usually finished with **FORTIS COAT 526 Gloss or Satin**.

Features and Benefits	<ul style="list-style-type: none"> • Non-yellowing • Medium build • Water-based two-pack • Exterior/Interior use • Low odour • Excellent adhesion to siliceous and most polar compounds • Chemically resistant • Cures well in humid or cold conditions
Typical Applications	<ul style="list-style-type: none"> • Priming Concrete, Ceramics, Glass, Timber flooring
Properties	<ul style="list-style-type: none"> • Colour: Clear • Finish: Semi-Gloss • Mix Ratio: 4.1 Parts A to 1 Part B by weight or volume • Pot life: 2 hours • Film Thickness: 60µm DFT • Coverage Rate: 10-12m²/L • Dry to recoat: 4-6 hours @20°C • Dry to sand: Overnight • Number of Coats: 1 • Recoat#: 10 hrs @20°C 65% RH • Final Cure#: 7 Days
Pack Size	5L Kit
Shelf Life	12 months @ 25°C unopened
Safety	<ul style="list-style-type: none"> • Contains isocyanates • Refer to Safety Data Sheet prior to use • Good industrial hygiene practices should be observed at all times • Appropriate PPE should be worn including impervious gloves & eye wear
Storage	Store in cool, dry conditions, out of direct sunlight and in a well-ventilated area. Do not store below 5°C or over 40°C
Surface Preparation	<p>For new wood and fully sanded old timber surfaces, final sand with 220 grit sandpaper.</p> <p>For concrete surfaces, best results are obtained from diamond-grinding or sanding. If diamond grinding or sanding is not possible, acid etching may be used.</p>
Application	<p>Use a Jiffy Mixer or similar with a variable speed drill, according to the manufacturer's recommendations.</p> <p>Add the hardener slowly and evenly into the mixing vortex in the resin component, while maintaining a constant mixing speed throughout the addition. Avoid entraining air. Continue mixing for a minimum of three minutes.</p> <p>Proper mixing of the viscous hardener into the low viscosity resin component is essential to achieve proper coating properties.</p> <p>Filter before use. Mixed product has a pot life of 2 hours at 25°C.</p>

FORTIS PRIME 520



Apply 1 - 2 coats of **Fortis Prime 520**, followed by 1 or 2 coats of **Fortis Coat 526 Gloss** or **Satin** depending on required finish

Clean-Up

Allow rollers to cure prior to discarding

Limitations

Note these times depend upon relative humidity, air circulation, temperature and film thickness. Actual times will vary according to combinations of these variables.

For further information, including Safety Data Sheets and Technical Bulletins on adhesive applications and surface preparation, refer to the Fortis website www.fortisadhesives.com.au.

Disclaimer - Fortis products should be used in accordance with the information contained herein. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained herein is to the best of our knowledge at the date of publication, Fortis makes no representation about the accuracy of the information. If you need clarification or more information, you should contact Fortis Adhesives & Coatings. Fortis products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, Fortis accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of Fortis Adhesives & Coatings products or reliance upon the information contained herein.

Fortis Adhesives & Coatings Pty Ltd

ABN 65 1333 915 732
14 Commercial Drive
Dandenong South
Victoria, Australia, 3175
www.fortisadhesives.com.au
+61 3 9706 5448

Manufacturers of a range of Industrial Adhesives, Floor Coatings and Concrete Repair Systems. From Epoxy to Polyaspartic, Polyurethane to PVA, and with our Industry leading Technical Support, Fortis has you covered.