## Technical Data Sheet

## FORTIS GLUE RELEASE



**FORTIS GLUE RELEASE** is a temporary water-based wax emulsion coating that allows surfaces to repel glue, adhesives and resins. It coats and protects equipment from dried glue and reduces cleaning time. Regular application improves equipment longevity by reducing the need for harsh cleaning that may damage equipment.

Features and Benefits	<ul> <li>Easy application</li> <li>Protects equipment</li> <li>Allows glue to be easily removed</li> <li>Reduces cleaning time</li> <li>Can be used on moving parts</li> <li>Low odour</li> <li>No silicone</li> <li>Zero VOCs</li> </ul>
Typical Applications	<ul> <li>Spray booths</li> <li>Woodworking equipment</li> <li>Clamps, machinery, benches</li> </ul>
Properties	<ul> <li>Appearance: White or creamy liquid</li> <li>Application temperature: for cold gluing applications up to 38°C</li> <li>Service temperature: 5-38°C</li> </ul>
Pack Size	1L, 5L, 20L
Shelf Life	12 months @ 25°C unopened
Safety	<ul> <li>Refer to Safety Data Sheet prior to use</li> <li>Good industrial hygiene practices should be observed at all times</li> <li>Appropriate PPE should be worn including impervious gloves &amp; eye wear</li> </ul>
Storage	Store in cool, dry conditions, out of direct sunlight and in a well-ventilated area. Do not store below $5^{\circ}$ C or over $40^{\circ}$ C
Application	<b>FORTIS GLUE RELEASE</b> can be easily brushed, wiped, rolled or sprayed onto the application surface. Apply liberally to all areas where required.
	Remove coating and cured adhesive mechanically at the end of the day, then re-apply following clean up.
Clean-Up	Once dried, can be easily scraped off mechanically, removing cured glue mess with the coating.
Limitations	Not recommended for use on porous surfaces, or walkways (slip hazards)

For further information, including Safety Data Sheets and Technical Bulletins on adhesive applications and surface preparation, refer to the Fortis website <u>www.fortisadhesives.com.au</u>.

**Disclaimer -** Fortis products should be used in accordance with the information contained herein. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained herein is to the best of our knowledge at the date of publication, Fortis makes no representation about the accuracy of the information. If you need clarification or more information, you should contact Fortis Adhesives & Coatings. Fortis products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, Fortis Adhesives & Coatings products or reliance upon the information contained herein.

## **Technical Data Sheet**

## FORTIS GLUE RELEASE



Fortis Adhesives & Coatings Pty Ltd ABN 65 1333 915 732 14 Commercial Drive Dandenong South Victoria, Australia, 3175

www.fortisadhesives.com.au +61 3 9706 5448

Manufacturers of a range of Industrial Adhesives, Floor Coatings and Concrete Repair Systems. From Epoxy to Polyaspartic, Polyurethane to PVA, and with our Industry leading Technical Support, Fortis has you covered.