

FORTIS SOL-X



Fortis Sol-X is a thinning and cleaning solvent compatible with a number of Fortis products. **Fortis Sol-X** is the recommended thinner for **Fortis 823 HS Epoxy Coatings** and for the cleaning of uncured Fortis epoxy and polyurethane adhesives and coatings. **Fortis Sol-X** is also suitable for the cleaning of most surfaces prior to application of coatings or adhesives to remove oil and grease, dust and other contaminants.

Features and Benefits	<ul style="list-style-type: none"> Effectively cleans uncured epoxy and polyurethane adhesives and coatings Medium evaporation rate
Typical Applications	<ul style="list-style-type: none"> Thinning solvent Cleaning of application tools Cleaning uncured products Surface preparation
Properties	<ul style="list-style-type: none"> colourless clear liquid
Pack Size	4L
Safety	<ul style="list-style-type: none"> Refer to Safety Data Sheet prior to use Use only in well ventilated area. Good industrial hygiene practices should be observed at all times Appropriate PPE should be worn including impervious gloves & eye wear
Storage	Store in cool, dry conditions, out of direct sunlight and in a well-ventilated area. Do not store below 5°C or over 40°C
Application	<p>When used as a thinning solvent for Fortis 823 HS Epoxy Coating, a rate of 3-6% Fortis Sol-X is recommended.</p> <p>Fortis Sol-X has excellent solvency for oils and grease, and can be used for surface preparation and cleaning of tools before and after application.</p> <p>When used for surface preparation, do not allow Fortis Sol-X to pool on surfaces or run into joints and cracks. Allow product to completely evaporate prior to coating application.</p>
Limitations	Fortis Sol-X may cause irreversible damage or marring of some plastic substrates or existing protective coatings, smudging of ink, or other damage to surfaces. Carry out a small test on a non-critical area to ensure there are no negative outcomes.

For further information, including Safety Data Sheets and Technical Bulletins on adhesive applications and surface preparation, refer to the Fortis website www.fortisadhesives.com.au.

Disclaimer - Fortis products should be used in accordance with the information contained herein. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained herein is to the best of our knowledge at the date of publication, Fortis makes no representation about the accuracy of the information. If you need clarification or more information, you should contact Fortis Adhesives & Coatings. Fortis products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, Fortis accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of Fortis Adhesives & Coatings products or reliance upon the information contained herein.

Fortis Adhesives & Coatings Pty Ltd
 ABN 65 1333 915 732
 14 Commercial Drive
 Dandenong South
 Victoria, Australia, 3175
www.fortisadhesives.com.au
 +61 3 9706 5448

FORTIS SOL-X



Manufacturers of a range of Industrial Adhesives, Floor Coatings and Concrete Repair Systems. From Epoxy to Polyaspartic, Polyurethane to PVA, and with our Industry leading Technical Support, Fortis has you covered.