

Australia's first family of paint.

# HAYMES ARTISAN COLLECTION

# **Natural Clear Matte**

Product Code: ACNCM

#### **Product description**

Haymes Artisan Collection Natural Clear Matte is a versatile sealer designed to protect and maintain the appearance of flat and matt finishes such as Artisan Surface, Real Copper and Real Iron paints. It may also be used on its own to create decorative finishes.



#### Where to use

Ideal for interior and exterior use over the Artisan Collection range on walls and trim. It can be tinted and used as a decorative coating on its own to produce interesting effects, such as wood graining.

Typical properties		
Gloss	Matt	
Application tools	Brush, 15mm nap microfibre roller, conventional spray	
Clean-up	Water	
Dry time	Touch dry 4 hours	
Coverage	6-10m <sup>2</sup> /L depending on application technique and surface porosity.	
Colour	Clear	
Sizes	500 ml, 1 L, 4 L	
VOC	15 g/L	
Volume solids	30%	

Surface preparation		
General surface preparation	<ol> <li>Scrape all loose/flaking paint. Sand smooth and dust down.</li> <li>All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.</li> <li>Sand gloss surfaces to a dull finish. Remove all dust.</li> <li>Remove all traces of efflorescence or mould using a 10% bleach solution, especially on masonry or concrete surfaces.</li> </ol>	
Previously painted surfaces	1. Ensure surface to be coated is clean, dry and free of wax, grease and other contaminants.	

#### Application

Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C, or if conditions will drop below 10°C during the drying period. All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying, times will be extended.

Stir contents thoroughly before and during use with a broad, flat stirrer using an upward action.

Apply one coat over specified Artisan Collection decorative products.

Thoroughly load a 15mm microfibre sleeve with Natural Clear Matte and apply <u>gently</u> and evenly, cutting in as you progress to maintain a wet edge.

NOTE that if a second coat is applied it may leave a milky finish.

#### Thinning

Not required.

### Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

### Safety and First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when using. If swallowed DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Consult a doctor if symptoms persist.

#### Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website <u>www.paintback.com.au</u> for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

#### Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint <u>www.haymespaint.com.au</u>. We are continually updating materials and methods, so please ensure you have the latest information.

## Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd A.B.N. 14 004 201 638 Waringa Drive Wendouree Industrial Estate Ballarat Vic 3350 Free call 1800 033 431 Free fax 1800 801 892 www.haymespaint.com.au

Versioned:

Updated 3<sup>rd</sup> April, 2020 Replaces version dated 12<sup>th</sup> December, 2019