

HAYMES ARTISAN COLLECTION

Mortar

Product Code: ACM

Product description

Haymes Artisan Collection Mortar is a malleable finish that has an earthy textural matt appearance. It allows the walls to breathe and can be used internally or externally. When using the product externally, a beautiful characteristic of the finish is that as it matures, it gives an aged look and feel adding to the authenticity of the product within its surroundings.



Key Features

- ✓ Bespoke texture
- ✓ Handcrafted finish
- ✓ Premium Quality
- ✓ Interior & Exterior

Where to use

Surfaces such as plaster, plasterboard, cement blocks, mud bricks, bare-faced brick and cement render. Not recommended for bathrooms, wet areas or kitchens.

Typical properties

Gloss	Matt
Application tools	Brush, medium-long nap synthetic roller
Clean-up	Water
Dry time	Touch dry 2 hours Recoat 6 hours
Coverage	4-8m ² /L depending on application technique and substrate porosity
Colour	Tintable to a wide range of colours.
Sizes	500ml, 4L, 10L
VOC	8.5 g/L
Volume solids	46%

Surface Preparation

General surface preparation	<ol style="list-style-type: none">1. Scrape all loose/flaking paint. Sand smooth and dust down.2. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.3. Sand gloss surfaces to a dull finish. Remove all dust.4. Prime bare surfaces with appropriate Haymes undercoats or primers.5. Apply Mortar directly onto mud bricks. No undercoat required.
-----------------------------	---

Application

Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C, or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice. All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

1. Stir contents thoroughly before and during use with a broad, flat stirrer, using an upward action, or preferably use a power-driven mixing paddle.
2. In damp and humid conditions, the addition of an anti-mould solution is recommended for exterior use.
3. Thinning is usually required for the first coat. Thin with up to 100 ml of clean water per litre of paint to ease application.
4. Apply 2-3 coats with a medium to long nap roller dependent upon texture desired. Alternatively, Mortar can be applied with a broad bristle brush in a criss-cross motion to achieve a softer, aged effect.
5. When using brush application for the final coat, it is recommended that the product be diluted with 1–2 litres of water per 15 litre pail.

Please check the colour for accuracy prior to application. Haymes Paint accepts no responsibility for the application of incorrect colours.

IMPORTANT NOTE: The finished result of decorative finishes will vary dependent upon the applicator and the application technique used. Haymes Paint recommends a sample application be conducted prior to undertaking your project to ensure consistency of finish. This is due to the variance that may be experienced between the Haymes finished sample and that achieved by the applicator. We recommend viewing our instructional videos located at

www.haymespaint.com.au/artisancollection

Thinning

Thinning is usually required for the first coat. Thin with up to 100 ml of clean water per litre of paint to ease application.

Care and maintenance

Due to the finish exuding a textured finish we recommend the appropriate care is taken with items such as furniture and clothes that may come into contact with the finish. The textured nature of the finish may cause scratching to furniture and grabbing of clothes if contact is made.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety and First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well-ventilated conditions that prevent inhalation of vapours. If swallowed DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Consult a doctor if symptoms persist.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website www.paintback.com.au for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au . We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Versioned: Updated 13th January, 2021
Replaces version dated 3rd April, 2020