

HAYMES ARTISAN COLLECTION

Base Coat

Product Code: ACBC

Product description

Haymes Artisan Collection Base Coat is specifically formulated to provide a suitable base colour prior to applying the Artisan Collection topcoats. The Low VOC, 100% acrylic product provides fantastic coverage to enable minimal coats whilst ensuring easier application of your desired decorative finish.



Key Features

- ✓ Interior & Exterior

Where to use

All prepared interior and exterior surfaces such as plasterboard, timber, masonry and pre-painted surfaces.

Typical properties

Gloss	Low Sheen
Application tools	Brush, roller or spray
Clean-up	Water
Dry time	Touch dry 20 mins Recoat 2 hours
Coverage	Up to 16m ² /L
Colour	White, Dark Tint
Sizes	500ml, 1Lt, 4Lt, 10Lt
VOC	<5 g/L
Volume solids	40%
Film build	Wet 62um Dry 25um

Surface preparation

General surface preparation	<ol style="list-style-type: none">1. Fill cracks, nail holes and imperfections with Haymes Unifill.2. Scrape all loose/flaking paint. Sand smooth and dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.3. Clean surface with Haymes Unikleen and rinse with clean water.4. Prime bare plaster, timber and metal areas with appropriate Haymes undercoats or primers.
Previously painted surfaces	<ol style="list-style-type: none">1. Prepare any damaged areas as for General Surface Preparation.2. Apply one coat of Haymes Ultraseal to any patched areas.3. Sand gloss surfaces to a dull finish. Remove all dust.
Plasterboard	<ol style="list-style-type: none">1. Prepare any damaged areas as for General Surface Preparation.2. Apply one coat of Haymes Ultraseal to any patched areas.

Directions for use

Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C, or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice. All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

1. Stir thoroughly before and during application.
2. Apply 1-2 coats in the recommended tinted colour for your topcoat.

Please check the colour for accuracy prior to application. Haymes Paint accepts no responsibility for the application of incorrect colours.

Thinning

Thinning is not recommended unless spraying; add up to 100ml clean water per litre of paint to achieve acceptable atomisation. Up to 50ml of clean water per litre of paint can be added to ease application under very warm conditions.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety and First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when using. If swallowed DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Consult a doctor if symptoms persist.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website www.paintback.com.au for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au . We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Versioned: Updated 24th January,2022
Replaces version dated 3rd March 2020.