

ELITE

Precoat General Purpose Undercoat

Product Code: EPGPU

Product description

Haymes Elite General Purpose Undercoat is an oil based, self-levelling, superior covering, high opacity undercoat for interior and exterior use. It has excellent adhesion and sanding properties and is suitable for application to pre-painted surfaces.



Key Features

- ✓ Superior Coverage
- ✓ Fantastic gloss hold-out
- ✓ Easy to sand

Where to Use

A general purpose undercoat for Interior substrates and Exterior pre-painted surfaces including; timber, metal, sealed plasterboard, masonry and hardboard.

Typical properties

Gloss	13-20 @ 60
Application tools	Brush, roller, spray
Clean-up	Mineral Turpentine
Dry time	Touch dry 6 hours Recoat 16 hours
Coverage	Up to 16m ² /L
Colour	White.
Sizes	4L, 10L
VOC	360 g/L
Approvals	APAS 0016/1
Volume solids	55%
Film build	Wet 63 um Dry 34 um

Surface Preparation

General surface preparation and previously painted surfaces.

1. Fill cracks, nail holes and imperfections with Haymes Unifill.
2. Scrape all loose/flaking paint. Sand smooth & dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.
3. Not suitable for use on Customwood or MDF.

Application

Do NOT apply if ambient temperature is less than 10°C or greater than 30°C, or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice.

- To avoid skin contact, we recommend the use of disposable or rubber gloves.
- Stir thoroughly before and during application using a broad flat stirrer.
- Apply 1 even coat by brush, roller or spray.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperatures or higher humidity drying times will be extended.

Thinning

Thinning is not recommended unless spraying; add up to 100ml clean turps per litre of paint to achieve acceptable atomisation. Up to 50ml of turps can be added per litre of paint to ease application under very warm conditions.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety & First Aid

Read label before use. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Harmful in contact with skin. Causes skin irritation. IF ON SKIN OR HAIR: Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash skin with plenty of soap and water. If skin irritation occurs get medical advice. IF IN EYES: Wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice. Harmful if swallowed. IF SWALLOWED: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water. If symptoms develop or persist seek medical advice. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/eye protection. Wash exposed skin thoroughly after handling.

Dangerous Goods Classification



Flammable Liquid Class 3
Packaging Group III
PAINT
UN1263



Warning

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au . We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Date of Preparation 21/09/2016