

Elite®

General Purpose Undercoat

Product Base Code: EPGPU

	Product Description						
	<p>Haymes Paint Elite General Purpose Undercoat is an oil-based, self-levelling, superior covering, high opacity undercoat for interior and exterior use. It has excellent adhesion and sanding properties and is suitable for application to pre-painted surfaces.</p>						
Key Features & Benefits							
 Interior & Exterior	 Mineral Turpentine wash-up	 Coverage Up to 16 sqm/L					
 Recoat 16 hrs	<table border="1"> <tr> <td>Excellent coverage</td> <td>Easy to apply</td> </tr> <tr> <td>Fantastic gloss holdout</td> <td>Delivers a true, even sheen.</td> </tr> <tr> <td>Easy to sand</td> <td>Quick preparation</td> </tr> </table>	Excellent coverage	Easy to apply	Fantastic gloss holdout	Delivers a true, even sheen.	Easy to sand	Quick preparation
Excellent coverage	Easy to apply						
Fantastic gloss holdout	Delivers a true, even sheen.						
Easy to sand	Quick preparation						

Where to use	
Substrate :	Previously Painted Surface Timber-Exterior and Timber-Weatherboard
Interior :	Doors, Skirting and Architraves and Window Frames
Exterior :	Doors, Walls and Window Frames

Typical Properties	
Colour	White and White Undercoat
Application method	Brush, roller, spray
Clean-up	Mineral Turpentine
Dry time - touch dry	6 hours
Dry time - recoat	16 hours
Coverage	Up to 16 sqm/L dependent upon surface porosity, profile and method of application.
Sizes	4L, 10L
VOC	350 g/L
Volume solids	55%

Film build wet	63 µm
Film build dry	35 µm

Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Do NOT apply if rain or dew is expected within 24 hours of application.
- Provide adequate ventilation during application and the drying period.
- Do NOT paint in direct sunlight.
- Soak all cloths with traces of paint or solvent in water to prevent spontaneous combustion.

Surface Preparation

Previously painted surface	<ol style="list-style-type: none"> 1. Fill cracks, nail holes and imperfections with Haymes Unifill 2. Scrape all loose flaking paint. Sand smooth and dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. Not suitable for use on Customwood or MDF.
IMPORTANT:	You must consult the installation guide of the construction product you are using for information on coatings and finishing guide to determine product suitability prior to commencing work. For further information and product specification consult a Haymes Paint representative on 1800 033 431.

Application

- Stir thoroughly before and during application using a broad flat stirrer.
- Apply one coat.
- Application methods:
 - Brush: Use a quality synthetic brush.
 - Roller: Use a 10-12 mm nap length on smooth to semi-smooth surfaces.
 - Spray: Airless Spray, High Volume Low Pressure (HVLP)

Thinning

Thinning is not recommended unless spraying; add up to 100mL clean mineral turpentine per litre of product to achieve acceptable atomisation. Up to 50mL of mineral turpentine can be added per litre of product to ease application under very warm conditions.

Care and Maintenance

Protect the surface against knocks and abrasion for 7 days. Maximum adhesion may take several days to develop depending on film build and drying conditions.

Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact

Storage

Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. Only use this product in a well ventilated space and away from ignition sources. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit www.paintback.com.au for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website www.haymespaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymespaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version

Version and Date Issued	Version 2.1 Date 13/07/2023
Supersedes	Version 2.0 Date 27/06/2022

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park



Australia's first family of paint. SINCE 1935

Ballarat Vic 3355
Freecall 1800 033 431
www.haymepaint.com.au