

DECKING OIL

Natural

Product Code: NDO

Product Description

An easy to use natural exterior timber oil formulated to protect exterior timber against weathering. The transparent finish penetrates deep into the timber to nourish and prevent against timber deterioration. It is easy to maintain, will not peel, repels water and protects against mould and algae formation

Product Features

- ✓ Enhances timbers natural colour
- ✓ Will not peel
- ✓ UV Protection

Where to use

Exterior timber and decking

Typical Properties

| | |
|------------------------|--------------------------------------|
| Gloss | Matt |
| Application tools | Brush, Applicator Pad |
| Clean Up | Mineral Turpentine |
| Dry Time | Touch Dry 8 hours Recoat 24 hours |
| Coverage | Up to 10m ² /L |
| Colour | Natural |
| Sizes | 4L |
| Recommended Film Build | Wet 100um Dry 19um |

Surface Preparation

| SURFACE | PREPARATION |
|-----------------------------|--|
| General Surface Preparation | <ol style="list-style-type: none"> 1. Ensure all surfaces are clean, bare, dry and free of mould, wax, grease and other contaminants prior to applying Decking Oil. The presence of contaminants will cause rejection and delamination 2. Clean the surface thoroughly with Simply Woodcare Wood Cleaner following application instructions 3. Rinse surface clean using a pressure washer and allow to dry 4. Check timber is ready for coating by sprinkling with water. Ensure water penetrates the timber otherwise a repeat application of wood cleaner or longer weathering is required 5. Fill cracks, nail holes and imperfections with Simply Woodcare Wood Putty. Sand smooth and dust down |
| New Timber | <ol style="list-style-type: none"> 1. Timber must be weathered for a minimum of 4-6 weeks ensuring leaching of the tannins and extractives has ceased prior to application of coating. For very dense timbers such as Spotted Gum and Iron Bark, these may require weathering for up to 6 months. We recommend all resinous and dense timbers to be regularly hosed with water during this period to assist leaching of the extractives, this will enable the finish to penetrate and adhere increasing the performance and longevity of your coating. 2. Prepare as for General Surface Preparation |

| | |
|--------------------------------------|--|
| Previously Coated Surfaces | 1. For best results we recommend removal of all previous coatings |
| Previously Oiled or Stained Surfaces | 1. Timber in sound condition can be re-oiled to rejuvenate the surface 2. Where the oil is patchy or in unsound condition it should be sanded back to a bare surface 3. Proceed as for General Surface Preparation |

Application

DO NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period.

- Do not apply to hot surfaces or in direct sunlight.
- Stir thoroughly before and during application using a broad flat stirrer.
- Apply two coats by brush or applicator at recommended coverage rate.
- Apply along the length of the board including all exposed edges and end grain.
- Appropriate preparation and application thickness is vital to the performance and longevity of the product.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperatures or higher humidity drying times will be extended.

Thinning

Thinning is not recommended.

Care and Maintenance

Decking Oils requires higher maintenance than film forming products. For best results we recommend regular applications to protect your deck against frequent traffic and UV damage. Maintenance or re-coating of timber should occur at the first signs of deterioration or water penetration. Periodically cleaning the surface with a mild detergent or Simply Woodcare Wood Cleaner will rejuvenate the surface and extend the service life by removing contaminants, which can damage the surface.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety & First Aid Instructions

Keep out of reach of children. Do Not Swallow . Harmful: may cause lung damage if swallowed. Avoid contact with skin and eyes. Harmful by inhalation. Handling and usage of this product must be carried out under well-ventilated conditions. Wear suitable breathing equipment, protective clothing, eye protection and impervious gloves when using. Keep containers closed when not in use. This product is flammable. If affected by inhalation, remove to fresh air. If swallowed, **DO NOT INDUCE VOMITING**, drink plenty of water and seek immediate medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with water for at least 15 minutes.

If any symptoms persist or occur later, seek medical advice.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from www.haymespaint.com.au . We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time; those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Freecall 1800 033 431
Freefax 1800 801 892
www.haymespaint.com.au

Dangerous Goods

Flammable Class 3
Packaging Group III
UN1263
PAINT

Date of Preparation 19/8/14