

Ultra Premium

Prepcoat Ultraprime

Product Base Code: UPUP

	Product Description			
	<p>Haymes Paint Ultraprime is an anti-corrosive metal primer suitable for all steel and wrought iron surfaces. With superb adhesion, it seals the surface, creating a rust-preventing barrier that also protects against blistering and flaking. The oil-based formulation can be used under water-based or oil-based topcoats. Suitable for interior and exterior use.</p>			
 Interior & Exterior	 Mineral Turpentine wash-up	 Coverage Up to 16 sqm/L		
			Key Features & Benefits	
			Anti - corrosion protection	Protects metal surfaces against rust
Superb adhesion	Locks onto metal surfaces to form a rust-prevention barrier	 Recoat 16 hrs		
Universal metal primer	Compatible with water-based and oil-based topcoats.			

Where to use

Substrate :	Metal (ferrous)
Interior :	Doors, Trims and Window Frames
Exterior :	Doors, Gates, Trims and Window Frames

Typical Properties

Colour	Grey
Application method	Brush, roller, spray, airless spray
Clean-up	Mineral Turpentine
Dry time - touch dry	4 hours
Dry time - recoat	16 hours
Coverage	Up to 16 sqm/L dependent upon surface porosity, profile and method of application.
Sizes	500mL, 1L, 4L
VOC	408 g/L
Volume solids	44%
Film build wet	63 µm
Film build dry	27 µm

Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Do NOT apply if rain or dew is expected within 24 hours of application.
- Provide adequate ventilation during application and the drying period.
- Do NOT paint in direct sunlight.
- Soak all cloths with traces of paint or solvent in water to prevent spontaneous combustion.

Surface Preparation

General surface preparation	All surfaces must be clean, bare, dry and free of wax, grease, rust and other surface contaminants. Remove all rust by abrasive blasting or mechanical sanding. Use Haymes Paint Derustit on any remaining traces of rust. Apply Ultraprime within 24 hours of blasting or sanding.
Metal (ferrous), steel, wrought iron	Remove all loose rust by wire brushing, scraping or sanding. Apply one coat of Haymes Paint Ultraprime or two coats when a water-based topcoat is used. For harsh exposure environments and areas within 3 km of the coast apply two coats of Haymes Paint Ultraprime.
IMPORTANT:	You must consult the installation guide of the construction product you are using for information on coatings and finishing guide to determine product suitability prior to commencing work. For further information and product specification consult a Haymes Paint representative on 1800 033 431.

Application

- Stir thoroughly before and during application using a broad flat stirrer.
- Apply one to two coats.
- Application methods:
 - Brush: Use a quality synthetic brush.
 - Roller: Use a 8-10mm microfibre cover on smooth to semi smooth surfaces.
 - Spray: Airless Spray, High Volume Low Pressure (HVLP).

Thinning

Thinning is not recommended unless spraying; add up to 100mL clean mineral turpentine per litre of product to achieve acceptable atomisation. Up to 50mL of mineral turpentine can be added per litre of product to ease application under very warm conditions.

Care and Maintenance

Protect the surface against knocks and abrasion for 7 days. Maximum adhesion may take several days to develop depending on film build and drying conditions.

Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact

Storage

Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. Only use this product in a well ventilated space and away from ignition sources. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit www.paintback.com.au for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website www.haymespaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymespaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version

Version and Date Issued	Version 2.1 Date 02/09/2024
Supersedes	Version 2.0 Date 27/06/2022

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park



Australia's first family of paint. SINCE 1935

Ballarat Vic 3355
Freecall 1800 033 431
www.haymepaint.com.au