

ELITE

Trim Enamel High Gloss

Product Code: ETEHG

Product description

Haymes Elite Enamel High Gloss is an interior/exterior, high quality, oil-based premium grade enamel that produces an extremely tough, hard wearing, mark resistant coating. Easy to apply, with excellent coverage the Elite Enamel has excellent flow and levelling ensuring a smooth finish.



Key Features

- ✓ Hard wearing
- ✓ Superb coverage
- ✓ Excellent levelling

Where to Use

Doors, windows, skirtings, furniture, trim, and walls where an extremely tough finish is required.

Typical properties

Gloss	78-90 @ 20°
Application tools	Brush, roller, spray
Clean-up	Mineral Turpentine
Dry time	Touch dry 4-6 hours Recoat 16 hours
Coverage	Up to 16m ² /L
Colour	White, Tintable
Sizes	4L, 10L
VOC	406 g/L
Approvals	APAS 0015/1
Volume solids	48%
Film build	Wet 63 um Dry 31 um

Surface Preparation	
General surface preparation	<ol style="list-style-type: none"> 1. Fill cracks, nail holes and imperfections with Haymes Unifill. 2. Scrape all loose/flaking paint. Sand smooth and dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. 3. Prime bare plaster, timber and metal areas with appropriate undercoats or primers.
Previously painted surfaces	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation. 2. Sand gloss surfaces to a dull finish. Remove all dust. 3. Apply one coat of Tricoat.
Timber	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation. 2. Apply one coat of Tricoat.
Steel & wrought iron	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation. 2. Remove any areas of rust. 3. Apply one coat of Metal Primer.
Galvanised iron	<ol style="list-style-type: none"> 1. Degrease. 2. Wash with Unikleen and a scourer and rinse with clean water. 3. Apply 1 coat of Tricoat. 4. Structural galvanised iron must also be abraded and coated with a coat of Metal Primer followed by a coat of Acrylic Sealer Undercoat.
Zincalume®	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation. 2. Apply one coat of Acrylic Sealer Undercoat.

Application
<p>Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice.</p> <ul style="list-style-type: none"> • Stir thoroughly before and during application. • Apply 2 coats by brush, roller or spray. • All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended. <p>Note:</p> <p>All oil-based enamels will yellow with age. This can be accelerated in areas with low amounts of natural light and is more visible with white or very light colours. To reduce the effects of yellowing we recommend;</p> <ol style="list-style-type: none"> 1. Providing maximum ventilation during application and drying. 2. Avoid applying water-based paint in the vicinity of freshly painted enamel 3. Refrain from using household cleaners containing high levels of ammonia within the first month following application of the enamel. <p>If there is risk of yellowing Haymes recommend the use of Ultratrim Semi Gloss Acrylic Enamel.</p>

Thinning
<p>Thinning is not recommended unless spraying, add up to 100ml clean mineral turps per litre of paint to achieve acceptable atomisation. Up to 50ml of mineral turps can be added per litre of paint to ease application under very warm conditions.</p>

Care and Maintenance
<p>New paintwork should not be exposed to steam or condensation for 72 hours. Protect the coating against abrasive contact for 7 days. After 7 days the finish can be cleaned with a mild detergent solution and a soft cloth.</p>

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety & First Aid

Read label before use. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Harmful in contact with skin. Causes skin irritation. IF ON SKIN OR HAIR: Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash skin with plenty of soap and water. If skin irritation occurs get medical advice. IF IN EYES: Wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice. IF SWALLOWED: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water. If symptoms develop or persist seek medical advice. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection. Wash exposed skin thoroughly after handling.

Dangerous Goods Classification



Packaging Group III
PAINT
UN1263



Warning

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Date of Preparation 21/09/2016