

ULTRA PREMIUM PREPCOAT

Ultrahold

Product Code: UPUH

Product description

Haymes Ultrahold is a methylated spirit-based stain blocker especially formulated to provide a very fast drying barrier coating to prevent the penetration of bleeding stains and odours through subsequent coatings. The blocking properties of Ultrahold makes it ideal for blocking stains from water, smoke, fire damage, tannin, mould, pets and more. Ultrahold has superb adhesion to most surfaces and can be over-coated with water-based or solvent-based topcoats.



Key Features

- ✓ Superior stain blocking
- ✓ Superb adhesion
- ✓ Rapid 1 hour recoat
- ✓ Suitable for interior use only

Where to Use

Suitable for Interior use on most surfaces including plasterboard, set plaster, concrete, masonry, timber, varnishes and gloss paints.

Typical properties

Gloss	3-5 @ 60°
Application tools	Brush, roller, spray
Clean-up	Methylated spirits
Dry time	Touch dry 15 mins Recoat 1 hours
Coverage	Up to 16m ² /L
Colour	White
Sizes	1L, 2L, 4L
VOC	602g/L
Volume solids	25%
Film build	Wet 62um Dry 15um

Surface Preparation

General surface preparation	<ol style="list-style-type: none">1. Fill cracks, nail holes and imperfections with Haymes Unifill.2. Scrape all loose/flaking paint. Sand smooth & dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.3. Prime bare timber and metal areas with appropriate primers.
Previously painted surfaces	<ol style="list-style-type: none">1. Prepare any damaged areas as for General Surface Preparation.2. Wash the surface thoroughly.3. Sand gloss surfaces to a dull finish and remove all dust.
Plasterboard	<ol style="list-style-type: none">1. Prepare any damaged areas as for General Surface Preparation2. Sand smooth and remove all dust.
Set plaster	<ol style="list-style-type: none">1. Prepare any damaged areas as for General Surface Preparation2. Vacuum or brush surfaces to remove all dust.
Masonry, brick, concrete, render	<ol style="list-style-type: none">1. New concrete and render must be cured for at least 28 days prior to painting.2. Wash with Haymes Unikleen & rinse with clean water.

Application

Do NOT apply if ambient temperature is less than 10°C or greater than 30°C, or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice.

- To avoid skin contact, we recommend the use of disposable or rubber gloves.
- Stir thoroughly before and during application using a broad flat stirrer.
- Apply 1 even coat by brush or roller.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

Thinning



Thinning is not generally recommended. Under warm conditions the product can be thinned using up to 50ml of methylated spirits per litre of paint.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety & First Aid

Read label before use. Keep out of reach of children. Highly flammable liquid and vapour. Harmful if inhaled. Avoid breathing vapours. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN OR HAIR: Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash skin with plenty of soap and water. If skin irritation occurs get medical advice. Causes serious eye irritation. IF IN EYES: Wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice. IF SWALLOWED: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water. If symptoms develop or persist seek medical advice. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/ eye protection. Wash exposed skin thoroughly after handling.

Dangerous Goods Classification	
 <p>Flammable Class 3 Packaging Group II UN1263 PAINT</p>	 <p>Danger</p>

Protect our environment
DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment
This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au . We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer
The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymespaint.com.au

Date of Preparation 21/09/2016