

ULTRA PREMIUM PREPCOAT

Ultracover

Product Code: UPUC

Product Description

An interior/exterior multi-use primer, sealer and undercoat, Haymes Ultracover offers superb coverage, excellent gloss holdout and superior adhesion. An environmentally-aware Low VOC formulation that is easy-to-use, quick drying and offers excellent filling and sanding properties. Ultracover is suitable for blocking efflorescence salts on masonry and render as well as for sealing graffiti, water, pencil, mildew and smoke stains. Ultracover is blister resistant and can be top coated with either water-based or oil-based paints whilst offering the convenience of water wash-up.

Product Features

- ✓ Superior adhesion
- ✓ Seals stains
- ✓ Blocks efflorescence leaching
- ✓ Suitable for Interior & Exterior



Where to use

Masonry, render, timber, galvanized iron, Zinalume®, aluminium, plasterboard, MDF, PVC and previously painted surfaces. Suitable for use over water or oil based paint. Seals stains such as permanent marker, pencil, water, smoke, tobacco and mildew.

Typical Properties

Application tools	Brush, roller, spray
Wash up	Water
Touch Dry	20 mins
Recoat	2 hours
Coverage	Up to 16m ² /L
Colour	White, Tintable to Haymes tinted undercoat formulations
Sizes	500ml, 1, 2, 4, 10L
VOC	<5g/L
Volume Solids	37%
Film Build per coat	Wet 63 um Dry 23 um

Surface Preparation

General Surface Preparation	<ol style="list-style-type: none"> 1. Fill cracks, nail holes and imperfections with Haymes Unifill. 2. Scrape all loose/flaking paint. Sand smooth & dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. 3. Prime bare timber and metal areas with appropriate primers.
Previously Painted Surfaces	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation. 2. Wash the surface thoroughly. Use a scouring pad on old enamel surfaces. 3. Clear finishes require sanding to remove gloss prior to painting.
Plasterboard	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation 2. Sand smooth & dust down
Timber & MDF	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation
Masonry, Brick, Concrete, Render	<ol style="list-style-type: none"> 1. New concrete and render must be cured for at least 28 days prior to painting. 2. Wash with Haymes Unicleen & rinse with clean water.
Galvanised Iron	<ol style="list-style-type: none"> 1. Degrease new galvanised iron 2. Use a scourer to wash with Haymes Unicleen and rinse with clean water.

	3. Structural Galvanised iron must be abraded and primed with a metal primer.
Zincalume [®]	1. Wash with Haymes Unikleen and rinse with clean water.
Aluminium	1. Wash with Haymes Unikleen and rinse with clean water.
Steel & Wrought iron	1. Remove all rust by abrasion or blasting to achieve a bright steel surface 2. Apply 2 coats of Haymes Ultraprime
Stain sealing	1. Prepare any damaged areas as for General Surface Preparation. 2. Wash the surface thoroughly to remove as much stain as possible and allow to dry. 3. Apply Haymes Ultracover and allow to dry overnight prior to top coating. 4. Some stains may require 2 coats of Haymes Ultracover and in the case of severe staining it may be necessary to Haymes Ultralock solvent based primer sealer undercoat.
Laminex	1. Prepare any damaged areas as for General Surface Preparation 2. Wash with Haymes Unikleen and rinse with clean water. 3. Sand surface with sandpaper to degloss the surface

Application

Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice.

- To avoid skin contact, we recommend the use of disposable or rubber gloves.
- Stir thoroughly before and during application using a broad flat stirrer.
- May be tinted to Haymes TU formulations.
- Apply 1 even coat by brush, roller or spray.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

Thinning

This product should not be thinned unless the surface is very porous or unless required for spraying. If necessary, use up to 100ml of clean water per litre of paint.

Care and maintenance

Protect the surface against knocks and abrasion for 7 days. Maximum adhesion may take several days to develop depending on film build and drying conditions.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety & First Aid Instructions

Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 1126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint (1800 033 431). We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time; those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive Wendouree Industrial Estate
Ballarat Vic 3350
Freecall 1800 033 431
Freefax 1800 801 892
www.haymespaint.com.au

Date of Preparation 10/07/2017