

ELITE Exterior Gloss

Product Code: EEGW

Product Description

A high quality, easy to apply, water based, self-priming 100% acrylic paint ideal for various exterior surfaces. It has excellent UV resistance and durability that provides fantastic coverage and is reinforced with a 12 Year Guarantee against blistering, peeling & flaking.

Product Features

- ✓ Excellent UV resistance
- ✓ Self-priming
- ✓ Fantastic coverage



Where to use

Weatherboards, brick and block work, render, pergolas and exterior timber surfaces

Typical Properties

Gloss	Gloss 20° > 40 60° > 70
Colour	White, Tintable
Sizes	4L, 10L, 15L
Clean Up	Water
Dry Time	Touch dry 20 mins Recoat 2 hours
Coverage	Up to 16m ² /L
Film Build	Wet 62um Dry 22um
Volume Solids	36%
VOC	65 g/L
Approvals	APAS 0280/4
Application tools	Brush, roller, spray

Surface Preparation

General Surface Preparation	<ol style="list-style-type: none"> 1. Fill cracks, nail holes and imperfections with Haymes Unifill. 2. Scrape all loose/flaking paint. Sand smooth & dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. 3. Prime timber and metal areas with appropriate primers.
Previously Painted Surfaces	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation. 2. Apply one coat of Haymes Acrylic Sealer Undercoat to any patched areas. 3. Sand gloss surfaces to a dull finish. Remove all dust

Timber	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation. 2. Remove any grey timber. 3. Apply 3 coats of Elite Exterior.
Masonry, Brick, Concrete, Render	<ol style="list-style-type: none"> 1. Wash with Haymes Unikleen & rinse with clean water.
Steel & Wrought Iron	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation. 2. Remove any areas of rust. 3. Apply one coat of Metal Primer
Galvanised Iron	<ol style="list-style-type: none"> 1. Degrease 2. Wash with Unikleen and a scourer and rinse with clean water 3. Apply 1 coat of Tricoat 4. Structural Galvanized Iron must also be abraded and coated with a coat of Metal primer.
Zincalume ®	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation.

Application

Do NOT apply if ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.

- Stir thoroughly before and during application.
- Apply 2 coats by brush, roller or spray. At times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.
- Please check the colour for accuracy prior to application. Haymes paint accepts no responsibility for the application of incorrect colours.

Thinning

Thinning is not recommended unless spraying; add up to 100ml clean water per litre of paint to achieve acceptable atomisation. Up to 50ml of water can be added per Litre of paint to ease application under very warm conditions.

Care and Maintenance

To rejuvenate the surface coating and extend the longevity regular cleaning is recommended. Clean the surface using a pressure washer to remove dirt and debris.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

First Aid & Safety Advice

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapours, use under well ventilated conditions to prevent inhalation of vapours. Wear suitable protective clothing, eye protection and impervious gloves. If affected by inhalation, remove to fresh air. If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. Should any symptoms persist seek prompt medical advice.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint (1800 033 431). We are continually updating materials and methods, so please ensure you have the latest information.

Warranty

Haymes guarantees that Haymes Elite Exterior will not flake, blister or peel for 12 years. For this warranty to apply Haymes Elite must be applied to correctly prepared surfaces. This warranty does not cover failure caused by the breakdown of any previous coatings. For the warranty to be valid Henry Haymes Pty Ltd must be notified within 14 days of the claimant becoming aware of an alleged fault and within 30 days of the initiation of the alleged fault. Should the alleged fault prove to be due to faulty product to the satisfaction of Henry Haymes Pty Ltd, Henry Haymes Pty Ltd will provide, free of charge, sufficient paint to rectify the affected area. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Contact Haymes Service Express 1800 033 431.

Please check the colour for accuracy prior to application. Haymes Paint accepts no responsibility for the application of incorrect colours.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time; those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive, Wendouree Industrial Estate
Ballarat Vic 3350
Freecall 1800 033 431
Freefax 1800 801 892
www.haymepaint.com.au

Date of Preparation 19/7/13