

## ELITE

### Acrylic Sealer Undercoat

Product Code: EPASU

#### Product Description

Elite Acrylic Sealer Undercoat is a premium quality acrylic sealer undercoat that is over 99% VOC Free. Providing superior coverage and adhesion, it is easy to sand, has excellent filling properties and can be over coated with either acrylic or oil based systems. Suitable for interior use only it is quick drying and easy to apply.



#### Product Features

- ✓ Superb coverage
- ✓ Easy to sand
- ✓ Excellent filling properties

#### Where to use

Plasterboard, MDF, timber, masonry and previously painted surfaces.

#### Typical Properties

Colour	White
Sizes	4L, 10L, 15L
Clean Up	Water
Dry Time	Touch Dry            20 mins Recoat                2 hours
Coverage	Up to 16m <sup>2</sup> /L
Film Build	Wet 63um Dry 22um
Volume Solids	35.2%
VOC	<5g/L
Approvals	APAS 0172
Application tools	Brush, Roller, Spray

#### Surface Preparation

General Surface Preparation & Previously Painted Surfaces	<ol style="list-style-type: none"> <li>1. Fill cracks, nail holes and imperfections with Haymes Unifill.</li> <li>2. Scrape all loose/flaking paint. Sand smooth &amp; dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.</li> <li>3. Wash surface thoroughly. Prime bare timber and metal areas with appropriate primers.</li> </ol>
Plasterboard	<ol style="list-style-type: none"> <li>1. Complete General Surface Preparation</li> <li>2. Sand joins smooth and dust down.</li> </ol>
Timber & MDF	<ol style="list-style-type: none"> <li>1. Complete General Surface Preparation.</li> <li>2. Apply one coat of a stain blocking primer on tannin-rich timber.</li> </ol>

## Application

Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.

- Stir thoroughly before and during application.
- Apply 1 coat by brush, roller or spray.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

## Thinning

Thinning is not recommended unless spraying; add up to 100ml clean water per litre of paint to achieve acceptable atomisation. Up to 50ml of water can be added per Litre of paint to ease application under very warm conditions.

## Care and Maintenance

New paintwork should not be exposed to steam or condensation for 72 hours. Protect the coating against abrasive contact for 7 days.

## Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

## First Aid & Safety Advice

**Keep out of reach of children.** Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.

## Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

## Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint (1800 033 431). We are continually updating materials and methods, so please ensure you have the latest information.

## Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time; those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Estate  
Ballarat Vic 3350  
Freecall 1800 033 431  
Freefax 1800 801 892  
[www.haymepaint.com.au](http://www.haymepaint.com.au)

Date of Preparation 24/10/14