

PRODUCT DATA SHEET

HAYMES DESIGNER FINISHES SUEDE



GENERAL DESCRIPTION

A rich ultra premium paint that dries to a soft matt finish, delivering a textured, sophisticated look.

USES

Interior and Exterior brad wall areas

COLOURS

Available in a range of 24 fashionable colours.

SIZES

Available in 2 litres, 5 litres and 500mls.

COVERAGE

Approximately 5-10 square metres per litre depending upon surface porosity and application method.

APPLICATION

Roller and brush.

PROVIDE ADEQUATE VENTILATION DURING USE.

DRYING TIMES

Touch Dry Time - 1 hour.

Recoat Dry Time - 4 hours.

Drying times refer to normal conditions (25°C, 50% humidity). Under cooler, humid or still conditions, longer drying times may be necessary.

DO NOT USE IN TEMPERATURES BELOW 10°C OR ABOVE 30°C.


DANGEROUS GOODS CLASSIFICATION

Not classified as Dangerous Goods.

SURFACE PREPARATION


Surface should be clean, dry and free of dust and other contaminants. Scrape all loose/flaking paint and sand smooth then dust down. Bare timbers and metal areas should be primed and/or undercoated with Haymes Acrylic Sealer Undercoat.

QUICK CHECK

 Interior/ Exterior

 Water Wash Up

 Roller & Brush

 Recoat - 4 hours

APPLICATION

To avoid skin contact we recommend the use of disposable gloves.

Stir paint thoroughly before and during application with a broad flat stirrer. Apply the first coat generously using a 8-10mm nap roller and roll as close to the edge as possible, finish the first coat by cutting in with a brush.

The second coat should be applied using a wide brush with random criss-cross strokes, take care to maintain a wet edge. A more random application results in a more attractive finish.

The final coat should be completed by one person to achieve a uniform appearance over the entire area.

The full suede appearance may take up to 72 hours to fully develop.

FINISHING

Protect the surface from water and other liquids for 24 hours after application. Avoid abrasive contact for at least 7 days after application, the surface can be cleaned by gently wiping with a mild detergent solution and a soft cloth.

THINNING & CLEAN UP

Thinning is not recommended. Clean all equipment with water immediately after use.

PAINTING CONDITIONS

Do not apply if the temperature is below 10°C or above 30°C.

STORAGE

Protect from extremes of temperature. Store between 5°C and 30°C.

PRECAUTIONS

- **Safety Directions:** **KEEP OUT OF REACH OF CHILDREN** Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist.
- **First Aid Instructions:** If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, **DO NOT INDUCE VOMITING** drink plenty of water and seek medical advice. Contact a Doctor or Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.
- **Protect Our Environment:** **DO NOT** pour left over product down the drain. Retain it in a marked sealed container for future use or disposal via chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council metal recycling facilities. Do not re-use empty cans.

For best results, preparation is vitally important when repainting. Always ensure that the adhesion of old paint is sound before proceeding.

**For further information or to place an order, call
Service Express direct: Phone - 1800 033 431
or email at - www.haymespaint.com.au**