

## ULTRA PREMIUM QuickPave Paving Paint

Product Code: QPP

### Product Description

Haymes QuickPave is a high quality paving paint with superior long lasting exterior durability. QuickPave is resistant to oil and hot tyres and dries to a semi-gloss finish.



### Product Features

- ✓ Water-based
- ✓ Quick drying
- ✓ Self priming
- ✓ Suitable for interior and exterior use

### Where to use

Suitable for use on floors, paths, driveways, concrete, stone and brick.

Note: Not suitable for use on Timber and Timber Decking.

### Typical Properties

Gloss	60° 12 - 18
Colour	White, UDT, DKT, EDT
Sizes	2,4,10L
Clean Up	Water
Dry Time	2 hours
Coverage	Up to 12m <sup>2</sup> /L depending on surface roughness and porosity
Film Build per coat	Wet 83um Dry 28um
Volume Solids	35%
VOC	51g/L
Approvals	NA
Application tools	Roller, brush or airless spray

### Surface Preparation

Previously Painted Surfaces	<ol style="list-style-type: none"> <li>1. Check the existing coating for adhesion by cutting an "X" in the surface with a sharp knife. Press tape firmly over the cut and pull off sharply. If any coating is removed then the existing coating must be removed prior to painting. Haymes recommends testing in several areas.</li> <li>2. Test for compatibility by sanding and cleaning a small area and applying 1 coat of QuickPave. After 24 hours conduct the test in step 1 again. Removal of QuickPave from the existing coating indicates that QuickPave cannot be used on the existing coating.</li> <li>3. Sand gloss surfaces to a dull finish. Remove all dust</li> <li>4. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. Remove oil stains using a degreaser</li> <li>5. Pressure wash the surface and allow to dry</li> </ol>
-----------------------------	---

Rough porous concrete (Rougher than 120 grit sandpaper)	<ol style="list-style-type: none"> <li>1. New concrete must be aged for at least 4 weeks prior to painting</li> <li>2. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. Remove oil stains using a degreaser</li> <li>3. Pressure wash the surface and allow to dry</li> <li>4. Removal of all dust and loose concrete is essential for a successful job. Brush the surface with a stiff bristle broom and vacuum residues. Test for dust by pressing tape on the surface. If the tape has dust particles present more thorough vacuuming is required.</li> </ol>
Smooth concrete	<ol style="list-style-type: none"> <li>1. New concrete must be aged for at least 4 weeks prior to painting</li> <li>2. Smooth concrete must be etched or abraded to achieve adequate penetration of the coating. Etch the surface using 5% Citric or hydrochloric acid thoroughly mixed into clean water.</li> <li>3. Apply the etching solution to the concrete and allow to stand for 10 minutes or until any bubbling has stopped.</li> <li>4. Pressure wash the surface thoroughly with clean water. All etching debris must be thoroughly removed.</li> <li>5. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. Remove oil stains using a degreaser</li> <li>6. Removal of all dust and loose concrete is essential for a successful job. Brush the surface with a stiff bristle broom and vacuum residues. Test for dust by pressing tape on the surface. If the tape has dust particles more thorough vacuuming is required.</li> <li>7. For car traffic, concrete must be as rough as 120 grit sandpaper.</li> </ol>
Stone or brick	<ol style="list-style-type: none"> <li>1. QuickPave can only be used on non-glazed surfaces</li> <li>2. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. Remove oil stains using a degreaser</li> <li>3. Pressure wash the surface and allow to dry</li> </ol>

### Application

Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period.

- Stir thoroughly before and during application.
- On bare surfaces the paint must be thinned for the first coat to achieve adequate penetration. Add 200ml of clean water per Litre of paint and stir thoroughly. Do not thin for subsequent coats.
- Apply 2 coats by brush, roller or spray. At times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.
- Please check the colour for accuracy prior to application. Haymes paint accepts no responsibility for the application of incorrect colours.

### Care and Maintenance

The surfaces can be walked on with bare feet or soft shoes in 2 hours. Protect the coating against abrasive contact for 7 days. After 7 days the finish can be cleaned with a mild detergent solution and a broom. Protect from car traffic for 7 days. Take care walking on wet surfaces, we recommend the addition of Haymes QuickPave Non Slip Additive if additional grip is required. Haymes does not recommend QuickPave for sloped surfaces.

### Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

### Safety Directions

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapours. Wear suitable protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well ventilated conditions that prevent inhalation of vapours.

**First Aid Instructions**

If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, drink plenty of water and seek immediate medical advice. Contact a doctor or Poisons Information Centre (Phone 13 1126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.

**Protect our environment**

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

**Manufacturer's comment**

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint (1800 033 431). We are continually updating materials and methods, so please ensure you have the latest information.

**Disclaimer**

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Estate  
Ballarat Vic 3350  
Freecall 1800 033 431  
Freefax 1800 801 892  
[www.haymepaint.com.au](http://www.haymepaint.com.au)

Date of Preparation      6/10/15