

Ultra Premium

Ultratrim Acrylic High Gloss

Product Base Code: UTG



Product Description

Haymes Paint Ultratrim High Gloss is a quick-drying, low odour, water-based acrylic enamel. The tough, chip-resistant properties provide a long-lasting finish for interior and exterior trim applications. Ultratrim is non-yellowing and doesn't discolour compared with traditional enamel paints. It has the convenience of water wash-up and dries to a smooth glossy finish.

Key Features & Benefits

Tough and durable	Traditional enamel replacement
Low-odour	No fumes or lingering odour
Fast drying	Quick 2-hour recoat
Non-yellowing	Retains original colour



Interior &
Exterior



Water wash-up



Coverage
Up to 16
sqm/L



Recoat
2 hrs

Where to use

Substrate :	Aluminium Colorbond Metal (ferrous) Zinc treated steel Timber and MDF
Interior :	Built-in robes/Cupboards, Doors, Skirting and Architraves, Trims and Window Frames
Exterior :	Doors, Trims and Window Frames

Typical Properties

Colour	White, Ultra Deep Tint, Dark Tint, Extra Dark Tint, Blue Tint, Green Tint, Orange Extra Tint, Red Tint and Yellow Extra Tint
Application method	Brush, roller, spray, airless spray
Gloss level	20° 40 - 55, 60° 75 -85
Clean-up	Water
Dry time - touch dry	20 minutes
Dry time - recoat	2 hours
Coverage	Up to 16 sqm/L dependent upon surface porosity, profile and method of application.
Sizes	500mL, 1L, 4L, White also available in 2L and 10L
VOC	49 g/L
Volume solids	35%
Film build wet	62 µm
Film build dry	22 µm

Approvals

Standard ID	Description	Complies With
APAS 0260/1 Note: Applies to White, Ultra Deep, Dark and Extra Dark Tint only.	Interior gloss latex paint(buildings)	AS3730.12
GGT STANDARD VER 4.0	GreenTag GreenRate Level A	
GGT STANDARD VER.4.0	GreenTag PHD PlatinumHealth	

Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Do NOT apply if rain or dew is expected within 24 hours of application.
- Provide adequate ventilation during application and the drying period.
- Do NOT paint in direct sunlight.
- Please consider the use of dark colours on exposed building materials, and follow the manufacturers light reflectance value (LRV) recommendation.
- For bright and deep colours, to ensure colour accuracy and opacity, apply the specified tinted undercoat prior to the application of the top coat(s).
- Under normal conditions, the coating may require up to seven days curing to develop hardness and properties.
- If more than one can is required for the final coat, mix all cans together prior to commencing.
- Please check the colour for accuracy before application. Haymes Paint accepts no responsibility for the application of incorrect colours.

Surface Preparation

General surface preparation	All surfaces must be clean, bare, dry and free of wax, grease and other surface contaminants. Fill any cracks, nail holes or imperfections with the appropriate filler. Sand smooth and dust down. If mould is present, treat the surface with a mould remover to effectively eliminate the mould spores. All traces of mould must be removed prior to painting. Some primers used on preprimed timber are of low quality. Unless a painting specification is supplied by the timber manufacturer, the timber must be sanded back to bare timber before coating.
Previously painted surface	Conduct an adhesion test [1], followed by a compatibility test [2]. Scrape all loose flaking paint. Sand surface smooth to a dull finish and remove all dust. Apply one coat of Haymes Paint Ultracover to any patched areas followed by one coat over the entire surface.
Timber	Weathered or greyed timber should be sanded to the original timber surface. Apply one coat of Haymes Paint Ultralock for tannin-rich timbers. For pre-primed timbers, please refer to the manufacturer's painting specification [3].
Galvanised iron	Thoroughly degrease new surfaces with a non-metallic scourer. Wash degreased and weathered surfaces using Haymes Paint Unikleen sugar soap. Rinse with clean water. Apply one coat of Haymes Paint Ultracover. Structural Galvanised iron must be abraded and primed with a metal or etch primer.

Surface Preparation	
Zincalume®	Remove oil using a solvent degreaser, then wash with Haymes Paint Unikleen using a mop or soft bristle brush, rinse with clean water. Apply one coat of Haymes Paint Ultracover.
Metal (ferrous), steel, wrought iron	Remove all loose rust by wire brushing, scraping or sanding. Apply one coat of Haymes Paint Rustlock Primer or Ultraprime or two coats of Ultraprime with a water-based topcoat. For harsh exposure environments and areas within 3 km of the coast apply two coats of Haymes Paint Ultraprime or Rustlock Primer. For longer-lasting corrosion protection on new surfaces, Haymes Paint recommend the application of Rustlock metal protection system.
Aluminium	Wash with Haymes Paint Unikleen & rinse with clean water. Abrade the surface with a non-metallic scourer. Apply one coat of Haymes Paint Ultracover.
MDF	Check that any pre primers are suitable for painting by cutting an X through the coating. Press tape firmly over the X and pull off sharply. If any coating is stuck to the tape, then the pre-primer must be entirely removed by sanding prior to any further painting. Sand smooth and remove all dust. Apply one coat of Haymes Ultraseal or Ultracover.
Colorbond®	Ensure weathered surfaces are clean and free of salts or other deposits. Wash new surfaces with a non-metallic scourer and Haymes Paint Unikleen sugar soap. Apply one coat of Haymes Paint Ultracover.
Zincanneal®, Galvanneal and Duragal®	Ensure Zinc treated surfaces are clean and free of oil, salts or other deposits. Remove oil using a solvent degreaser, then wash new surfaces with a non-metallic scourer and Haymes Paint Unikleen sugar soap. Apply one coat of Haymes Paint Ultracover.
Adhesion test	[1] To check the adhesion of an existing coating, cut an 'X' lightly into the coating and firmly apply adhesive tape across the cut and then remove tape. If the tape removes the existing coating, remove all previous coatings before painting.
Compatibility test	[2] Test for compatibility with a previous coating by sanding and cleaning a small inconspicuous area. Apply 1 coat of the desired topcoat and allow to dry. After 24 hours, conduct an adhesion test. If the tape removes the coating, remove all previous coatings before painting. It is recommended to conduct the compatibility test in several areas.
Preprimed timber	[3] Some primers used on preprimed timber are of low quality. Unless a painting specification is supplied by the timber manufacturer, the timber must be sanded back to bare timber before coating.
IMPORTANT:	You must consult the installation guide of the construction product you are using for information on coatings and finishing guide to determine product suitability prior to commencing work. For further information and product specification consult a Haymes Paint representative on 1800 033 431.

Application
<ul style="list-style-type: none"> • Stir thoroughly before and during application using a broad flat stirrer. • Apply one to two coats. • Application methods: <ul style="list-style-type: none"> • Brush: Use a quality synthetic brush. • Roller: Use a 8-10mm microfibre cover on smooth to semi smooth surfaces. • Spray: Airless Spray, High Volume Low Pressure (HVLP).

Thinning

Thinning is not recommended unless spraying; add up to 100mL clean water per litre of product to achieve acceptable atomisation. Up to 50mL of water can be added per litre of product to ease application under very warm conditions.

Care and Maintenance

New paintwork should not be exposed to steam or condensation for 72 hours. Protect the coating against abrasive contact for 7 days. After 7 days the finish can be cleaned with a mild detergent solution and a soft cloth.

Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit www.paintback.com.au for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website www.haymespaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.



Australia's first family of paint. SINCE 1935

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymespaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version

Version and Date Issued	Version 2.2 Date 02/07/2024
Supersedes	Version 2.1 Date 20/05/2024

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3355
Freecall 1800 033 431
www.haymespaint.com.au