

HAYMES ANCILLARY

Gap Filler

Product Code: HGF

Product description

Haymes Gap Filler is a white, durable, paintable, one-part acrylic sealant/caulking compound for gaps and joining. It can be used both as a sealant or adhesive and is ideal for use where movement or vibration causes conventional fillers and putties to crack and fall out.



Key Features

- ✓ Easy to apply
- ✓ Flexible
- ✓ Paintable
- ✓ Smooth finish

Where to Use

Use on brick, wood, plasterboard, gypsum board products, and painted surfaces.

Not recommended for weatherboard overlaps or gaps between tongue and groove boards.

Typical properties

Clean-up	Water
Dry time	Dry time at 25°C: Water based paints: 30 minutes Solvent based paints: 48 hours
Colour	White
Sizes	450g

Surface Preparation

Ensure all surfaces are free from dust, oil, grease, dirt, old loose fillers or other elements that will affect adhesion.

1. Cut blind seal and fit nozzle
2. Trim end of nozzle to obtain correct bead width
3. Cured plug will form in nozzle after use, before reusing remove plug and extrude sealant.
4. Entire contents should be used within 12 months

Directions for use

Ensure all surfaces are free from dust, oil, grease, dirt, old loose fillers or other elements that will affect adhesion.

1. Apply sealant into crack or gap to be filled using an even pressure ensuring the sealant has surface contact.
2. Smooth off sealant with a putty knife or finger by dipping in clean water and applying lightly for a smooth even finish. Clean up excess sealant with a dry cloth.
3. Allow sealant / caulk to set for approximately 30 minutes before painting. If solvent-based paints are used, allow 48 hours. Sealant will cure at a depth of 1.5mm per day and 3-4mm per week depending on conditions (faster cure will occur in hot weather).

The use of flat water-based paints directly over the filler is not recommended as some cracking of the paint film may occur due to shrinkage. The use of an oil-based undercoat is recommended under these paints.

Storage

Store in a cool, dry place. Avoid direct sunlight.

Safety & First Aid

Avoid contact with skin and eyes by wearing appropriate protective clothing. On contact, uncured sealant can irritate eyes and sensitive skin. Avoid breathing vapours. Do not allow sealant to contaminate contact lenses. Keep out of reach of children.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If skin contact occurs, wipe off and wash with detergent solution. Product releases acetic acid while curing.

Protect our environment

Retain leftover product in a market sealed container for future use or disposal via special chemical waste collection programs. Dispose of empty containers in general waste.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
www.haymespaint.com.au

Date of Preparation 21/2/17