

PRODUCT DATA SHEET

HAYMES DESIGNER

FINISHES SPECIAL PAINT

GENERAL DESCRIPTION

A water-based high opacity grain filling paint for imparting Scandinavian, limed or chalky finishes or stucco finishes on interior walls.

PRODUCT CODE DFSPW

- Smooth subtle sheen finish
- Easy to use
- Superb coverage
- Fills end grain

WHERE TO USE

For Floors, walls, furniture and other interior surfaces.

TYPICAL PROPERTIES

Gloss	Flat, can be polished
Colour	White
Sizes	500ml, 4L
Clean Up	Water
Dry Time	Touch 20mins Recoat 2hours
Coverage	Up to 16m ² /L
Film Build	Wet 63um Dry 24um
Volume Solids	37.7%
VOC	40g/L
Application tools	Brush

SURFACE PREPARATION

General Surface Preparation	<ol style="list-style-type: none"> 1. Fill cracks, nail holes and imperfections with Haymes Unifill. 2. Scrape all loose/flaking paint. Sand smooth & dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. 3. Prime bare plaster, timber and metal areas with appropriate undercoats or primers.
Previously Painted Surfaces	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for general surface preparation. 2. Apply one coat of Haymes Acrylic Sealer Undercoat to any patched areas. 3. Sand gloss surfaces to a dull finish. Remove all dust 4. For surfaces in good condition no primers or undercoats are required.*
Plasterboard	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for general surface preparation.

	2. Apply one coat of Haymes Acrylic Sealer Undercoat.
Timber	1. Prepare any damaged areas as for general surface preparation. 2. Apply one coat of Haymes Acrylic Timber Primer.
Masonry, Brick, Concrete, Render	1. Wash with Haymes Unikleen & rinse with clean water. 2. Apply one coat of Haymes Acrylic Sealer Undercoat.

DIRECTIONS FOR USE

1. Do NOT apply if ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
2. The area to be painted must be clean and in sound condition. Very rough areas should be sanded smooth. Semi gloss and gloss finishes must be sanded to a dull finish.
3. Mix thoroughly with a broad flat stirrer.
4. Apply 2 – 3 coats by brush.
5. For a Scandinavian finish sand the final coat with 1200 grade sand paper to achieve a polished finish. Protect your work with a wax finish.
6. For stucco plaster, apply 2 – 3 coats using a criss cross brushing technique. Roughen the surface of the final coat with a trowel while wet. Allow to dry and finish with a colour wash to highlight the texture.
7. Please check the colour for accuracy prior to application. Haymes paint accepts no responsibility for the application of incorrect colours.

THINNING

Thinning is not generally recommended. On very porous surfaces add up to 100ml clean water per litre of paint. Up to 50ml of water can be added per Litre of paint to ease application under very warm conditions.

STORAGE

Protect from extremes of temperature. Store between 5°C and 30°C.

CARE AND MAINTENANCE

New paintwork should not be exposed to steam or condensation for 72 hours. Protect the coating against abrasive contact for 7 days. After 7 days the finish can be cleaned with a mild detergent solution and a soft cloth.

SAFETY DIRECTIONS

Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

FIRST AID INSTRUCTIONS

If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 1126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.

PROTECT OUR ENVIRONMENT

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via council recycling facilities.

MANUFACTURER'S COMMENT: This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible.

Dangerous Goods

NA

For further information or to place an order, call Service Express 1800 033 4331 or email info@haymespaint.com.au

Disclaimer

The information provided is correct at the time of preparation, however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.