

# Safety Data Sheet



Hazardous Substance, Dangerous Goods

## 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

**Product Name :** **Peel Away 1**

**Product Code :** **PA1**

**Product Use :** As a high quality water based caustic paint stripper for interior/exterior use for removing alkyd based paints from wood, bricks, cast iron and fibreglass.

**Company Name :** Haymes Paint

**ABN :** 14 004 201 638

**Address :** Waringa Drive, Wendouree Industrial Park, Victoria 3355, Australia.

**Emergency Telephone :** **03 5342 6200. Office Hours : 7.30am to 5.30pm Monday to Friday.**  
**Poisons Information Centre : 13 11 26** (From anywhere and anytime in Australia)

**Telephone Number/Fax :** Tel: 03 5342 6200. Office Hours : 7.30am to 5.30pm Monday to Friday.

## 2. HAZARDS IDENTIFICATION

**GHS Classification :** This material is hazardous according to health criteria of Safe Work Australia. HAZARDOUS SUBSTANCE.

**Hazard Pictograms :**



**SIGNAL WORD :**

**Danger**

**Hazard Classification :**

Corrosive to metals - Category 1  
Skin corrosion - Category 1A  
Serious eye damage/eye irritation - Category 1  
Specific Target Organ Toxicity ( Single Exposure ) - Category 3  
Specific Target Organ Toxicity ( Repeat Exposure ) - Category 2

**Hazard Statement(s) :**

H290 : May be corrosive to metals.  
H314 : Causes severe skin burns and eye damage.  
H318 : Causes serious eye damage.  
H335 : Exposure via inhalation may cause respiratory irritation.  
H373 : May cause damage to lungs and respiratory tract through prolonged and repeated exposure.

**Precautionary Statement(s) :**

**Prevention :**

P101 : If medical advice is needed, have product container or label at hand.  
P102 : Keep out of reach of children.  
P103 : Read label before use.  
P234 : Keep only in original packaging.  
P260 : Do not breathe dust/mist/spray.  
P261 : Avoid breathing vapours.  
P264 : Wash exposed skin thoroughly after handling.  
P271 : Use only outdoors or in a well-ventilated area.

**Response :**

P301+330+331 : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P310 : Immediately call a POISON CENTRE or doctor/physician.  
P303+350+351 : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P363 : Wash contaminated clothing before reuse.  
P305+351+338 : IF IN EYES, rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

**Product name :** **Peel Away 1**  
**Issued :** **2-2-23**  
**Version :** **2.0**

# Safety Data Sheet



**Response continued :** P310 : Immediately call a POISON CENTRE or doctor/physician.  
P321 : Specific treatment (see First Aid Measures on this SDS).  
P304+340 : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312 : Call a POISON CENTRE or doctor/physician if you feel unwell.  
P390 : Absorb spillage to prevent material damage.

**Storage :** P403+233 : Store in a well ventilated place. Keep container tightly closed.  
P405 : Store locked up.

**Disposal :** P501 : Dispose of contents/container in accordance with local, regional, national, international regulations.

**SUSMP Poisons Schedule :** **S6 Poison**

**Dangerous Goods Classification :** Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road and Rail".  
**Class 8 Corrosive liquid**

### 3. COMPOSITION INFORMATION

Chemical Entity	CAS NO	Proportion
Calcium hydroxide	1305-62-0	15 - 25 %
Sodium hydroxide	1310-73-2	5 - 15 %
Crystalline Silica (respirable fraction)	14808-60-7	<0.1 %
Ingredients determined not to be hazardous :	-	Balance
		100%

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre ( Phone Australia 131 126 ).

**Inhalation :** Remove victim from exposure. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin :** For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is available). If swelling, redness, blistering, or irritation occurs seek immediate medical assistance.

**Eye :** If in eyes, hold eyelids apart and rinse the eyes continuously with running water. Remove contact lenses if present and easy to do. Continue rinsing for several minutes until all contaminants are washed out completely. Immediately call a doctor. Continue rinsing.

**Ingestion :** If swallowed rinse mouth. Do NOT induce vomiting. Call a Poisons Information Centre or doctor.

**Symptoms and effects that may arise if the product is mishandled and overexposure occurs are :**

**Inhalation :** Irritation and coughing.

**Skin contact :** Burning pain, irritation, redness.

**Eye contact :** Burning pain, irritation, watering, redness.

**Ingestion :** Vomiting, dizziness, convulsions, abdominal pains and diarrhea.

**Advice to First Aiders :** Be aware of the material(s) involved, and wear protective equipment if there is a risk of inhalation or skin and eye contamination.

**First Aid Facilities :** Eye wash and normal washroom facilities.

**Advice to Doctor :** Treat symptomatically.

# Safety Data Sheet



## 5. FIRE-FIGHTING MEASURES

<b>Hazchem Code :</b>	<b>2X</b>
<b>Suitable extinguishing media :</b>	Use water fog to cool containers and prevent rupture and explosion by internal expansion.
<b>Specific hazards :</b>	Product is a caustic water based paste which does not sustain combustion. It can react with metals such as zinc, aluminium and tin and acids causing the generation of heat and possible explosions. Water diluted product from heat ruptured containers is also reactive. Spattered residues from an explosion will cause skin and eye burns.
<b>Fire fighting further advice :</b>	Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition. Prevent any possible contamination of drains and waterways.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Small Spills :</b>	Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.
<b>Large Spills :</b>	Shut off all possible sources of ignition. Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

**Dangerous Goods - Initial Emergency Response Guide No :** 37

## 7. HANDLING AND STORAGE

<b>Handling :</b>	Avoid skin and eye contact and inhalation of dust, vapour, mist or aerosols.
<b>Storage :</b>	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use. Check regularly for leaks.  This material is described as a Dangerous Good Class 8 Corrosive Liquid as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.  This material is a Scheduled Poison S6 and must be stored, maintained and used in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**Control Parameters :** No value assigned for this specific product by Safe Work Australia. However, Workplace Standard(s) for constituent(s) are :

Chemical Entity	TWA		STEL		Carcinogen Category	Notices
	ppm	mg/m3	ppm	mg/m3		
Calcium hydroxide	-	5	-	-	-	Sodium hydroxide
Sodium hydroxide	-	2	Peak limitation	-	-	-
Crystalline Silica (respirable fraction)	-	0.1	-	-	1A	

As published by Safe Work Australia

TWA - the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15-minute period, which should not be expected at any time during a normal eight-hour workday.

<b>Product name :</b>	<b>Peel Away 1</b>
<b>Issued :</b>	<b>2-2-23</b>
<b>Version :</b>	<b>2.0</b>

# Safety Data Sheet



These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If directions for use are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Engineering Controls :** Ensure ventilation is adequate and that air concentrations are controlled below quoted Workplace Exposure Standards. Close with lid when not in use.

**Personal protection equipment :** **OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.**

Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment.

**Hygiene measures :** Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance :</b>	White viscous paste.
<b>Odour :</b>	Slight
<b>Odour Threshold :</b>	Not Available
<b>Solubility :</b>	Soluble in water.
<b>Specific Gravity (20 °C) :</b>	1.2 - 1.5
<b>Relative Vapour Density (air=1) :</b>	Approximately 1
<b>Vapour Pressure (20 °C) :</b>	As for water
<b>Flash Point (°C) :</b>	Not Applicable
<b>Flammability Limits (%) :</b>	Not Applicable
<b>Autoignition Temperature (°C) :</b>	Not Applicable
<b>Melting Point/Range (°C) :</b>	Not Applicable
<b>Boiling Point/Range (°C) :</b>	100°C
<b>Decomposition Point (°C) :</b>	Not Available
<b>pH :</b>	10-12
<b>Viscosity (Kinematic @ 40 °C) :</b>	Not Available
<b>Total VOC (g/litre) :</b>	Not Available

## 10. STABILITY AND REACTIVITY

<b>Reactivity :</b>	The solution in water is a strong base, it reacts violently with acid and is corrosive.
<b>Chemical stability :</b>	Stable under normal conditions.
<b>Hazardous reactions :</b>	Addition of chemicals such as acids may cause the generation of heat and possible explosion.
<b>Conditions to avoid :</b>	Contact with incompatible materials.
<b>Incompatible materials :</b>	Do not put into contact with metals such as aluminium, zinc or tin.
<b>Hazardous decomposition products:</b>	Will react with aluminium to produce hydrogen which is flammable and explosive.

**Product name :** Peel Away 1  
**Issued :** 2-2-23  
**Version :** 2.0

## 11. TOXICOLOGICAL INFORMATION

### Information on toxicological effects :

<b>Acute toxicity - Inhalation :</b>	Insufficient information available for classification.
<b>Acute toxicity - Skin contact :</b>	Insufficient information available for classification.
<b>Acute toxicity - Ingestion :</b>	This product has been classified as Non-hazardous. Acute Toxicity Estimate based on ingredients : LD50 > 2000 mg / kg.
<b>Skin corrosion/irritation :</b>	This product is classified as a Category 1A Hazard. Causes severe skin burns and eye damage.
<b>Serious eye damage/irritation :</b>	This product is classified as a Category 1 Hazard. Causes serious eye damage.
<b>Respiratory Sensitisation :</b>	This product has been classified as Non-hazardous.
<b>Skin Sensitisation :</b>	This product has been classified as Non-hazardous.
<b>Aspiration hazard :</b>	This product has been classified as Non-hazardous.
<b>Specific target organ toxicity ( single exposure ) :</b>	This product is classified as a Category 3 Hazard. Exposure via inhalation may affect the respiratory tract.
<b>Chronic Toxicity :</b>	
<b>Mutagenicity :</b>	This product has been classified as Non-hazardous.
<b>Carcinogenicity :</b>	This product has been classified as Non-hazardous.
<b>Reproductive toxicity:</b>	This product has been classified as Non-hazardous.
<b>Specific target organ toxicity ( repeat exposure ) :</b>	This product is classified as a Category 2 Hazard. Repeated or prolonged exposure to dust or mist via inhalation may cause damage to the lungs.
<b>Likely routes of exposure :</b>	Routes of entry anticipated : Inhalation, skin and eye.

No adverse health effects expected if material is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are :

### Potential acute health effects :

<b>Inhalation :</b>	Inhalation of dust or mist may cause irritation of respiratory tract.
<b>Skin contact :</b>	Corrosive to skin - may cause skin burns. Contact with skin will result in severe irritation.
<b>Eye contact :</b>	Corrosive to eyes. Risk of serious damage to eyes.
<b>Ingestion :</b>	Chemical burns of the digestive tract.

### Symptoms related to the physical, chemical and toxicological characteristics :

<b>Inhalation :</b>	Irritation and coughing.
<b>Skin contact :</b>	Burning pain, irritation, redness.
<b>Eye contact :</b>	Burning pain, irritation, watering, redness.
<b>Ingestion :</b>	Vomiting, dizziness, convulsions, abdominal pains and diarrhea.

### Delayed and immediate effects and also chronic effects from short and long term exposure :

<b>Inhalation :</b>	Over exposure from prolonged or repeated inhalation of dust, mist or spray can cause damage to lungs and respiratory tract. However, due to the nature of the product and typical methods of use, adverse health effects are not anticipated.
<b>Skin contact :</b>	Prolonged or repeated contact can lead to irritation and/or irritant contact dermatitis.
<b>Eye contact :</b>	Permanent eye damage, including loss of sight, may occur.
<b>Ingestion :</b>	No information available for this product.

---

<b>Product name :</b>	<b>Peel Away 1</b>
<b>Issued :</b>	<b>2-2-23</b>
<b>Version :</b>	<b>2.0</b>

## 12. ECOLOGICAL INFORMATION

Avoid contaminating drains and waterways.

<b>Acute aquatic hazard :</b>	No information available to complete an assessment.
<b>Long-term aquatic hazard :</b>	No information available to complete an assessment.
<b>Ecotoxicity :</b>	No information available.
<b>Persistence and degradability :</b>	No information available.
<b>Bioaccumulative potential :</b>	No information available.
<b>Mobility :</b>	No information available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled dispose in accordance with local, regional, national and international regulations.

## 14. TRANSPORT INFORMATION

<b>Road and Rail Transport :</b>	Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road and Rail".
<b>UN number :</b>	3266
<b>Dangerous Goods Class :</b>	8
<b>Packing Group :</b>	II
<b>Hazchem Code :</b>	2X
<b>Emergency Response Guide No :</b>	37
<b>Proper Shipping Name :</b>	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
<b>Segregation Dangerous Goods :</b>	Not to be loaded with explosives ( Class 1 ), dangerous when wet ( Class 4.3 ), oxidising agents ( Class 5.1 ), organic peroxides ( Class 5.2 ), if the Class 6 dangerous goods are cyanides - ( Class 6 ), radioactive substances ( Class 7 ), any Class 8 strong alkalis, foodstuffs or food packaging, however exemptions may apply.
<b>Marine Transport :</b>	Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code ( IMDG ) Code) for transport by sea.
<b>UN number :</b>	3266
<b>Dangerous Goods Class :</b>	8
<b>Packing Group :</b>	II
<b>Hazchem Code :</b>	2X
<b>Emergency Response Guide No :</b>	37
<b>Proper Shipping Name :</b>	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
<b>Air Transport :</b>	Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
<b>UN number :</b>	3266
<b>Dangerous Goods Class :</b>	8
<b>Packing Group :</b>	II
<b>Hazchem Code :</b>	2X
<b>Emergency Response Guide No :</b>	37
<b>Proper Shipping Name :</b>	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

---

<b>Product name :</b>	<b>Peel Away 1</b>
<b>Issued :</b>	<b>2-2-23</b>
<b>Version :</b>	<b>2.0</b>

# Safety Data Sheet



## 15. REGULATORY INFORMATION

**This product/constituent(s) is/are covered by the following requirements :**

This material is hazardous according to health criteria of Safe Work Australia. HAZARDOUS SUBSTANCE.

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road and Rail".

The Standard for the Uniform Scheduling of Medicines and Poisons No. 37.

**S6 Poison**

All the constituents of this product are listed on the Australian Inventory of Industrial Chemicals ( AIIC ), or exempted.

## 16. OTHER INFORMATION

This Safety Data Sheet has been prepared by Haymes Paint Technical Department.

**Reason(s) for issue :** 5 Yearly Revision.

**Literature References :** Globally Harmonised System of Classification and Labelling of Chemicals (GHS), 7th revised edition, United Nations, 2017.

Model Codes of Practice: Classification and labelling of workplace hazardous chemicals, and preparation of safety data sheets for hazardous chemicals - Safe Work Australia, July 2020.

Australian Inventory of Industrial Chemicals ( AIIC ).

European Chemicals Agency ( ECHA ).

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Haymes Paint cannot anticipate or control the conditions under which the product may be used, prior to usage, review the SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

---

**Product name :** Peel Away 1  
**Issued :** 2-2-23  
**Version :** 2.0